General catalog for Compressed Air, Gas and Vacuum Solutions



Download a QR Reader and scan the code to read this catalog on your tablet.





Sustainable Productivity

FOR 140 YEARS, WE HAVE INCREASED OUR CUSTOMER'S PRODUCTIVITY.

Atlas Copco is an industrial group with world-leading position in products and services that deliver sustainable productivity. The company was founded in Sweden in 1873, celebrating 140 years of successful business in 2013.

Today, we have sale and service operations in more than 170 countries. The voices of our customers around the world are very important to us. By listening to customers we learn about what we do well and what we need to improve.

Each year, we open new customer centers in emerging markets, always with a long-term commitment to local customers and partners.

Atlas Copco Compressor Technique provides gas and process compressors, expanders, air and gas treatment equipment as well as air management systems and service for industrial applications.

In this catalogue you will find our comprehensive offering of energy efficient compressed air, gas and vacuum solutions to help improve customers sustainable productivity.

Drivers of innovation from idea to customer benefit



We want to put our customers ahead of their competition. For Atlas Copco, energy efficiency is always a top priority and a strong incentive to seek new and better solutions.

Our continuous drive to further reduce the carbon footprint, to find new and better ways of utilizing materials and to minimize waste has resulted in numerous innovations.

A lot of new opportunities relate to the development of intelligent controls and monitoring systems. Further development of oil-free and low pressure technology will open up opportunities to reach new heights in air efficiency.

For the oil-injected technology, continuous innovations and new solutions make this technology a strong contributor to customer efficiency and energy savings for the future.

An industry benchmark

Our achievements are also recognized externally and we are perceived as an industry benchmark in many areas.

For example, we are listed in the Dow Jones Sustainability index as one of the world's most innovative companies. And at the World Economic Forum in Davos in Switzerland we were listed as the 10th most sustainable company in the world. We have been on that list six times.



ISO 9001 We have the quality leading role in the Industry. We trust the customer introduced.



ISO 14001 The Environmental Management System is an integrated part of any business process at Atlas Copco Airpower.



OHSAS 18001:1999 International Labour and Health and Safety Management system

Sustainable development

Atlas Copco has set very high environmental targets for our operations as well as for our equipment.

By making our equipment as energy efficient as possible, we help our customers to reduce their impact on the environment. This can help them to promote their products as sustainable solutions in the marketplace.

For our operations, we are continuously reducing the environmental impact in key areas such as energy consumption, water consumption, CO_2 emissions, and waste.

A large majority of our employees already work in companies that are triple certified (ISO 9001, ISO 14001 and OHSAS 18001). By the end of 2013 Compressor Technique is committed to having triple certifications for all of our operations.

Energy efficiency is our benchmark



Compressed air is simply indispensable in many processes today, so it is all the more astonishing that many businesses have long since disregarded the most significant cost factor in compressed air supply - the cost of energy. Approximately 80% of the total life-cycle cost is apportionable to energy! For this reason, Atlas Copco has been striving for greater energy efficiency for many years, with the aim of boosting our customers' productivity in the long term.

"Committed to sustainable productivity" is the standard we bear. Nevertheless, we are always seeking to develop new, more efficient drive systems and to better tailor individual components to overall designs.

Today, operators are able to run their systems consistently at the optimum operating point and to ensure that all machines are used to full capacity. The result in both cases is a lower electricity bill. When scrutinizing the lifecycle costs of compressed air systems, investments in energy efficient systems always pay off.

This is particularly true when it comes tov heat recovery: Compressors generate heat energy which can be harnessed for other purposes in the operating environment. We have the experience and technical means at our disposal to implement appropriate solutions. Electrical energy that has been expended once, for instance, can be reused in the form of thermal energy: To bolster hall heating, heat warm water or warm up processes. Heat recovery quickly pays for itself. We offer compressors already equipped with these systems, but there are also retrofitting options available for existing systems.



Variable Speed Drive (VSD): reducing energy costs



In the company's relentless quest to cut costs and develop innovative products, Atlas Copco unveiled the pioneering variable speed drive (VSD) technology in 1994. VSD delivers considerable energy savings, and in doing so preserves the environment for future generations. By continually investing in research and development, Atlas Copco is able to offer a wide range of integrated VSD compressors.

Fluctuating compressed air demand in 92% of all systems

In almost every production environment, air demand fluctuates based on a number of factors (time of day, week or even month). Extensive measurements and studies of compressed air demand profiles show that compressed air demand varies considerably in 92% of all compressor and fan systems. Compressed air demand is found to be relatively stable in just 8% of all systems. Tests have indicated that VSD compressors and fans save energy in these situations too.

Profile 1



64% of all systems

 Factory in 24-hour operation: low demand at night, high demand during the day



Profile 2



- 28% of all systems
- Factory in two-shift operation, inoperative at weekends: irregular air demand

Cost over entire service life of compressor and fan -35% energy savings on average

VSD technology from Atlas Copco adjusts the motor speed to the air demand automatically, achieving substantial energy savings of 35% on average. Over the entire service life of a compressor or fan,

Energy savings with VSD

Investment

Watch This Sign!

Profile 3



- 8% of all systems
- Factory in two-shift operation, inoperative at weekends: typical area of operation at "constant" speed

costs can be reduced on average by 22%. What's more, thanks to lower system pressure, VSD dramatically reduces the energy requirements in the overall production process.

The leader in oil-free compressed air technology



Oil-free air is used in all kinds of industries where air quality is paramount for the production process and end product. These applications include food and beverage processing, the pharmaceutical industry (manufacturing and packaging), wastewater treatment, chemical and petrochemical processing, semiconductor and electronics manufacturing, the medical sector, automotive paint spraying, textile manufacturing and many more.Contamination by even the smallest quantities of oil can result in costly production downtime and product spoilage, making **Class 0** an industry standard.

First in oil-free air technology

Over the past sixty years Atlas Copco has pioneered the development of oil-free air technology, resulting in a range of air compressors and blowers that provide 100% pure, clean air. Through continuous research and development, Atlas Copco achieved a new milestone, setting the standard for air purity as the first manufacturer to be awarded ISO 8573-1 CLASS 0 certification.

Eliminating any risk

As the industry leader committed to meeting the needs of the most demanding customers, Atlas Copco requested the renowned TÜV institute to type-test its range of oil-free compressors and blowers. Using the most rigorous testing methodologies available, all possible oil forms were measured across a range of temperatures and pressures. The TÜV found no traces of oil at all in the output air stream. Thus Atlas Copco is not only the first compressor and blower manufacturer to receive CLASS 0 certification, but also exceeds ISO 8573-1 CLASS 0 specifications.

CLASS 0 means:

- ✓ Zero risk of contamination.
- Zero risk of damaged or unsafe products.
- ✓ Zero risk of losses from operational downtime.
- Zero risk of damaging your company's hard-won professional reputation.



Download a QR Reader and scan the code for more infomation about www.classzero.com.



CLASS	Concentration total oil (aerosol, liquid, vapor) mg/m³									
0	As specified by the equipment user or supplier and more stringent than class 1									
1	< 0.01									
2	< 0.1									
3	<1									
4	< 5									

Current ISO 8573-1 (2010) classes (the five main classes and the associated maximum concentration in total oil content).

Service and optimization for your compressed air system





Bottlenecks quickly eliminated

Atlas Copco Rental delivers 100% oil-free compressed air to companies in industry. Where additional demand exists for power or air, or where processes cannot be interrupted for the maintenance or repair of internal systems, Atlas Copco Rental provides support with its complete rental solutions. Our solutions guarantee the least possible disruption to your production process. Our growing portfolio of services built on expert knowledge and experience, which is widely recognized as "industry leading", also includes other special applications, such dehydration, pressure tests, cleaning of oil and gas pipelines at sea, and much more. Sustainable economic performance, reduced energy costs and improved profitability: Our services get you there faster. Operators' unique requirements for servicing and maintenance are just as varied as the range of compressed air systems available. These requirements range from original replacement parts and premium maintenance agreements to system optimization and remote monitoring. With our perfectly tailored and extendable aftermarket products, we have the ideal solutions for worry-free compressed air systems and high availability.

Our range of services and our experienced, qualified service team are at your disposal regardless of whether you have purchased a compressor or dryer from us: Let us optimize your energy consumption, boost your availability and safeguard the reliability and efficient operation of your compressed air system for many years, or even decades, to come. We can perform regular inspections of your systems, enable you to take advantage of the technical progress made and help you to steadily boost your efficiency. If required, we can also remotely monitor your compressed air system centrally via the Internet, 24 hours a day, 365 days a year, allowing you to depend on the productivity and availability of your system at all times.

Table of Content

ARTICLE	PAGE Nos.
OVERVIEW	2
Drivers of innovation - from idea to customer benefit	3
Energy efficiency is our benchm12 to 13	4
Variable Speed Drive (VSD): Reducing energy costs	5
The leader in oil-free compressed air technology	6
Service and optimization for your compressed air system	7
OIL-INJECTED COMPRESSORS	12 - 13
Automan: Oil-lubricated aluminium piston compressors, 1.5-7.5 kW / 2-10 hp	14 - 16
LE/LT: Industrial oil-lubricated aluminium piston compressors	17 - 20
GX 2-11: Oil-injected rotary screw compressors, 2-11 kW / 3-15 hp	21 - 22
GA 5-11/GA 5-15 VSD: Oil-injected rotary screw compressors, 5.5-11 KW / 7.5-15 hp	23 - 25
GA 11+-30/GA 15-30 VSD: Oil-injected rotary screw compressors, 11-30 kW / 15-40 hp	26 - 30
GA 15-22: Oil-injected rotary screw compressors, 15-22 kW / 20-30 hp	31 - 32
GA 30+-90 / GA 37-90 VSD: Oil-injected rotary screw compressors, 30-90 kW / 40-125 hp	33 - 36
GA 90+-160+ / GA 110-160 VSD: Oil-injected rotary screw compressors, 90-160 kW / 125-200 hp	37 - 39
GA 200-500 (VSD)	40 - 42
GR 110-200: Oil-injected rotary screw compressors, 110-200 kW / 150-270 hp	43 - 44
B&D: Oil-lubricated high-pressure reciprocating compressors, up to 450 bar (a) (6500 psia), 37-150 kW	45
CU/CT/CN: Oil-lubricated high pressure trunk-piston compressors, up to 351 bar(a) 5090 psia), 22-200 kW	46
GG: Oil-lubricated gas screw compressors, 16 bar(a) (232 psia)	47
S100/S750: Car and bus refueling stations	48
OIL-FREE COMPRESSORS	49 - 52
LFx 0.7 - 2.0 series: Compact oil-free piston compressors, 0.5-1.5 kW / 0.7-2 hp	53 - 54
LF: Industrial oil-free aluminum piston compressors, 1.5-7.5 kW / 2-10 hp	55 - 56
SF 1-22: Oil-free scroll compressors, 1.5-22 kW / 2-30 hp	57 - 59
AQ 30-55 / 15-55 VSD: Water-injected screw compressors, 15-55 kW / 20-75 hp	60 - 62
ZT 15-22, ZR/ZT 30-45, ZR/ZT 22-37-55 VSD: Oil-free rotary tooth compressors, 15-55 kW / 20-75 hp	63 - 64
Z 55-900 (VSD): Oil-free air- and water-cooled rotary screw compressors, 55-935 kW / 75-1253 hp	65 - 75
ZH: Oil-free centrifugal compressors, 400-2750 kW, 500-3500 hp	76 - 78
ZH 350+: Oil-free high-speed drive centrifugal compressors, 350 kW, 470 hp	79
OIL-FREE COMPRESSORS FOR LOW & HIGH PRESSURE APPLICATIONS	80 - 83
ZE/ZA (VSD): Oil-free rotary screw compressors, 22-500 kW / 40-700 hp	84
ZS: Oil-free positive displacement screw blowers, 18-160 kW, 25-215 hp	85

ARTICLE	PAGE Nos.
ZS+ VSD: Oil-free Variable Speed Drive positive displacement screw blowers, 22-160 kW, 40-215 hp	86
ZB 100-160 VSD: Oil-free Variable Speed Drive centrifugal air compressors, 100-160 kW, 135-215 hp	87
DM: Oil-less reciprocating trunk-piston compressors, up to 351 bar (a) (5090 psia), 30 kW	88
DX/DN: Oil-free reciprocating piston compressors, up to 45 bar (652 psig) 30-315 kW /40-422 hp	89
HX HN: Oil-free reciprocating compressors	90
P: Oil-free reciprocating piston compressors, up to 40 bar (580 psig), 37-275 kW /50-368 hp	91 - 92
ZD: Oil-free screw and reciprocating piston compressors, up to 40 bar (580 psig), 136-770 kW / 182-1032 hp	93 - 94
MEDICAL EQUIPMENT	95 - 96
MED / MED+: Medical air purifiers	97 - 98
GA MED: Screw compressors for medical applications	99 - 100
uAIR: Medical Air Plant	101 - 102
mVAC: Medical vacuum systems	103 - 105
Oxyplant: Medical oxygen plant	106 - 107
COMPRESSORS FOR RAILWAY, MARINE AND SKI SLOPE APPLICATIONS	108 - 109
AIR AND GAS TREATMENT	111 - 114
FX: Refrigerant air dryers, 7-1236 l/s, 14-2516 cfm	115 - 116
FD: Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm	117 - 121
CD: Heatless desiccant air dryers, 360-1600 l/s, 763-3392 cfm	122
CD+: Heatless desiccant air dryers, 25-1400 l/s, 53-2968 cfm	123 - 124
BD: Blower purge desiccant air dryers, 360-1600 l/s, 763-3392 cfm	125 - 126
BD+: Blower purge desiccant air dryers, 100-3000 l/s, 212-6360 cfm	127 - 128
MD: Heat of compression rotary drum dryers, 88-2500 l/s, 185-5297 cfm	129 - 130
XD: Heat-of-compression desiccant air dryers, 1400-7000 l/s, 2970-14840 cfm	131 - 132
SD: Membrane dryers	133 - 134
BAP / BAP+: Purification units for breathable air	135 - 136
Compressed air purification: Something else you should consider	137
NGP series: PSA nitrogen generators, capacity 1-300 l/s, flow 4-1100 Nm ³ /h purity 95-99.999%	138 - 139
NGM 1-7: Membrane nitrogen generators, capacity 1.4-140 l/s, flow 5-500 Nm ³ /h, purity 95-99%	140 - 141
OGP series: PSA oxygen generators, capacity 0.6-56 l/s, flow 2-200 Nm ³ /h, purity 90-95%	142 - 143
DD+, DDp+, PD+, QD+ filters: Compressed air filters	144 - 146
WSD 25-750 / WD 80 / EWD 50-1500: Water separators and drains	147 - 148
QDT: Activated carbon tower, 20-310 l/s, 42-657 cfm	149 - 150
OSC and OSD: Oil/water separator systems for the condensate treatment	151 - 152

Table of Content

ARTICLE	PAGE Nos.
VACUUM PUMPS	153 - 154
GV 20-300: Oil-sealed rotary vane vacuum pumps, 20-365 m³/h, 12-215 cfm	155 - 156
GV 630-4800: Oil-sealed rotary screw vacuum pumps, 557-5734 m ³ /h, 328-3377 cfm	157 - 158
TOTAL CUSTOMER CARE	159 - 160
Save energy	161 - 163
Monitor your products	164
Customer support plans	165 - 168
Upgrade your product	169 - 170
Genuine parts	171 - 179
Airnet	180

OIL-INJECTED COMPRESSORS

Our oil-lubricated compressors are the best choice for all industrial applications which require a general compressed air quality.

Oil-injected compressors

Our oil-lubricated compressors are the best choice for all industrial applications requiring a general compressed air quality.

We offer durable piston compressors (such as the LE/LT series) and premium screw compressors with high volume flows and efficiencies (GA series, up to 14 bar and GG gas screw up to 16 bar). If somewhat higher pressures are required, our two-stage GR screw compressors are also available (13 to 20 bar). For pressures up to 350 bar, our C series compressors are available for air and gas applications.

Average cost and power saving potential with VSD with a standard compressor over the entire service life



Direct power savings of 35% on average

- Minimal unloading losses
- Volume flow adjusts to current compressed air requirement
- No wasteful idling
- The precise pressure control in the VSD compressors enables a narrow pressure band and a low working pressure, which results in a lower power requirement

Whether you cast large diesel engines or vibration dampers for the automotive industry, clean metal parts with sanding machines, or manufacture construction machinery, bicycles, bridge components or household china, we can supply you with the compressed air and gas system you need.

The compressor, the refrigerant dryer, all the filters and condensate drains, the control system, the piping, and even the connections. (Almost) all of them can be integrated into one machine according to your needs – Always reliable and robust, made up of thousands of proven components and extremely efficient.

Wherever a compressed air supply is needed, we have the right equipment. Whether it is shipping companies looking for a compressed air supply for ships, or rolling stock manufacturers, suppliers of coke oven machinery, or providers of welding beads for pipeline construction in the desert. Our compressors supply the right air for every purpose and are extremely reliable, even in the harshest conditions.

Whether our customers are medium-sized businesses or global companies with specific requirements, we can adapt our organization to meet these specific requirements.

We have separate engineering teams for marine and railway settings, and have developed specific products for these industries. In the railway industry, for example, our screw compressors supply working air for braking or to control the valves. Our piston compressors support the main engines on ships when they start up; our equipment can provide the nitrogen required on cargo ships - to extend the shelf life of food being transported by sea, or for cleaning oil pipeline systems. And our spare parts are available worldwide.

Indirect power savings

- The lower working pressure through VSD leads to additional savings of up to 10%
- Lower power requirement for existing base load machines
- Lower leakage losses; e.g., v at 6 bar, the air losses are 13% lower than at 7 bar
- Most compressed air applications consume less air at a lower pressure



Automan

Oil-lubricated aluminium piston compressors, 1.5-7.5 kW / 2-10 hp

High performance, easy operation

AUTOMAN compressors are built to provide maximum safety for the user. They require minimal space, are easy to maneuver, and are supplied as a complete ready-to-use system.

- AF 20 30E | Page 15
- AH 10 20E | Page 14
- AC 20 100E | Page 15



GX 2-11

Oil-injected rotary screw compressors, 2-11 kW / 3-15 hp

Proven industrial technology for your workshop

The proven Atlas Copco screw technology is characterized by optimum performance, high reliability, long service life, and low maintenance requirements.

• GX 2-11 | Page 21 - 22



LE/LT

Industrial oil-lubricated aluminium piston compressors

Powerful, durable and reliable

Ideal for trade and industry. Can be individually combined. For smaller air volumes and high performance, with low energy costs and low environmental impact.

• LE/LT 2-20 | Page 17 - 20



GA Series

Oil-injected rotary screw compressors

Robust work horses

This series offers the perfect combination of innovative screw technology, environmentally-friendly design, and outstanding quality with minimal operation and installation costs. Numerous variants and options offer the ideal compressor for any use.

- GA 5-11/GA 5-15 VSD | Page 23 25
- GA 11+-30/GA 15-30 VSD | Page 26 30
- GA 30+-90 / GA 37-90 VSD | Page 33 36
- GA 90+-160+ / GA 110-160 VSD | Page 37 39
- GA 200 500 (VSD) | Page 40 42



GA VSD Series

 $\label{eq:complexity} \text{Oil-injected rotary screw compressors}$

Power savings of 35% on average

Adapting to the fluctuating compressed air requirement. Precise pressure control, flexible operation, and flexible pressure selection result in considerable power savings.

- GA 5-11/GA 5-15 VSD | Page 23 25
- GA 11+-30/GA 15-30 VSD | Page 26 30
- GA 30+-90 / GA 37-90 VSD | Page 33 36
- GA 90+-160+ / GA 110-160 VSD | Page 37 39
- GA 200-500 (VSD) | Page 40 42



High Pressure range

Oil-lubricated high pressure compressors

A complete offering up to 500 bar.

- GR 110-200 | Page 43 44
- **B&D** | Page 45
- CU/CT/CN | Page 46
- **GG** | Page 47
- S100/S750 | Page 48

Automan Oil-lubricated aluminium piston compressors, 1.5-7.5 kW / 2-10 hp

Automan oil-lubricated aluminium piston compressors are solid, robust and reliable. They are designed for professional applications where they offer troublefree performance even under demanding circumstances.

CUSTOMER BENEFITS

• **Solid reliability**— The Automan tank is powder coated, giving it the best protection against damage and corrosion. Its block is slow running, which extends its lifetime.

• **Durable components** – The heavy-duty air intake filter is built to work reliably in dusty conditions and offers long service intervals. The TEFC motor is weather resistant thanks to Class F insulation and IP54 protection. All models are equipped with a pressure reducing valve with quick coupling and D.O.L with a built in pressure differential switch making the compressor complete, ready to operate.

• **Minimum maintenance** – All Automan models are built for easy maintenance. The Automan oil, approved by Atlas Copco, is the guarantee for extended compressor lifetime.



AH 15 E 24



AH 20 E 6



AH 10 E 6



AH 15 E 6

AH series oil-free 230 Volt 1 phase - 8 bar(e)/115 psig

Direct drive - portable or mobile - 6 or 24 l horizontal receiver

Model	Instal	led power	Piston o	Piston displacement		Cylinders	Stanes	Mass		
	hp	kW	l/s	cfm	. b	eyere	oragoo	kg	lbs	
AH 10 E 6 silent, portable	1	0.75	1.4	2.9	1450	1	1	15	33	
AH 15 E 6 portable	1.5	1.1	2.6	5.6	3400	1	1	10	22	
AH 15 E 24 mobile	nobile 1.5 1.1 2.6		5.6	3400	1	1	18	40		
AH 20 E 6 roll cage, portable	2	1.5	3.2	6.8	2850	1	1	22	48	



AF 20 E 6







AF 30 E 22



AF 20 E 24



AF 30 E 24

AF series 230 Volt 1 phase - 8 bar(e)/115 psig for AF 20 E or 10 bar(e)/145 psig for AF 30 E

Direct drive - stationary or mobile $-\,2\,x$ 11, 6, 10, 24, 50 or 90 l receiver

Model	Installe	d power	Piston dis	splacement	Free A	ir Delivery		Culindara	Stores
woder	hp	kW	l/s	cfm l/s cfm ^{rpm}		rpm	Cynnuers	Stages	
AF 20 E	2	1.5	3.2	6.8	1.7	3.6	2850	1	1
AF 30 E	3	2.2	5.2	11	3.1	6.6	1450	2	1



AC series 230 Volt 1 phase - 10 bar(e)/145 psig

Belt drive - stationary or mobile - 27, 50, 90 or 200 l horizontal alternatively 150 l vertical receiver

Model	Installed power		Piston displacement		Free Air	Delivery		Outlin dama	Stance	
wodei	hp	kW	l/s	cfm	l/s	cfm	rpm	Cylinders	Stages	
AC 20 E	2	1.5	3.1	6.6	1.8	3.8	916	2	1	
AC 30 E	3	2.2	5.8	12.3	4.2	8.9	1059	2	1	

AC series 230 or 400 V 3 phase - 10 bar(e)/145 psig for AC 20-30 E, 11 bar(e)/160 psig for AC 40-100 E

Belt drive - stationary or mobile – 50, 90, 200, 270 or 500 l horizontal alternatively 270 l vertical receiver - Star Delta starter from 5.5 hp

Model	Installed power		Piston displacement		Free Air	Delivery		Culindara	Stanes	
woder	hp	kW	l/s	cfm	l/s	cfm	rpm	Cynnaers	Stages	
AC 20 E	2	1.5	3.8	8.1	2.2	4.7	1120	2	1	
AC 30 E	3	2.2	5.8	12.3	4.2	8.9	1059	2	1	
AC 40 E	4	3	7.7	16.3	5.7	12.1	1303	2	2	
AC 55 E	5.5	4	10.6	22.4	6.9	14.6	975	2	2	
AC 75 E	7.5	5.5	13.9	29.5	10.7	23.3	663	2	2	
AC 100 E	10	7.5	16.7	35.4	12.9	27.5	795	2	2	

AC series 230 or 400 V 3 phase - 14 bar(e)/203 psig Belt drive - stationary - 300 or 500 I horizontal alternatively 270 I vertical receiver – Star Delta starter from 5.5 hp

Model	Installed power		Piston dis	placement	Free Air	Delivery		Cylinders	Stagos	
Wouer	hp	kW	l/s	cfm	l/s	cfm	rpm	Gynnuers	Jacuyes	
AC 40 T	4	3	5.3	11.2	3.9	8.3	896	2	2	
AC 55 T	5.5	4	8.1	17.2	5.3	11.2	750	2	2	
AC 75 T	7.5	5.5	11.2	23.6	8.6	18.2	530	2	2	
AC 100 T	10	7.5	13.9	29.5	10.7	22.7	663	2	2	



Petrol	&	diesel	series	10-14	bar/145	- 203 p	JSi
--------	---	--------	--------	-------	---------	----------------	-----

Petrol & Diesel Driven Compressors	Model	Motor			Vessel	Pressure		FAD @	Weight	
Туре		hp	kW	Fuel	İtr	bar	psi	l/m	cfm	
AC40E100 Petrol	Mobile	3,5	2,6	Petrol	100	10	145	188	6,7	71
AC55E50 Petrol	Mobile	4,8	3,6	Petrol	50	10	145	251	8,9	73
AC55E100 Petrol	Mobile	4,8	3,6	Petrol	100	10	145	251	8,9	94
AC55E200 Petrol	Mobile	4,8	3,6	Petrol	200	10	145	251	8,9	120
AC55E11+11 Petrol	Mobile	4,8	3,6	Petrol	11+11	10	145	251	8,9	70
AC55E11+11R Petrol	Rollbar	4,8	3,6	Petrol	11+11	10	145	254	9,0	70
AC71E25+25R Petrol	Rollbar	7,1	5,3	Petrol	25+25	10	145	416	14,7	143
AC71T270 Petrol	Stationary	7,1	5,3	Petrol	270	14	203	347	12,3	223
AC100T270 Petrol	Stationary	10,7	8,2	Petrol	270	14	203	571	20,2	235
AC71T270 Diesel	Stationary	7,5	5,5	Diesel	270	14	203	485	17,1	239
AC110T270 Diesel	Stationary	10,9	8,2	Diesel	270	14	203	762	26,9	258
AC75T270 Diesel 2KvA	Stationary	7,5	5,5	Diesel	270	14	203	302	10,7	265
AC110T270 Diesel 2KvA	Stationary	10,9	8,2	Diesel	270	14	203	439	15,5	270
Silencer extension kit Petrol	Option	-	-	Petrol	-	-	-	-	-	-
Silencer extension kit Diesel	Option	-	-	Diesel	-	-	-	-	-	-

LE/LT Industrial oil-lubricated aluminium piston compressors

Looking for a durable, high-performance compressed air solution for your specific industrial application? Designed with the highest attention to quality, Atlas Copco's LE/LT oil-lubricated aluminium piston compressors for exceptional stand reliability and low operating costs. LE is your compressor for 10 bar and the LT for 15, 20 or 30 bar applications. Incorporating state-of-the-art technology, LE/LT compressors deliver the lowest operating temperatures in the industry, while offering quality air with very low oil carryover. Proven design and high-quality materials ensure performance and extra long life. The LE/LT range is suitable for stand-alone use or easy integration in your OEM product. Atlas Copco also offers an oil-free piston compressor: the LF.



CUSTOMER BENEFITS

Solid reliability – Thanks to a unique, robust design and the optimal combination of quality materials, LE/LT compressors offer improved performance and extended product life. The fan is designed for an optimal cooling air flow.

Low running costs - Operational costs are limited and due to the use of highly durable components the compressors have a long lifetime. Easy maintenance- All components and service points are easily accessible.

Saving floor space – The compressor block which is directly coupled to the motor is manufactured using lightweight materials. This provides excellent cooling characteristics: ideal for integration with limited space requirements.



- Oil-lubricated or 100% oil-free (see LF compressors)
- Direct drive
- Working pressure up to 30 bar
- IP-55 electric motors with ISO Class F

Aluminum construction

The aluminum casing with cooling fins, supported by a large fan, ensures optimum heat dissipation.

Valve assembly

The patented stainless "Flexi-Disc Valve Assembly" provides a consistent air flow. The system also has a special construction designed for very long operating times

Piston – cylinder assembly

The ideal combination of cylinders and pistons has an aluminum-silicon alloy and a graphite insert. This guarantees excellent, smooth operating characteristics, even with too little oil.



LE/LT 2–20 oil lubricated piston compressors

Туре	Maximum working pressure	Volume flow ¹⁾		Motor rated power	Sound pressure level ²⁾		Container volume ³⁾	Approx. weight	Dimensions L × W × H
LE/LT – Piston compr	essors								
	bar	l/s	m³/min	kW	db(A	4)	L	kg	mm
LE 2-10/90	10	3.40	0.20	1.5	80	65	90	85	1118 × 510 × 1017
LE 3-10/90	10	4.40	0.26	2.2	81	66	90	89	1118 × 510 × 1017
LE 5-10/250	10	8.40	0.50	4.0	81	66	250	150	1852 × 510 × 1082
LE 7-10/250	10	11.70	0.70	5.5	82	70	250	191	1852 × 592 × 1162
LE 10-10/250	10	15.70	0.94	7.5	83	70	250	203	1852 × 592 × 1162
LE 15-10/250	10	18.60	1.12	11.0	86	-	250	330	1852 × 790 × 1200
LE 20-10/250	10	23.90	1.43	15.0	86	-	250	360	1852 × 790 × 1200
LT 2-15/90	15	3.10	0.19	1.5	80	65	90	100	1118 × 533 × 1017
LT 3-15/90	15	4.00	0.24	2.2	81	66	90	104	1118 × 533 × 1017
LT 5-15/250	15	6.70	0.40	4.0	81	66	250	170	1852 × 533 × 1082
LT 7-15/250	15	9.20	0.55	5.5	82	70	250	211	1852 × 606 × 1162
LT 10-15/250	15	11.70	0.70	7.5	83	70	250	223	1852 × 606 × 1162
LT 2-20/90	20	2.10	0.13	1.5	80	65	90	100	1118 × 533 × 1017
LT 3-20/90	20	2.90	0.17	2.2	81	66	90	104	1118 × 533 × 1017
LT 5-20/250	20	5.00	0.30	4.0	81	66	250	170	1852 × 533 × 1082
LT 7-20/250	20	6.70	0.40	5.5	82	70	250	211	1852 × 606 × 1162
LT 10-20/250	20	9.10	0.55	7.5	83	70	250	223	1852 × 606 × 1162
LT 15-20/250	20	15.10	0.91	11.0	86	73	250	333	1852 × 830 × 1980
LT 20-20/250	20	18.00	1.08	15.0	86	73	250	361	1852 × 830 × 1980
LT 3-30	30	2.50	0.15	2.2	81	-	-	49	686 × 533 × 497
LT 5-30	30	4.40	0.26	4.0	81	-	-	51	686 × 533 × 497
LT 7-30	30	6.40	0.38	5.5	82	-	-	90	860 × 606 × 600
LT 10-30	30	8.50	0.51	7.5	83	-	-	102	932 × 606 × 600
LT 15-30	30	9.30	0.56	11.0	83	-	-	166	1024 × 682 × 675
LT 20-30	30	17.00	1.02	15.0	89	-	-	194	1103 × 713 × 675

¹¹ Volume flow measured in accordance with ISO 1217, Ed. 4, Appendix C-2009, reference conditions: dry intake air, intake pressure 1 bar, coolant temperature 20°C. Details for: 10-bar versions at 7 bar, 15-bar versions at 12 bar, 20-bar versions at 20 bar, 30-bar versions at 30 bar. Volume flow reduction through regeneration air requirement on versions with cd dryers.

²⁾ Sound pressure level measured in accordance with ISO 2151, Edition 2004 with a tolerance of 3 dB(A); right column in table LE/LT for versions with canopy.

Voltage 400 V/50 Hz. Other voltages available on request.

³⁾ Other container sizes available on request

Туре	Maximum working pressure	Volum	e flow ¹⁾	Motor rated power	Sound pressure level ²⁾	Approx. weight	Dimensions L × W × H
LE/LT – Piston compr	essors – Pack vei	rsion					
	bar	l/s	m³/min	kW	db(A)	kg	mm
LE 2-10-Pack	10	3.40	0.20	1.5	63	101	1036 × 680 × 721
LE 3-10-Pack	10	4.40	0.26	2.2	64	105	1036 × 680 × 721
LE 5-10 - Pack	10	8.40	0.50	4.0	64	107	1036 × 680 × 721
LE 7 – 10 - Pack	10	11.70	0.70	5.5	68	159	1326 × 740 × 816
LE 10-10-Pack	10	15.70	0.94	7.5	68	171	1326 × 740 × 816
LE 15-10-Pack	10	18.60	1.17	11.0	-	240	1458 × 938 × 864
LE 20-10-Pack	10	23.90	1.43	15.0	-	255	1458 × 938 × 864
LT 2–15-Pack	15	3.10	0.19	1.5	63	101	1036 × 680 × 721
LT 3–15-Pack	15	4.00	0.24	2.2	64	105	1036 × 680 × 721
LT 5–15-Pack	15	6.70	0.40	4.0	66	107	1036 × 680 × 721
LT 7–15-Pack	15	9.20	0.55	5.5	68	159	1326 × 740 × 816
LT 10-15-Pack	15	11.70	0.70	7.5	68	171	1326 × 740 × 816
LT 2–20-Pack	20	2.10	0.13	1.5	63	101	1036 × 680 × 721
LT 3–20-Pack	20	2.90	0.17	2.2	64	105	1036 × 680 × 721
LT 5–20-Pack	20	5.00	0.30	4.0	66	107	1036 × 680 × 721
LT 7-20-Pack	20	6.70	0.40	5.5	68	159	1326 × 740 × 816
LT 10-20-Pack	20	9.10	0.55	7.5	68	171	1326 × 740 × 816
LT 15-20-Pack	20	15.10	0.91	11.0	69	280	1546 × 830 × 875
LT 20-20-Pack	20	18.00	1.08	15.0	69	301	1546 × 830 × 875

¹⁾ Volume flow measured in accordance with ISO 1217, Ed. 4, Appendix C-2009, reference conditions: dry intake air, intake pressure 1 bar, coolant temperature 20°C. Details for: 10-bar versions at 7 bar , 15-bar versions at 12 bar, 20-bar versions at 20 bar , 30-bar versions at 30 bar. Volume flow reduction through regeneration air requirement on versions with cd dryers.

²¹ Sound pressure level measured in accordance with ISO 2151, Edition 2004 with a tolerance of 3 dB(A), Voltage 400 V/50 Hz. Other voltages available on request.



We can help you to choose the best option

As well as the product quality and product range, we have focused on a combined product portfolio. This includes compressors with a drive performance of 1.5-15 kW, and volume flows of 3.4-24 l/s, as well as a variety of other options.

We will help you find a compressor that suits your demands and requirements at all times.

Special design / optionsthe LE / LT series



LE / LT unit



LE / LT with acoustic enclosure (Pack)



LE-/LT-Trolley mobile version available with electric or petrol engine



LE/LT (15 bar) on standing container







LE / LT-special version Quality compressed air system with CD adsorption kit on container (volume reduction due to purge air requirement)

GX 2-11 Oil-injected rotary screw compressors, 2-11 kW / 3-15 hp.

Atlas Copco's oil-injected rotary screw GX compressors are the powerful and reliable industrial screw compressors for small and medium sized industries. The GX compressors are available in various versions (floor mounted, tank mounted, with or without integrated dryer) to provide flexibility. Built from high-quality components and materials, they provide a reliable source of high-quality air in temperatures up to 46°C/115°F.



Fewer wear parts Longer service intervals Easy service access with

for components

Guaranteed long service life

parts

CUSTOMER BENEFITS

Reliability - The GX series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. The screw compressor technology allows 100% continuous duty cycle and the reinforced frame eliminates resonance. GX compressors are built for a long lifetime of reliable operation.

Reduced energy costs – Our GX compressors offer the low energy consumption and high efficiency of a rotary screw compressor. Compared to piston compressors that suffer from increased energy consumption over time, these screw compressors always provide high efficiency.

Plug and play installation – In addition to boasting a minimum footprint, the GX series discharges cooling air from the top, allowing placement against the wall or in a corner. The tank mounted GX with built-in dryer reduces space requirements even further, making it ideal if you have limited space at your facility.

Silent operation – Atlas Copco supplies GX compressors with full sound enclosures which reduce the sound levels to as low as 61 dB(A). The rotary screw technology minimizes vibration, while optimized cooling air flow enhances quiet operation.

Integrated air treatment - The GX 2-11 FF is available with an advanced built-in refrigerant air dryer. By cooling the compressed air and removing water before it can enter your compressed air network, it prevents rust in your compressed air piping and avoids damage to your air tools.

Easy maintenance at low costs:





Compressor	Max. worki	ng pressure		Capacity FAD		Installed m	otor power	Noise level	Weigl	nt (kg/lbs)*
Туре	bar(e)	psi	l/s	m³/h	cfm	kW	hp	dB(A)	Pack	Full Feature
50 Hz VERSION										
GX 2 EP	10	145	4.0	14.4	8.5	2.2	3	61	165/364	200/441
GX 3 EP	10	145	5.3	19.1	11.2	3	4	61	165/364	200/441
GX 4 EP	10	145	7.8	28.1	16.5	4	5	62	165/364	200/441
GX 5 EP	10	145	10.0	36.0	21.2	5.5	7.5	64	165/364	200/441
GX 7 EP	10	145	14.0	50.4	29.7	7.5	10	66	214/472	264/582
GX 7 EL	7.5	109	19.6	70.6	41.5	7.5	10	65	245/540	314/692
	10	145	16.1	58.0	34.1	7.5	10	65	245/540	314/692
	13	189	12.9	46.4	27.3	7.5	10	65	245/540	314/692
GX 11 EL	7.5	109	27.0	97.2	57.2	11	15	67	257/567	326/719
	10	145	23.3	83.9	49.4	11	15	67	257/567	326/719
	13	189	19.0	68.4	40.3	11	15	67	257/567	326/719
60 Hz VERSION										
GX 2 EP	10.3	150	4.0	14.4	8.5	2.2	3	61	165/364	200/441
GX 4 EP	10.3	150	7.8	28.1	16.5	4	5	62	165/364	200/441
GX 5 EP	10.3	150	10.0	36.0	21.2	5.5	7.5	64	165/364	200/441
GX 7 EP	10.3	150	13.8	49.6	29.2	7.5	10	66	214/472	264/582
GX 7 EL	7.4	107	19.5	70.2	41.3	7.5	10	67	245/540	314/692
	9.1	132	17.3	62.3	36.7	7.5	10	67	245/540	314/692
	10.8	157	14.9	53.6	31.6	7.5	10	67	245/540	314/692
	12.5	181	12.3	44.3	26.1	7.5	10	67	245/540	314/692
GX 11 EL	7.4	107	27.8	100.1	58.9	11	15	68	257/567	326/719
	9.1	132	24.7	88.9	52.3	11	15	68	257/567	326/719
	10.8	157	22.5	81.0	47.7	11	15	68	257/567	326/719
	12.5	181	20.0	72.0	42.4	11	15	68	257/567	326/719

* Tank mounted variant.

EP: Electropneumatic, EL: Elektronikon. Standard air receiver size, GX 2-7 EP: 200 I/60 gal, GX 7-11 EL: 270 I/80 gal. Unit performance measured according to ISO 1217, latest edition. Mean noise level (pack variant) measured according to Pneurop/Cagi PN8NTC2 test code; tolerance 3 dB(A).

AVAILABLE OPTIONS	GX 2-7 EP	GX 2-7 EP FF	GX 7-11 EL	GX 7-11 EL FF
Integrated aftercooler	-	-	0	~
Water separator (shipped loose)	-	~	0	~
Timer water drain on water separator (shipped loose)	-	-	0	-
Timer drain on air receiver (tank mounted only)	0	0	0	0
Electronic no loss water drain on water separator (shipped loose)	-	~	0	√
Electronic no loss water drain on air receiver (500 l/120 gal tank mounted only)	0	0	0	0
Integrated DDx filter kit	-	-	-	0
Integrated high performance PDx filter kit	-	0	-	0
500 I/120 gal air receiver (tank mounted only)	-	-	0	0
Tropical thermostat	-	-	0	0
- : Not available V: Standard O: Optional				

-	٠	INDL	avaiiauie	

O: Optional

	L (mm)	W (mm)	H (mm)
PACK FLOOR M	OUNTED		
GX 2-7 EP	620	575/605*	975
GX 7-11 EL	810/840*	590	1085
FULL FEATURE	FLOOR MOUNT	ED	
GX 2-7 EP	-	-	-
GX 7-11 EL	1205/1235*	590	1085
PACK TANK MO	UNTED		
GX 2-7 EP	1420	575	1280
GX 7-11 EL**	1533	590	1332
FULL FEATURE	TANK MOUNTE	D	
GX 2-7 EP	1420	575	1280
GX 7-11 EL**	1533	590	1332

* Length with inlet grating. ** Dimensions of GX 7-11 EL tank mounted are 1935 x 590 x 1463 mm (L x W x H) with a 500 I vessel and 1880 x 590 x 1463 mm (L x W x H) with a 120 gal vessel.



GX 2-7 EP Floor Mounted



GX 7-11 EL FF Tank Mounted

GA 5-11/GA 5-15 VSD

Oil-injected rotary screw compressors, 5.5-11 KW / 7.5-15 hp

Atlas Copco's oil-injected rotary screw compressors are leader in the market thanks to outstanding performance and flexible operation. This results in the highest productivity while minimizing the total cost of ownership. GA compressors are available in two series: GA 5-11 and GA 5-15 VSD. The GA 5-11 is the best workshop solution, built to perform even in the harshest conditions. The GA 5-15 VSD range is the ideal solution for productions with a fluctuating air demand, optimizing your energy consumption. Both ranges supply the high-quality air you need to keep your air network clean and your production up and running.



CUSTOMER BENEFITS

Highest reliability – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. Ensuring a long and trouble-free life at the lowest operating cost. The compressor contains the latest generation of Atlas Copco's innovative oil-injected screw element.

Reduced energy costs – Our GA compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element. Furthermore, the GA Variable Speed Drive (VSD) reduces energy costs by a further 35% by automatically adjusting the air supply to your air demand with a large turndown operating range.

Air system integration – The GA Work Place Air System can be installed where you need compressed air. Its low noise operation and integrated air treatment equipment eliminates the need for a separate compressor room. All GA compressors are tested and delivered ready for use. The integrated options will reduce installation costs and pressure drops significantly, thus saving additional energy cost.

Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

Integrated air treatment – All GA compressors can be installed with integrated dryers, filters and oil-water separators to protect your compressed air network. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.

GA⁺ series: Your advantage for more power and efficiency

With the new GA+ series, Atlas Copco is offering premium oilinjected screw compressors with excellent volume flow and high efficiency. The improved performance is a direct result of the multitude of innovations that have been integrated into the compressor unit.

- Higher volume flow
- Lower specific power input
- Improved efficiency

	Working p	ressure	Caj	pacity FA	D*	Insta	illed	Noise		Weight (k	g)	
COMPRESSOR	WorkP	lace		min-max		motor	power	level**	Work	Place	WorkPlace	Full Feature
TYPE	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)	Floor-mounted	Tank-mounted	Floor- mounted	Tank- mounted
50 Hz VERSION												
GA 5 7.5	7.5	109	15.0	54.0	31.7	5.5	7.5	60	257	317	300	360
8.5	8.5	123	13.2	47.5	27.9	5.5	7.5	60	257	317	300	360
10	10	145	11.7	42.1	24.7	5.5	7.5	60	257	317	300	360
13	13	189	8.4	30.2	17.7	5.5	7.5	60	2 57	317	300	360
GA 7 7.5	7.5	109	21.0	75.6	44.3	7.5	10	61	270	330	315	375
8.5	8.5	123	21.8	78.5	46.0	7.5	10	61	270	330	315	375
10	10	145	17.2	70.6	36.3	7.5	10	61	270	330	315	375
13	13	189	14.2	51.1	30.0	7.5	10	61	270	330	315	375
GA 11 7.5	7.5	109	30.7	110.5	64.8	11	15	62	293	353	343	403
8.5	8.5	123	28.3	101.9	59.7	11	15	62	293	353	343	403
10	10	145	26.0	93.6	54.9	11	15	62	293	353	343	403
13	13	189	22.0	79.2	46.5	11	15	62	293	353	343	403

	Max. Wo	orking	Cap	oacity FA	D*	Insta	Installed Noise Weight (kg/lbs) motor power level** WorkPlace WorkPlace Full Fe					
COMPRESSOR	WorkP	ure lace	İ	min-max		motor	power	level**	Work	Place	WorkPlace	Full Feature
IYPE	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)	Floor-mounted	Tank-mounted	Floor- mounted	Tank- mounted
60 Hz VERSION												
GA 5 100	7.4	107	15.0	54.0	31.7	5.5	7.5	60	257	317	300	360
125	9.1	132	13.2	47.5	27.9	5.5	7.5	60	257	317	300	360
150	10.8	157	11.7	42.1	24.7	5.5	7.5	60	257	317	300	360
175	12.5	181	8.4	30.2	17.7	5.5	7.5	60	257	317	300	360
GA 7 100	7.4	107	21.0	75.6	44.3	7.5	10	61	270	330	315	375
125	9.1	132	21.8	78.5	46.0	7.5	10	61	270	330	315	375
150	10.8	157	17.2	70.6	36.3	7.5	10	61	270	330	315	375
175	12.5	181	14.2	51.1	30.0	7.5	10	61	270	330	315	375
GA 11 100	7.4	107	30.4	109.4	64.1	11	15	62	293	353	343	403
125	9.1	132	27.0	97.2	57.0	11	15	62	293	353	343	403
150	10.8	157	24.9	89.6	52.5	11	15	62	293	353	343	403
175	12.5	181	22.0	79.2	46.4	11	15	62	293	353	343	403

* Unit performance measured according to ISO 1217, Ed. 3, Annex C-1996. ** Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions: - Absolute inlet pressure 1 bar (14.5 psi). - Intake air temperature 20°C, 68°F.

FAD is measured at the following working pressures: - 7.5 bar versions at 7 bar(e). - 8.5 bar versions at 8 bar(e).

- 10 bar versions at 9.5 bar(e).
- 13 bar versions at 12.5 bar(e).

(floor-mounted)

(tank-mounted)

Maximum working pressure for VSD machines: - 13 bar(e) (188 psig)

GA 5-7-11 pack & GA 5-7-11-15 VSD pack

GA 5-7-11 pack & GA 5-7-11-15 VSD pack





floor-mounted



	Max. W	orking		Installed motor power		Naiaa		Weight (kg/lbs)			
COMPRESSOR TYPE	press WorkP	ure lace	Cap	acity FAD* min	-max	pov	u motor ver	level**	Work	Place	WorkPla Feat	ice Full ure
	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)	Floor- mounted	Tank- mounted	Floor- mounted	Tank- mounted
50/60 Hz VERSIO	N											
	5.5	80	6.1-15.2	22.0-54.7	13.4-33.4	5.5	7.5	62	275	335	318	378
	7.5	109	6.0-15.0	21.6-54.0	13.2-33.0	5.5	7.5	62	275	335	318	378
GA 5 VSD	10	145	6.8-11.7	24.5-42.1	15.0-25.7	5.5	7.5	62	275	335	318	378
	13	188	8.3-10	29.9-36.0	18.3-22.0	5.5	7.5	62	275	335	318	378
	5.5	80	5.1-20.5	18.4-73.8	11.2-45.1	7.5	10	64	280	340	325	385
	7.5	109	5.1-20.3	18.4-73.1	11.2-44.7	7.5	10	64	280	340	325	385
GA 7 VSD	10	145	6.5-16.8	23.4-60.5	14.3-37.0	7.5	10	64	280	340	325	385
	13	188	7.9-13.8	28.4-49.7	17.4-30.4	7.5	10	64	280	340	325	385
	5.5	80	8.2-31	29.5-111.6	18.0-68.2	11	15	66	293	353	343	403
	7.5	109	8.1-30.7	29.2-110.5	17.8-67.5	11	15	66	293	353	343	403
GA TI VSD	10	145	8.7-24.1	31.3-86.8	19.1-53.0	11	15	66	293	353	343	403
	13	188	10.2-20.7	36.7-74.5	22.4-45.5	11	15	66	293	353	343	403
	5.5	80	9.0-37.5	32.4-135.0	19.8-82.5	15	20	69	300	360	352	412
GA 15 VSD	7.5	109	9.1-37.1	32.8-133.6	20.0-81.6	15	20	69	300	360	352	412
GA 15 VSD	10	145	8.8-30.9	31.7-111.2	19.4-68.0	15	20	69	300	360	352	412
	13	188	8.5-24.8	30.6-89.3	18.7-54.6	15	20	69	300	360	352	412

* Unit performance measured according to ISO 1217, Ed. 3, Annex C-1996.
** Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions:

Reference conditions: - Absolute inlet pressure 1 bar (14.5 psi). - Intake air temperature 20°C, 68°F. FAD is measured at the following working pressures: - 7.5 bar versions at 7 bar(e). - 8.5 bar versions at 9.5 bar(e). - 10 bar versions at 19.5 bar(e). - 13 bar versions at 12.5 bar(e).

Maximum working pressure for VSD machines: - 13 bar(e) (188 psig)



GA 5-7-11 FF & GA 5-7-11-15 VSD FF (tank-mounted)

GA 5-7-11 FF & GA 5-7-11-15 VSD FF (floor-mounted)



Oil - injected compressors

GA 11+-30/GA 15-30 VSD Oil-injected rotary screw compressors, 11-30 kW / 15-40 hp

Atlas Copco's oil-injected rotary screw compressors are leader in the market thanks to outstanding performance and flexible operation. This results in the highest productivity while minimizing the total cost of ownership. GA compressors are available in two series, GA+ 11-30 and GA 15-30 VSD, enabling you to perfectly match your requirements for compressed air solutions. Built to perform even in the harshest environments, these products will keep your production running

CUSTOMER BENEFITS

efficiently.

• **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. Ensuring a long and trouble-free life at the lowest operating cost. GA compressors are equipped with the latest generation of Atlas Copco's innovative oil-injected screw element integrated with a closed gear drive eliminating the need for a coupling suitable for the harshest environment.

• **Reduced energy costs** – GA compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element and motors. The GA Variable Speed Drive (VSD) also reduces energy costs by a further 35% by automatically adjusting the air supply to your air demand with a large turndown operating range.

• Air system integration – The GA WorkPlace Air System can be installed where you need compressed air. Its low noise operation and integrated air treatment equipment eliminates the need for a separate compressor room. All GA compressors are tested and delivered ready for use. The integrated options will reduce installation costs and pressure drops significantly, thus saving additional energy cost.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• Integrated air treatment – All GA compressors have integrated dryer, filters and oil-water separator available to protect your compressed air network. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



			Max. work	ing pressure			-		Installed	motor	Noico	Wei	ght (kg)
COMPRES TYPE	SOR	Work	Place	WorkPlace	Full Feature	Ca	apacity FAD*		pow	er	level**	Work-	Work- Place Full
		bar(e)	psig	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)	TIACE	Feature
50 Hz VERSIC	N		7.5 109										
GA 15	7.5	7.5	109	7.3	105	43	154.8	91.1	15	20	72	375	440
	8	8.5	116	8.3	120	39.4	141.8	83.5	15	20	72	375	440
	10	10	145	9.8	9.8 141		130.7	76.9	15	20	72	375	440
	13	13	189	12.8	185	30.1	108.4	63.8	15	20	72	375	440
GA 18	7.5	7.5	109	7.3	105	52.5	189	111.2	18.5	25	73	395	470
	8	8.5	116	8.3	120	50.2	180.7	106.4	18.5	25	73	395	470
	10	10	145	9.8	141	43.5	156.6	92.2	18.5	25	73	395	470
	13	13	189	12.8	185	37.2	133.9	78.8	18.5	25	73	395	470
GA 22	7.5	7.5	109	7.3	105	60.2	216.7	127.6	22	30	74	410	485
	8	8.5	116	8.3	120	58.3	209.9	123.5	22	30	74	410	485
	10	10	145	9.8	141	51.7	186.1	109.5	22	30	74	410	485
	13	13	189	12.8	185	45.0	162	95.3	22	30	74	410	485

Technical specifications GA 15-22

COMPRESSOR		Max. work	ing pressure							Nt	Wei	ight (kg)	
COMPRESSOR Type		Work	Place	WorkPlace	Full Feature	C	apacity FAD*		Installed mo	otor power	Noise Ievel**	Work-	Work- Place Full
		bar(e)	psig	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)	FIACE	Feature
60 Hz VERSION													
GA 15	100	7.4	107	7.2	104	42.5	153.0	90.1	15	20	72	375	440
1	125	9.1	132	8.9	128	39.6	142.6	83.9	15	20	72	375	440
1	150	10.8	157	10.3	149	35.8	128.9	75.9	15	20	72	375	440
1	175	12.5	181	12.3	178	29.3	105.5	62.1	15	20	72	375	440
GA 18	100	7.4	107	7.2	104	51.3	184.7	108.7	18.5	25	73	395	470
	125	9.1	132	8.9	128	47.7	171.7	101.1	18.5	25	73	395	470
	150	10.8	157	10.3	149	43.3	155.9	91.7	18.5	25	73	395	470
	175	12.5	181	12.3	178	37.8	136.1	80.1	18.5	25	73	395	470
GA 22	100	7.4	107	7.2	104	60.6	218.2	128.4	22	30	74	410	485
	125	9.1	132	8.9	128	56.0	201.6	118.7	22	30	74	410	485
	150	10.8	157	10.3	149	50.7	182.5	107.4	22	30	74	410	485
	175	12.5	181	12.3	178	46.5	167.4	98.5	22	30	74	410	485

Pack

H1: 1558 mm, 61" H2:932 mm, 37"

L1: 1853 mm, 73"

L2: 1285 mm, 51" W: 680 mm, 27"

* Unit performance measured according to ISO 1217, Annex C, latest edition.

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)

- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar

- 8 bar versions at 7.5 bar

- 10 bar versions at 9.5 bar

- 13 bar versions at 12.5 bar

GA 15 - GA 18 - GA 22

Full Feature

H: 1558 mm, 61" L: 1853 mm, 73"

W: 680 mm, 27"

Air receiver size of GA 15-22 tank-mounted variants: 500L. Added weight: 125 kg.

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Pressure dew point of integrated refrigerant dryer of GA 15 - GA 18 - GA 22 at reference conditions 5°C, 41°F.





Technical specifications GA 11+-30 (50 Hz version)

	М	ax. worki	ng pressu	re				• •			Weig	ht (kg)			
COMPRESSOR Type	Work	Place	Workf Full Fe	Place ature	Cap	bacity FA	D*	Insta motor p	lled oower	Noise level**	WorkPlace	WorkPlace	Length (mm)	Width (mm)	Height (mm)
	bar(e)	psig	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)		i uni i cature			
50 Hz VERSION															
GA 11 ⁺ 7.	5 7.5	109	7.3	105	35.8	128.9	75.9	11	15	63	410	455	1255	692	1475
8.	5 8.5	116	8.3	120	33.8	121.7	71.7	11	15	63	410	455	1255	692	1475
1	D 10	145	9.8	141	30.3	109.1	64.2	11	15	63	410	455	1255	692	1475
1	3 13	189	12.8	185	25.2	90.7	53.4	11	15	63	410	455	1255	692	1475
GA 15 ⁺ 7.	5 7.5	109	7.3	105	46.9	168.8	99.4	15	20	64	420	470	1255	692	1475
8.	5 8.5	116	8.3	120	43.8	157.7	92.9	15	20	64	420	470	1255	692	1475
1	D 10	145	9.8	141	39.8	143.3	84.4	15	20	64	420	470	1255	692	1475
1	3 13	189	12.8	185	32.8	118.1	69.5	15	20	64	420	470	1255	692	1475
GA 18 ⁺ 7.	5 7.5	109	7.3	105	58.1	209.2	123.2	18.5	25	65	440	500	1255	692	1475
8.	5 8.5	116	8.3	120	54.3	195.5	115.1	18.5	25	65	440	500	1255	692	1475
1	0 10	145	9.8	141	48.7	175.3	103.2	18.5	25	65	440	500	1255	692	1475
1	3 13	189	12.8	185	41.1	148.0	87.1	18.5	25	65	440	500	1255	692	1475
GA 22+ 7.	5 7.5	109	7.3	105	68.2	245.5	144.6	22	30	66	455	515	1255	692	1475
8.	5 8.5	116	8.3	120	64.5	232.2	136.7	22	30	66	455	515	1255	692	1475
1	D 10	145	9.8	141	58.1	209.2	123.2	22	30	66	455	515	1255	692	1475
1	3 13	189	12.8	185	50.7	182.5	107.5	22	30	66	455	515	1255	692	1475
GA 26+ 7.	5 7.5	109	7.3	105	79.8	287.3	169.2	26	35	67	525	595	1255	865	1475
8.	5 8.5	116	8.3	120	76.2	274.3	161.5	26	35	67	525	595	1255	865	1475
1	D 10	145	9.8	141	69.3	249.5	146.9	26	35	67	525	595	1255	865	1475
1	3 13	189	12.8	185	60.1	216.4	127.4	26	35	67	525	595	1255	865	1475
GA 30 7.	5 7.5	109	7.3	105	90.0	324.0	190.8	30	40	68	540	610	1255	865	1475
8.	5 8.5	116	8.3	120	86.4	311.0	183.2	30	40	68	540	610	1255	865	1475
1	0 10	145	9.8	141	79.8	287.3	169.2	30	40	68	540	610	1255	865	1475
1	3 13	189	12.8	185	68.7	247.3	145.6	30	40	68	540	610	1255	865	1475

* Unit performance measured according to ISO 1217, Annex C, latest edition.

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi) - Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

- 7.5 bar versions at 7 bar - 8 bar versions at 7.5 bar

- 10 bar versions at 9.5 bar

- 13 bar versions at 12.5 bar

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Pressure dew point of integrated refrigerant dryer of GA 11⁺ - GA 15⁺ - GA 18⁺ - GA 22⁺ - GA 20⁺ - GA 30 at reference conditions 2°C to 3°C, 36°F to 37°F.



GA 11+ - GA 15+ - GA 18+ - GA 22+

H: 1475 mm, 58" L: 1255 mm, 49"

W: 692 mm, 27"

		Ма	ıx. worki	ng pressı	ire							Weig	ıht (kg)			
COMPRES TYPE	SOR	Work	Place	Work Full Fe	Place eature	C	apacity FA	\D*	Inst motor	alled power	Noise level**	Work-	Work- Place Full	Length (mm)	Width (mm)	Height (mm)
		bar(e)	psig	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dB(A)	11000	Feature			
60 Hz VERSI	ON															
GA 11+	100	7.4	107	7.2	104	37.0	133.2	78.4	11	15	63	410	455	1255	692	1475
	125	9.1	132	8.9	128	32.0	115.2	67.8	11	15	63	410	455	1255	692	1475
	150	10.8	157	10.3	149	29.3	105.5	62.1	11	15	63	410	455	1255	692	1475
	175	12.5	181	12.3	178	25.3	91.1	53.6	11	15	63	410	455	1255	692	1475
GA 15+	100	7.4	107	7.2	104	48.3	173.9	102.4	15	20	64	420	470	1255	692	1475
	125	9.1	132	8.9	128	42.9	154.4	90.9	15	20	64	420	470	1255	692	1475
	150	10.8	157	10.3	149	39.4	141.8	83.5	15	20	64	420	470	1255	692	1475
	175	12.5	181	12.3	178	33.9	122.0	71.9	15	20	64	420	470	1255	692	1475
GA 18+	100	7.4	107	7.2	104	59.6	214.6	126.4	18.5	25	66	440	500	1255	692	1475
	125	9.1	132	8.9	128	53.3	191.9	113.0	18.5	25	66	440	500	1255	692	1475
	150	10.8	157	10.3	149	47.8	172.1	101.3	18.5	25	66	440	500	1255	692	1475
	175	12.5	181	12.3	178	42.5	153.0	90.1	18.5	25	66	440	500	1255	692	1475
GA 22+	100	7.4	107	7.2	104	70.3	253.1	149.0	22	30	67	455	515	1255	692	1475
	125	9.1	132	8.9	128	62.9	226.4	133.3	22	30	67	455	515	1255	692	1475
	150	10.8	157	10.3	149	56.9	204.8	120.6	22	30	67	455	515	1255	692	1475
	175	12.5	181	12.3	178	52.3	188.3	110.9	22	30	67	455	515	1255	692	1475
GA 26+	100	7.4	107	7.2	104	81.2	292.3	172.1	26	35	67	525	595	1255	865	1475
	125	9.1	132	8.9	128	74.1	266.8	157.1	26	35	67	525	595	1255	865	1475
	150	10.8	157	10.3	149	67.4	242.6	142.9	26	35	67	525	595	1255	865	1475
	175	12.5	181	12.3	178	60.7	218.5	128.7	26	35	67	525	595	1255	865	1475
GA 30	100	7.4	107	7.2	104	90.1	324.4	191.0	30	40	68	540	610	1255	865	1475
	125	9.1	132	8.9	128	84.1	302.8	178.3	30	40	68	540	610	1255	865	1475
	150	10.8	157	10.3	149	77.1	277.6	163.5	30	40	68	540	610	1255	865	1475
	175	12.5	181	12.3	178	70.1	252.4	148.6	30	40	68	540	610	1255	865	1475

Technical specifications GA 11+-30 (60 Hz version)

* Unit performance measured according to ISO 1217, Annex C, latest edition.

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)

- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures: - 7.5 bar versions at 7 bar

- 8 bar versions at 7.5 bar
 10 bar versions at 9.5 bar
- 13 bar versions at 12.5 bar

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

Pressure dew point of integrated refrigerant dryer of GA 11⁺ - GA 15⁺ - GA 18⁺ - GA 22⁺ - GA 26⁺ - GA 30 at reference conditions 2°C to 3°C, 35°F to 37°F.



GA 26⁺ - GA 30

- H: 1475 mm, 58"
- L: 1255 mm, 49"

Technical specifications GA 15-30 VSD

COMPRESSOR	Max. working pressure		Capacity FAD MinMax.							Installed motor		Weight (kg)		Longth	\M/idth	Unight
TYPE	WorkPlace		l/s		m³/h		cfm		power		50/60 Hz	Work-	WorkPlace Full	(mm)	(mm)	(mm)
	bar(e)	psig	Min.	Max.	Min.	Max.	Min.	Max.	kW	hp	dB(A)	Place	Feature			
GA 15 VSD	4	58	16.0	48.7	57.6	175.3	33.9	103.2	15	20	66	480	530	1255	865	1475
	7	102	15.9	48.5	57.2	174.6	33.7	102.8	15	20	66	480	530	1255	865	1475
	10	145	18.0	41.6	64.8	149.8	38.2	88.2	15	20	66	480	530	1255	865	1475
	13	188	20.4	32.8	73.4	118.1	43.2	69.5	15	20	65	480	530	1255	865	1475
GA 18 VSD	4	58	16.0	60.1	57.6	216.4	33.9	127.4	18	25	67	490	550	1255	865	1475
	7	102	15.9	60.0	57.2	216.0	33.7	127.2	18	25	67	490	550	1255	865	1475
	10	145	18.0	52.0	64.8	187.2	38.2	110.2	18	25	67	490	550	1255	865	1475
	13	188	20.4	42.0	73.4	151.2	43.2	89.0	18	25	66	490	550	1255	865	1475
GA 22 VSD	4	58	16.0	70.5	57.6	253.8	33.9	149.5	22	30	68	500	560	1255	865	1475
	7	102	15.9	70.3	57.2	253.1	33.7	149.5	22	30	68	500	560	1255	865	1475
	10	145	18.0	61.4	64.8	221.0	38.2	130.2	22	30	68	500	560	1255	865	1475
	13	188	20.4	50.2	73.4	180.7	43.2	106.4	22	30	67	500	560	1255	865	1475
GA 26 VSD	4	58	16.0	81.5	57.6	293.4	33.9	172.8	26	35	70	520	590	1255	865	1475
	7	102	15.9	81.2	57.2	292.3	33.7	172.1	26	35	70	520	590	1255	865	1475
	10	145	18.0	72.4	64.8	260.6	38.2	153.5	26	35	70	520	590	1255	865	1475
	13	188	20.4	59.7	73.4	214.9	43.2	126.6	26	35	69	520	590	1255	865	1475
GA 30 VSD	4	58	16.0	93.3	57.6	335.9	33.9	197.8	30	35	70	530	600	1255	865	1475
	7	102	15.9	93.0	57.2	334.8	33.7	197.2	30	35	70	530	600	1255	865	1475
	10	145	18.0	82.7	64.8	297.7	38.2	175.3	30	35	70	530	600	1255	865	1475
	13	188	20.4	70.8	73.4	254.9	43.2	150.1	30	35	69	530	600	1255	865	1475

* Unit performance measured according to ISO 1217, Annex C, latest edition.

Pressure dew point of integrated refrigerant dryer at reference conditions: 2°C to 3°C, 35°F to 37°F.

Maximum working pressure for VSD machines: 13 bar(e) (188 psig)

Reference conditions:

- Absolute inlet pressure 1 bar (14.5 psi)

- Intake air temperature 20°C, 68°F

** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code; tolerance 2 dB(A).

GA 15 VSD - GA 18 VSD -GA 22 VSD - GA 30 VSD

H: 1400 mm, 55"

W: 650 mm, 26"



L: 1380 mm, 66"

GA 15-22 Oil-injected rotary screw compressors, 15-22 kW / 20-30 hp

Atlas Copco's oil-injected rotary screw compressors are leader in the market thanks to outstanding performance and flexible operation. This results in the highest productivity while minimizing the total cost of ownership. GA compressors are built to perform even in the harshest environments; these products will keep your production running smoothly.

CUSTOMER BENEFITS

• **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. Ensuring a long and trouble-free life at the lowest operating cost. GA compressors are equipped with the latest generation of Atlas Copco's innovative oil-injected screw element.

• **Reduced energy costs** – Our GA compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element and motors, and minimal internal losses.

• Air system integration – The GA WorkPlace Air System can be installed where you need compressed air. Its low noise operation and integrated air treatment equipment eliminates the need for a separate compressor room. All GA compressors are tested and delivered ready for use. The integrated options will reduce installation costs and pressure drops significantly, thus saving additional energy cost.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• Integrated air treatment – All GA compressors have integrated dryer and filters available to protect your compressed air network. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



Technical specifications GA 15-22

COMPRESSOR	Max. working pressure	Capacity FAD*	Installed Motor Power	Noise Level**	Weight		
ТҮРЕ	Workplace/ Workplace FF				Workplace/ Workplace FF		
	bar(e)	m³h	kW	dB(A)			
50 Hz VERSION							
GA 15 7.5	7.5/7.3	154.8	15	72	375/440		
8.5	8.5/8.3	141.8	15	72	375/440		
10	10/9.8	130.7	15	72	375/440		
13	13/12.8	108.4	15	72	375/440		
GA 18 7.5	7.5/7.3	189	18.5	73	395/470		
8.5	8.5/8.3	180.7	18.5	73	395/470		
10	10/9.8	156.6	18.5	73	395/470		
13	13/12.8	133.9	18.5	73	395/470		
GA 22 7.5	7.5/7.3	216.7	22	74	410/485		
8.5	8.5/8.3	209.9	22	74	410/485		
10	10/9.8	186.1	22	74	410/485		
13	13/12.8	162	22	74	410/485		
50 Hz VERSION							
	psig	cfm	hp	dB(A)	lbs		
GA 15 100	107/104	90.1	20	72	827/970		
125	132/128	83.9	20	72	827/970		
150	157/149	75.9	20	72	827/970		
175	181/178	62.1	20	72	827/970		
GA 18 100	107/104	108.7	25	73	871/1036		
125	132/128	101.1	25	73	871/1036		
150	157/149	91.7	25	73	871/1036		
175	181/178	80.1	25	73	871/1036		
GA 22 100	107/104	128.4	30	74	904/1069		
125	132/128	118.7	30	74	904/1069		
150	157/149	107.4	30	74	904/1069		
175	181/178	98.5	30	74	904/1069		

* Unit performance measured according to ISO 1217, Ed. 3, Annex C-1996. ** Mean noise level measured according to ISO 2151/Pneuro/Cagi PN8NTC2 test code ; tolerance 2 dB(A)

Reference conditions: - Absolute inlet pressure 1 bar (14.5 psi) - Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures: - 7.5 bar versions at 7 bar - 8.5 bar versions at 8 bar

- 10 bar versions at 9.5 bar
 13 bar versions at 12.5 bar

GA 15 - GA 18 - GA 22

Full Feature

H: 1558 mm, 61" L: 1853 mm, 73" W: 680 mm, 27"

Pressure dew point of integrated refrigerant dryer of GA 15 - GA 18 - GA 22 at reference conditions 5°C, 41°F.

Air receiver size : 500L. Added weight: 125 kg.

Pack

H1: 1558 mm, 61" H2:932 mm, 37" L1: 1853 mm, 73" L2: 1285 mm, 51" W: 680 mm, 27"





GA 30+-90 / GA 37-90 VSD

Oil-injected rotary screw compressors, 30-90 kW / 40-125 hp

Atlas Copco's oil-injected rotary screw GA compressors are leaders in the market, with outstanding reliable performance. Their flexible operation results in the highest productivity, while minimizing the total cost of ownership. GA compressors are available in three series – GA, GA⁺ and GA VSD –enabling you to perfectly match your requirements for compressed air solutions. Built to perform even in the harshest environments, these products will keep your production running efficiently.

CUSTOMER BENEFITS

• **Highest reliability** – The GA series is designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217. The latest generation of Atlas Copco's innovative oil-injected screw element ensures a long and trouble-free life, at the lowest operating costs. The integrated closed gear drive eliminates the need for a coupling thus reducing maintenance requirements while increasing GA reliability suitable for the harshest environments.

• **Reduced energy costs** – Our GA / GA+ compressors can reduce your energy costs and overall compressor lifecycle costs thanks to the use of our highly efficient element and motors. Furthermore, the GA Variable Speed Drive (VSD) reduces energy costs by a further 35% by automatically adjusting the air supply to your air demand with a large turndown operating range.

• Air system integration – The GA WorkPlace Air System can be placed where you need it. Its low noise operation and integrated air treatment equipment eliminate the need for a separate compressor room. All GA compressors are delivered ready for use, significantly reducing installation costs, pressure drops and thus saving additional energy cost.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• Integrated air treatment – All GA compressors are available with an integrated dryer that efficiently removes moisture, aerosols and dirt particles to protect your investment. This quality air expands the life of equipment, increasing efficiency and ensuring quality in your final product.



Download a QR Reader and scan the code for for our interactive leaflet.



<u>Oil - injected compressors</u>

Android app





Compressor Type	Pressure variant	Max. work sure Wo	king pres- rkPlace	C	apacity FAD	*	Installed m	Installed motor power		Installed motor power Noise Weight level** WorkPlace			Weight WorkPlace		Weight WorkPlace Full Feature		
		bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	kg	lbs	kg	lbs				
GA 30⁺	7.5	7.5	109	99	5.9	209	30	40	65	817	1801	898	1980				
	8.5	8.5	123	90	5.4	191	30	40	65	817	1801	898	1980				
	10	10	145	82	4.9	175	30	40	65	817	1801	898	1980				
	13	13	189	71	4.3	151	30	40	65	817	1801	898	1980				
GA 37	7.5	7.5	109	115	6.9	243	37	50	69	905	1994	820	1807				
	8.5	8.5	123	106	6.4	225	37	50	69	905	1995	820	1808				
	10	10	145	100	6.0	213	37	50	69	905	1995	820	1808				
	13	13	189	81	4.9	172	37	50	69	905	1995	820	1808				
GA 37+	7.5	7.5	109	122	7.3	258	37	50	65	902	1989	987	2176				
	8.5	8.5	123	118	7.1	250	37	50	65	902	1989	987	2176				
	10	10	145	102	6.1	216	37	50	65	902	1989	987	2176				
	13	13	189	85	5.1	180	37	50	65	902	1989	987	2176				
GA 45	7.5	7.5	109	137	8.2	291	45	60	72	894	1971	979	2158				
	8.5	8.5	123	127	7.6	268	45	60	72	894	1971	979	2158				
	10	10	145	117	7.0	248	45	60	72	894	1971	979	2158				
	13	13	189	102	6.1	217	45	60	72	894	1971	979	2158				
GA 45+	7.5	7.5	109	149	8.9	315	45	60	66	970	2138	1060	2337				
	8.5	8.5	123	139	8.3	295	45	60	66	970	2138	1060	2337				
	10	10	145	128	7.7	270	45	60	66	970	2138	1060	2337				
	13	13	189	106	6.4	225	45	60	66	970	2138	1060	2337				
GA 55	7.5	7.5	109	169	10.2	359	55	75	69	1229	2709	1329	2930				
	8.5	8.5	123	159	9.5	336	55	75	69	1229	2709	1329	2930				
	10	10	145	148	8.9	313	55	75	69	1229	2709	1329	2930				
	13	13	189	126	7.6	267	55	75	69	1229	2709	1329	2930				
GA 55⁺	7.5	7.5	109	184	11.1	390	55	75	66	1358	2994	1458	3214				
	8.5	8.5	123	174	10.4	369	55	75	66	1358	2994	1458	3214				
	10	10	145	156	9.5	331	55	75	66	1358	2994	1458	3214				
GA 75	7.5	7.5	109	226	13.5	478	75	100	73	1259	2776	1379	3040				
	8.5	8.5	123	209	12.6	444	75	100	73	1259	2776	1379	3040				
	10	10	145	189	11.4	401	75	100	73	1259	2776	1379	3040				
	13	13	189	162	9.7	344	75	100	73	1259	2776	1379	3040				
GA 75*	7.5	7.5	109	248	14.9	526	75	100	68	1413	3115	1533	3380				
	8.5	8.5	123	235	14.1	497	75	100	68	1413	3115	1533	3380				
	10	10	145	210	12.6	445	75	100	68	1413	3115	1533	3380				
	13	13	189	177	10.6	375	75	100	68	1413	3115	1533	3380				
GA 90	7.5	7.5	109	281	16.9	596	90	125	73	1425	3142	1545	3406				
	8.5	8.5	123	275	16.5	582	90	125	73	1425	3142	1545	3406				
	10	10	145	250	15.0	529	90	125	73	1425	3142	1545	3406				
	13	13	189	216	13.0	458	90	125	73	1425	3142	1545	3406				

Technical specifications GA 30+-90 (50 Hz versions)

* Unit performance measured according to ISO 1217, Annex C, Edition 4

Reference conditions:

Absolute inlet pressure 1 bar (14.5 psi) Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures: 7.5 bar versions at 7 bar 8.5 bar versions at 8 bar

10 bar versions at 9.5 bar

13 bar versions at 12.5 bar

** A-weighted emission sound pressure level at the work station, Lp WSA (re 20 μPa) dB (with uncertainty 3 dB). Values determined according to noise level test code ISO 2151 and noise measurement standard ISO 9614. Pressure dew point of integrated refrigerant dryer at reference conditions: 2°C to 3°C, 36°F to 37°F.

COMPRESSOR Type	Pressure variant	Max. worki Work	ng pressure Place	Ca	pacity FAD*		Installe po	ed motor wer	Noise level**	Weiq WorkP	ght 'lace	We Work Full Fe	ight Place eature
		bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	kg	lbs	kg	lbs
GA 30⁺	100	7.4	107	100	6.0	212	30	40	65	817	1801	898	1980
	125	9.1	132	91	5.4	192	30	40	65	817	1801	898	1980
	150	10.8	157	82	4.9	174	30	40	65	817	1801	898	1980
	175	12.5	181	75	4.5	158	30	40	65	817	1801	898	1980
GA 37	100	7.4	107	116	7.0	246	37	50	69	905	1995	820	1808
	125	9.1	132	108	6.5	229	37	50	69	905	1995	820	1808
	150	10.8	157	96	5.8	204	37	50	69	905	1995	820	1808
	175	12.5	181	87	5.2	185	37	50	69	905	1995	820	1808
GA 37+	100	7.4	107	120	7.2	255	37	50	65	905	1995	987	2176
	125	9.1	132	111	6.6	234	37	50	65	905	1995	987	2176
	150	10.8	157	100	6.0	212	37	50	65	905	1995	987	2176
	175	12.5	181	91	5.4	192	37	50	65	905	1995	987	2176
GA 45	100	7.4	107	139	8.3	294	45	60	72	894	1971	979	2158
	125	9.1	132	128	7.7	271	45	60	72	894	1971	979	2158
	150	10.8	157	118	7.1	250	45	60	72	894	1971	979	2158
	175	12.5	181	105	6.3	222	45	60	72	894	1971	979	2158
GA 45+	100	7.4	107	146	8.8	310	45	60	66	970	2138	1060	2337
	125	9.1	132	134	8.0	284	45	60	66	970	2138	1060	2337
	150	10.8	157	126	7.5	266	45	60	66	970	2138	1060	2337
	175	12.5	181	111	6.7	236	45	60	66	970	2138	1060	2337
GA 55	100	7.4	107	174	10.5	369	55	75	69	1229	2709	1329	2930
	125	9.1	132	154	9.3	327	55	75	69	1229	2709	1329	2930
	150	10.8	157	142	8.5	300	55	75	69	1229	2709	1329	2930
	175	12.5	181	128	7.7	272	55	75	69	1229	2709	1329	2930
GA 55⁺	100	7.4	107	184	11.0	390	55	75	67	1358	2994	1458	3214
	125	9.1	132	166	10.0	352	55	75	67	1358	2994	1458	3214
	150	10.8	157	141	8.5	299	55	75	67	1358	2994	1458	3214
GA 75	100	7.4	107	229	13.7	485	75	100	73	1259	2776	1359	2996
	125	9.1	132	200	12.0	424	75	100	73	1259	2776	1359	2996
	150	10.8	157	189	11.4	401	75	100	73	1259	2776	1359	2996
	175	12.5	181	169	10.1	358	75	100	73	1259	2776	1359	2996
GA 75+	100	7.4	107	248	14.9	525	75	100	69	1413	3115	1533	3380
	125	9.1	132	227	13.6	481	75	100	69	1413	3115	1533	3380
	150	10.8	157	204	12.3	433	75	100	69	1413	3115	1533	3380
	175	12.5	181	182	10.9	385	75	100	69	1413	3115	1533	3380
GA 90	100	7.4	107	289	17.4	613	90	125	74	1425	3142	1545	3406
	125	9.1	132	267	16.0	565	90	125	74	1425	3142	1545	3406
	150	10.8	157	250	15.0	530	90	125	74	1425	3142	1545	3406
	175	12.5	181	228	13.7	484	90	125	74	1425	3142	1545	3406

Technical specifications GA 30+-90 (60 Hz version)

Please refer to the footnotes, reference conditions and FAD details of the 50 Hz versions.

	Working pressure				Capacity	FAD*			Installed motor		Noise	Weight		Weight WorkPlace	
COMPRESSOR TYPE			l/s		m³/min		cfm		power		level**	WorkPlace		Full Feature	
	bar(e)	psig	min	max	min	max	min	max	kW	hp	dB(A)	kg	lbs	kg	lbs
GA 37 VSD	4	58	26.0	124	1.6	7.4	55	263	37	50	66/67	1042	2297	1127	2485
	7	102	26.0	123	1.6	7.4	55	260	37	50	66/67	1042	2297	1127	2485
	10	145	25.8	107	1.5	6.4	55	226	37	50	66/67	1042	2297	1127	2485
	13	189	40.3	87	2.4	5.2	85	185	37	50	66/67	1042	2297	1127	2485
GA 45 VSD	4	58	26.0	146	1.6	8.8	55	310	45	60	69/72	1100	2425	1190	2624
	7	102	26.0	145	1.6	8.7	55	307	45	60	69/72	1100	2425	1190	2624
	10	145	25.8	128	1.5	7.7	55	271	45	60	69/72	1100	2425	1190	2624
	13	189	40.3	107	2.4	6.4	85	226	45	60	69/72	1100	2425	1190	2624
GA 55 VSD	4	58	32.4	197	1.9	11.8	69	418	55	75	69/72	1380	3042	1480	3263
	7	102	26.0	175	1.6	10.5	55	371	55	75	69/72	1380	3042	1480	3263
	10	145	25.4	155	1.5	9.3	54	328	55	75	69/72	1380	3042	1480	3263
	13	189	37.0	129	2.2	7.7	78	273	55	75	69/72	1380	3042	1480	3263
GA 75 VSD	4	58	37.8	250	2.3	15.0	80	529	75	100	69/70	1534	3382	1654	3646
	7	102	37.4	250	2.2	15.0	79	530	75	100	69/70	1534	3382	1654	3646
	10	145	48.1	219	2.9	13.2	102	465	75	100	69/70	1534	3382	1654	3646
	13	189	58.3	182	3.5	10.9	124	386	75	100	69/70	1534	3382	1654	3646
GA 90 VSD	4	58	37.0	293	2.2	17.6	78	621	90	125	73/74	1534	3382	1654	3646
	7	102	39.4	292	2.4	17.5	84	619	90	125	73/74	1534	3382	1654	3646
	10	145	48.3	257	2.9	15.4	102	545	90	125	73/74	1534	3382	1654	3646
	13	189	59.4	214	3.6	12.9	126	454	90	125	73/74	1534	3382	1654	3646

Technical specifications GA 37-90 VSD (50/60 Hz versions)

*Unit performance measured according to ISO 1217, Annex E, Edition 4

Maximum working pressure for VSD machines: 13 bar(e) (188 psig)
GA 90+-160+ / GA 110-160 VSD

Oil-injected rotary screw compressors, 90-160 kW / 125-200 hp

Efficient, reliable and built to last, the GA 90+-160+ / GA 110-160 VSD compressors are designed to provide high-quality compressed air even under harsh conditions. Every GA is designed, manufactured and tested to comply with ISO 9001, ISO 14001 and ISO 1217. They use the latest generation of Atlas Copco's oil-injected screw element, ensuring a long and trouble-free life at the lowest possible operating cost. Engineered for reliable service, even in ambient temperatures up to 55°C/131°F and very harsh environmental circumstances, the GA takes reliability to a new level. Features such as Variable Speed Drive and energy recovery lead to significant reductions in energy use and cost

CUSTOMER BENEFITS

• Highest reliability – GA compressors incorporate the latest generation of Atlas Copco's state-of-the-art compression elements based on innovative asymmetric rotor profiles, a high-quality drive system and heavy-duty air inlet filters. All these components are selected to operate continuously in the toughest conditions and at ambient temperatures up to 55°C/131°F. Together they ensure long and trouble-free life of your compressor at the lowest operating cost. • Maximum energy savings – The innovative design of our GA compressors (including screw element, motor, VSD-controlled cooling fans etc.) enables you to achieve substantial savings in your energy costs and overall compressor lifecycle costs. The GA Variable Speed Drive (VSD) reduces energy costs by a further 35% on average by automatically adjusting the air supply to your air demand. And to reduce your costs even further, install the optional energy recovery system.

• **Integrated air treatment** – The GA Full Feature with highly energy efficient integrated refrigerant dryer and air filter ensures the continuous supply of clean and dry air to extend the life of equipment, enhance system reliability and avoid costly downtime and production delays.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Easy installation** – The integrated design includes internal piping, coolers, motor, lubrication and control system: all supplied as a ready-to-use package. Installation is fault-free and commissioning time is low. Simply plug and run.



							l	Dimensi	ions									
			Air-cool	led Pacl	k			Air	cooled	Full Fea	ture		N	/ater-co	oled Pa	ick & Fu	II Featu	re
Compressor		L	۷	v		ł	1	L	۷	N		H		L	١	N	H	H
cype	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
GA 90+-160+	2600	102	2000	79	2000	79	3200	126	2000	79	2000	79	2600	102	1630	64	2000	79
GA 110-160	2600	102	2000	79	2000	79	3200	126	2000	79	2000	79	2600	102	1632	64	2000	79
GA 110-160 VSD	3200	132	2000	79	2000	79	3800	150	2002	79	2347	92	3200	156	1630	64	2347	92

	Mav	imum wo	rkina nres	sure			Canaci	tv FAD ⁽¹⁾							w	einht	
COMPRESSOR	Intura		rking pro-	55010			oupuor	y i Ab			Insta	alled	Noise			cigin	
ТҮРЕ	Pa	ck	Full Fe	ature ⁽³⁾		Pack		F	Full Featur	e	motor	power	Level ⁽²⁾	Pa	ck	Full	Feature
	bar(e)	psig	bar(e)	psig	l/s	m³/min	cfm	l/s	m³/min	cfm	kW	HP	dB(A)	kg	lb	kg	lb
GA 50 Hz																	
GA 90+ - 5.5	5.5	80	5.3	77	330	19.8	699	333	20.0	706	90	125	68	2917	6417	3310	7282
GA 90 ⁺ - 7.5	7.5	109	7.3	106	292	17.5	619	293	17.6	621	90	125	68	2917	6417	3310	7282
GA 90 ⁺ - 8.5	8.5	123	8.3	120	274	16.4	581	275	16.5	583	90	125	68	2897	6373	3290	7238
GA 90+ - 10	10	145	9.8	142	244	14.6	517	244	14.6	517	90	125	68	2709	5960	3102	6824
GA 90 ⁺ - 14	14	203	13.8	200	196	11.8	415	204	12.2	432	90	125	68	2709	5960	3102	6824
GA 110 - 7.5	7.5	109	7.3	106	342	20.5	725	343	20.6	727	110	150	69	2779	6114	3172	6978
GA 110 - 8.5	8.5	123	8.3	120	324	19.4	687	326	19.6	691	110	150	69	2779	6114	3172	6978
GA 110 - 10	10	145	9.8	142	297	17.8	629	297	21.4	754	110	150	69	2759	6070	3152	6934
GA 110 ⁺ - 5.5	5.5	80	5.3	77	401	24.1	850	404	24.2	856	110	150	69	2967	6527	3360	7392
GA 110 ⁺ - 7.5	7.5	109	7.3	106	356	21.4	754	357	21.4	756	110	150	69	2967	6527	3360	7392
GA 110 ⁺ - 8.5	8.5	123	8.3	120	337	20.2	714	338	20.3	716	110	150	69	2967	6527	3360	7392
GA 110 ⁺ - 10	10	145	9.8	142	306	23.8	839	306	18.4	648	110	150	69	2947	6483	3340	7348
GA 110 ⁺ - 14	14	203	13.8	200	245	14.7	519	252	15.1	534	110	150	69	2759	6070	3152	6934
GA 132 - 7.5	7.5	109	7.3	106	405	24.3	858	406	24.4	860	132	175	70	3134	6895	3527	7759
GA 132 - 8.5	8.5	123	8.3	120	385	23.1	816	386	23.2	818	132	175	70	3134	6895	3527	7759
GA 132 - 10	10	145	9.8	142	356	21.4	754	356	21.4	754	132	175	70	3114	6851	3507	7715
GA 132 ⁺ - 5.5	5.5	80	5.3	77	471	28.3	998	475	28.5	1006	132	175	70	3271	7196	3644	8017
GA 132 ⁺ - 7.5	7.5	109	7.3	106	424	25.4	898	425	25.5	901	132	175	70	3251	7152	3644	8017
GA 132 ⁺ - 8.5	8.5	123	8.3	120	401	24.1	850	402	24.1	852	132	175	70	3251	7152	3644	8017
GA 132 ⁺ - 10	10	145	9.8	142	368	22.1	780	368	22.1	780	132	175	70	3237	7121	3630	7986
GA 132+ - 14	14	203	13.8	200	295	17.7	625	301	18.1	638	132	175	70	3049	6708	3442	7572
GA 160 - 7.5	7.5	109	7.3	106	505	30.3	1070	506	30.4	1072	160	215	71	3361	7394	3754	8259
GA 160 - 8.5	8.5	123	8.3	120	480	28.8	1017	481	28.9	1019	160	215	71	3341	7350	3734	8215
GA 160 - 10	10	145	9.8	142	443	26.6	939	443	26.6	939	160	215	71	3341	7350	3734	8215
GA 160 ⁺ - 10	10	145	9.8	142	443	26.6	939	443	26.6	939	160	215	71	3341	7350	3734	8215
GA 160 ⁺ - 14	14	203	13.8	200	362	21.7	767	369	22.1	782	160	215	71	3327	7319	3720	8184

Technical specifications GA 90+-160+/GA 110-160/GA 110-160 VSD - 50 Hz

	Max	imum work	ing press	u re ⁽⁴⁾	(Capacity FAD	1)	Insta	alled	Noise		We	ight	
COMPRESSOR	Р	ack	Full Fe	ature ⁽³⁾	Pa	ick / Full Feat	ure	motor	power	Level ⁽²⁾	Pa	ick	Full Fe	ature
	bar(e)	psig	bar(e)	psig	l/s	m³/min	cfm	kW	HP	dB(A)	kg	lb	kg	lb
GA VSD 50 Hz														
GA 110 VSD - 8.5	3.5	72.5	5	72.5	96 - 412	5.8 - 24.7	203 - 873	110	150	71	3894	8585	4154	9158
	7	102	7	102	93 - 369	5.6 - 22.1	198 - 782	110	150	71	3894	8585	4154	9158
	8	116	8	116	92 - 348	5.5 - 20.9	194 - 737	110	150	71	3894	8585	4154	9158
GA 110 VSD - 10	6	87	6	87	95 - 389	5.7 - 23.3	201 - 824	110	150	71	3894	8585	4154	9158
	8	116	8	116	92 - 348	5.5 - 20.9	194 - 813	110	150	71	3894	8585	4154	9158
	9.5	138	9.5	138	88 - 322	5.3 - 19.3	187 - 682	110	150	71	3894	8585	4154	9158
GA 110 VSD - 14	9	131	9	131	90 - 330	5.4 -19.8	190 - 699	110	150	71	3894	8585	4154	9158
	10	145	10	145	87-314	5.2 - 18.8	184 - 665	110	150	71	3894	8585	4154	9158
	13.5	196	13.5	196	74 - 256	4.5 - 15.4	157 - 542	110	150	71	3894	8585	4154	9158
GA 132 VSD - 8.5	3.5	51	3.5	51	97 - 539	5.8 - 32.3	206 - 1142	132	175	68	3930	8646	4248	9346
	7	102	7	102	93 - 457	5.6 - 27.4	197 - 968	132	175	68	3930	8646	4248	9346
	8	116	8	116	91 - 435	5.5 - 26.1	193 - 922	132	175	68	3930	8646	4248	9346
GA 132 VSD - 10	6	87	6	87	94 - 481	5.6 - 28.9	199 - 1019	132	175	68	3930	8646	4248	9346
	8	116	8	116	91 - 435	5.5 - 26.1	193 - 922	132	175	68	3930	8646	4248	9346
	9.5	138	9.5	138	89 - 403	5.3 - 24.2	189 - 854	132	175	68	3930	8646	4248	9346
GA 132 VSD - 14	9	131	9	131	90 - 412	5.4 - 24.7	191 - 873	132	175	68	3930	8646	4248	9346
	10	145	10	145	88 - 393	5.3 - 23.5	186 - 828	132	175	68	3930	8646	4248	9346
	13.5	196	13.5	196	81 - 325	4.9 - 19.5	172 - 689	132	175	68	3930	8646	4248	9346
GA 160 VSD - 8.5	3.5	51	3.5	51	97 - 572	5.8 - 34.3	206 - 1212	160	215	69	3930	8646	4248	9346
	7	102	7	102	93 - 540	5.6 - 32.4	197 - 1144	160	215	69	3930	8646	4248	9346
	8	116	8	116	91 - 515	5.5 - 30.9	193 - 1091	160	215	69	3930	8646	4248	9346
GA 160 VSD - 10	6	87	6	87	94 - 566	5.5 - 34.0	199 - 1199	160	215	69	3930	8646	4248	9346
	8	116	8	116	91 - 515	5.5 - 30.9	193 - 1091	160	215	69	3930	8646	4248	9346
	9.5	138	9.5	138	89 - 480	5.3 - 28.8	189 - 1017	160	215	69	3930	8646	4248	9346
GA 160 VSD - 14	9	131	9	131	90 - 492	5.4 - 29.5	191 - 1042	160	215	69	3930	8646	4248	9346
	10	145	10	145	88 - 469	5.3 - 28.1	186 - 994	160	215	69	3930	8646	4248	9346
	13.5	196	13.5	196	82 - 394	4.9 - 23.6	174 - 835	160	215	69	3930	8646	4248	9346

(1) Unit Performance Measured according to ISO 1217, Ed. 3, Annex C - 1996

Reference conditions:

Absolute inlet pressure 1 bar (14.5 psi)
Intake air temperature 20°C (68°F)

• Cooling medium temperature 20°C (68°F)

(2) Noise level:

Measured according to ISO 2151: 2004 using ISO 9614/2

(3) Maximum working pressure is reduced by 0.2 bar when integrated DD filter option is selected (4) Maximum working pressure for GA VSD - 8.5; 10; 14 bar (e)/GA VSD FF - 8.3; 9.8 ; 13.8 bar(e)

Integrated dryer: Compressed air pressure dewpoint at dryer reference conditions 3°C

Integrated DD filter: Particle removal down to 1 micron and maxium remaining aerosol 0.1 mg/m³

FAD is measured at the following working pressures:

• 5.5 bar variants at 5 bar

7.5 bar variants at 7 bar
8.5 bar variants at 8 bar

• 10 bar variants at 9.5 bar

• 14 bar variants at 13.5 bar

	-																
	Maxi	mum wo	rking pres	ssure			Capaci	ty FAD ⁽¹⁾			Insta	alled	Noise		We	ight	
	Pa	ck	Full Fe	ature ⁽³⁾		Pack		F	- ull Featu	e	motor	power	Level ⁽²⁾	Pa	ick	Full Fe	eature
	bar(e)	psig	bar(e)	psig	l/s	m³/min	cfm	l/s	m³/min	cfm	kW	HP	dB(A)	kg	lb	kg	lb
GA 60 Hz																	
GA 90⁺ - 75	5.5	80	5.3	77	343	20.6	727	346	20.8	733	90	125	68	2917	6417	3310	7282
GA 90+ - 100	7.4	107	7.2	104	302	18.1	640	303	18.2	642	90	125	68	2917	6417	3310	7282
GA 90 ⁺ - 125	9.1	132	8.9	129	274	16.4	581	275	16.5	583	90	125	68	2897	6373	3290	7238
GA 90+ - 150	10.9	158	10.7	155	239	14.3	506	239	14.3	506	90	125	68	2709	5960	3102	6824
GA 90+ - 200	14	203	13.5	196	205	12.3	434	213	12.8	451	90	125	68	2709	5960	3102	6824
GA 110 - 100	7.4	107	7.2	104	350	21.0	742	352	21.1	746	110	150	69	2779	6114	3172	6978
GA 110 - 125	9.1	132	8.9	129	320	19.2	678	322	19.3	682	110	150	69	2779	6114	3172	6978
GA 110 - 150	10.9	158	10.7	155	286	17.2	606	286	17.2	606	110	150	69	2759	6070	3152	6934
GA 110 ⁺ - 75	5.5	80	5.3	77	406	24.4	860	409	24.5	867	110	150	69	2967	6527	3360	7392
GA 110 ⁺ - 100	7.4	107	7.2	104	363	21.8	769	364	21.8	771	110	150	69	2967	6527	3360	7392
GA 110 ⁺ - 125	9.1	132	8.9	129	331	19.9	701	332	19.9	703	110	150	69	2967	6527	3360	7392
GA 110 ⁺ - 150	10.9	158	10.7	155	295	17.7	625	295	17.7	625	110	150	69	2947	6483	3340	7348
GA 110 ⁺ - 200	14	203	13.5	196	248	14.9	525	255	15.3	540	110	150	69	2759	6070	3152	6934
GA 132 - 100	7.4	107	7.2	104	403	24.2	854	405	24.3	858	132	175	70	3134	6895	3527	7759
GA 132 - 125	9.1	132	8.9	129	370	22.2	784	371	22.3	786	132	175	70	3134	6895	3527	7759
GA 132 - 150	10.9	158	10.7	155	336	20.2	712	336	20.2	712	132	175	70	3114	6851	3507	7715
GA 132+ - 75	5.5	80	5.3	77	467	28.0	990	471	28.3	998	132	175	70	3271	7196	3644	8017
GA 132 ⁺ - 100	7.4	107	7.2	104	421	25.3	892	422	25.3	894	132	175	70	3251	7152	3644	8017
GA 132 ⁺ - 125	9.1	132	8.9	129	385	23.1	816	386	23.2	818	132	175	70	3251	7152	3644	8017
GA 132 ⁺ - 150	10.9	158	10.7	155	346	20.8	733	346	20.8	733	132	175	70	3237	7121	3630	7986
GA 132+ - 200	14	203	13.5	196	290	17.4	614	296	17.8	627	132	175	70	3049	6708	3442	7572
GA 160 - 100	7.4	107	7.2	104	475	28.5	1006	477	28.6	1011	150	200	71	3361	7394	3754	8259
GA 160 - 125	9.1	132	8.9	129	437	26.2	926	438	26.3	928	150	200	71	3341	7350	3734	8215
GA 160 - 150	10.9	158	10.7	155	397	23.8	841	397	23.8	841	150	200	71	3341	7350	3734	8215
GA 160 ⁺ - 150	10.9	158	10.7	155	397	23.8	841	397	23.8	841	150	200	71	3341	7350	3734	8215
GA 160 ⁺ - 200	14	203	13.5	196	337	20.2	714	345	20.7	731	150	200	71	3327	7319	3720	8184

Technical specifications GA 90+-160+/GA 110-160/GA 110-160 VSD - 60 Hz

	Max	kimum we	orking pre	essure ⁽⁴⁾		Capacity FAD	1)	Insta	alled	Noise		We	eight	
COMPRESSOR	Pa	ick	Full I	eature ⁽³⁾	I	Pack / Full Feat	ıre	motor	power	Level ⁽²⁾	Pa	ick	Ful	l Feature
11112	bar(e)	psig	bar(e)	psig	l/s	m³/min	cfm	kW	HP	dB(A)	kg	lb	kg	lb
GA VSD 60 Hz														
GA 110 VSD - 125	3.5	72.5	5	72.5	96 - 412	5.7 - 24.5	203 - 867	110	148	71	3894	8585	4154	9158
	7	102	7	102	93 - 371	5.6 - 22.2	198 - 786	110	148	71	3894	8585	4154	9158
	8	116	8	116	90 - 336	5.4 - 20.0	191 - 711	110	148	71	3894	8585	4154	9158
GA 110 VSD - 150	6	87	6	87	95 - 389	5.7 - 23.3	201 - 824	110	148	71	3894	8585	4154	9158
	8	116	8	116	90 - 336	5.4 - 20.0	192 - 712	110	148	71	3894	8585	4154	9158
	9.5	138	9.5	138	86 - 307	5.1 - 18.4	182 - 651	110	148	71	3894	8585	4154	9158
GA 110 VSD - 200	9	131	9	131	90 - 330	5.3 - 19.8	190 - 699	110	148	71	3894	8585	4154	9158
	10	145	10	145	86 - 307	5.2 - 18.4	182 - 650	110	148	71	3894	8585	4154	9158
	13.5	196	13.5	196	74 - 256	4.4 - 15.3	157 - 543	110	148	71	3894	8585	4154	9158
GA 132 VSD - 125	3.5	51	3.5	51	97 - 539	5.8 - 32.3	206 - 1142	132	175	68	3930	8646	4248	9346
	6.9	100	6.9	100	93 - 459	5.6 - 27.5	197 - 973	132	175	68	3930	8646	4248	9346
	8.6	125	8.6	125	90 - 422	5.4 - 25.2	191 - 890	132	175	68	3930	8646	4248	9346
GA 132 VSD - 150	6	87	6	87	94 - 481	5.4 - 25.2	191 - 890	132	175	68	3930	8646	4248	9346
	8.6	125	8.6	125	90 - 422	5.4 - 25.2	191 - 890	132	175	68	3930	8646	4248	9346
	10.4	151	10.4	151	87 - 386	5.2 - 23.0	184 - 812	132	175	68	3930	8646	4248	9346
GA 132 VSD - 200	9	131	9	131	90 - 414	5.4 - 24.7	191 - 873	132	175	68	3930	8646	4248	9346
	10.4	151	10.4	151	87 - 386	5.2 - 23.0	184 - 812	132	175	68	3930	8646	4248	9346
	13.5	196	13.5	196	81 - 325	4.9 - 19.5	172 - 689	132	175	68	3930	8646	4248	9346
GA 160 VSD - 125	3.5	51	3.5	51	97 - 579	5.8 - 34.3	206 - 1212	160	215	69	3930	8646	4248	9346
	6.9	100	6.9	100	93 - 543	5.6 - 32.6	197 - 1151	160	215	69	3930	8646	4248	9346
	8.6	125	8.6	125	90 - 501	5.4 - 30.1	191 - 1062	160	215	69	3930	8646	4248	9346
GA 160 VSD - 150	6	87	6	87	94 - 566	5.6 - 34.0	199 - 1199	160	215	69	3930	8646	4248	9346
	8.6	125	8.6	125	90 - 501	5.4 - 30.1	191 - 1062	160	215	69	3930	8646	4248	9346
	10.4	151	10.4	151	87 - 461	5.2 - 27.7	184 - 977	160	215	69	3930	8646	4248	9346
GA 160 VSD - 200	9	131	9	131	90 - 492	5.4 - 29.5	191 - 1042	160	215	69	3930	8646	4248	9346
	10.4	151	10.4	151	87 - 461	5.2 - 27.7	184 - 977	160	215	69	3930	8646	4248	9346
	13.5	196	13.5	196	82 - 394	4.9 - 23.6	174 - 835	160	215	69	3930	8646	4248	9346

(1) Unit Performance Measured according to ISO 1217, Ed. 3, Annex C - 1996

Reference conditions:

Absolute inlet pressure 1 bar (14.5 psi)
Intake air temperature 20°C (68°F)

• Cooling medium temperature 20°C (68°F)

(2) Noise level:

Measured according to ISO 2151: 2004 using ISO 9614/2

(3) Maximum working pressure is reduced by 0.2 bar when integrated DD filter option is selected

(4) Maximum working pressure for GA VSD - 8.5; 10; 14 bar (e)/GA VSD FF - 8.3; 9.8; 13.8 bar(e) Integrated dryer: Compressed air pressure dewpoint at dryer reference conditions 3°C

Integrated DD filter: Particle removal down to 1 micron and maxium remaining aerosol 0.1 mg/m³ FAD is measured at the following working pressures:

• 75 psi variants at 73 psi

100 psi variants at 100 psi
125 psi variants at 125 psi

• 150 psi variants at 150 psi • 200 psi variants at 200 psi

GA 200-500 (VSD)

Atlas Copco's GA 200-500 (VSD) oil-injected rotary screw compressors are designed and built to provide the maximum free air delivery at the lowest energy costs. The robust design ensures your process will function continuously even in the harshest conditions such as temperatures up to 46°C/115°F.

CUSTOMER BENEFITS

• Highest reliability – Our GA 200-500 (VSD) compressors incorporate a superior oil-injected screw element based on innovative asymmetric rotor profiles and a high-quality drive system. All components are selected to ensure a long and trouble-free life of your compressor at the lowest operating cost. ,

• Reduced energy costs – The GA Series' superior screw elements are designed to give the optimum combination of maximum free air delivery for low energy consumption. The state-of-the-art compressor

element is powered by Efficiency 1 class/NEMA EPAct electric motors, contributing to maximum compressor package efficiency. Beside this, the GA 315 VSD can offer additional energy savings of on average 35% by automatically adjusting the motor speed to the air demand.

• Integrated air treatment – The GA Full Feature with highly energyefficient integrated refrigerant dryer and air filter ensures the continuous supply of clean and dry air to extend the life of equipment, enhance system reliability and avoid costly downtime and production delays.

• Advanced control monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Easy installation** – The integrated design includes internal piping, coolers, motor, lubrication and control system: all supplied as a ready-to-use package. Installation is fault-free and commissioning time is low. Simply plug and run.



COMPRESSOR	Ма	ximum wo	rking press	sure	Ca	apacity FAI) ⁽¹⁾	Installe	d motor	Noise Ievel ⁽²⁾		We	ight	
ТҮРЕ	Pa	ck	Full F	eature	Pac	k / Full Fea	ture				Pa	ick	Full F	eature
	bar(e)	psig	bar(e)	psig	l/s	m³/ min	cfm	kW	hp	dB(A)	kg	lb	kg	lb
GA 200-500 Twin														
GA 200	7.5	109	7.25	105	603	36.1	1278	200	270	75	4727	10421	5127	11303
	8.5	123	8.25	120	568	34.0	1204	200	270	75	4727	10421	5127	11303
	10	145	9.75	141	513	30.7	1087	200	270	75	4727	10421	5127	11303
	13	189	12.75	185	436	26.1	924	200	270	75	4727	10421	5127	11303
GA 250	7.5	109	7.25	105	730	43.7	1548	250	335	75	5017	11060	5417	11942
	8.5	123	8.25	120	697	41.7	1477	250	335	75	5017	11060	5417	11942
	10	145	9.75	141	631	37.8	1338	250	335	75	5017	11060	5417	11942
	13	189	12.75	185	530	31.7	1124	250	335	75	5017	11060	5417	11942
GA 315	7.5	109	-	-	928	55.8	1966	315	420	72	7510	16559	-	-
	8.5	123	-	-	864	51.9	1831	315	420	72	7510	16559	-	-
	10	145	-	-	784	47.1	1661	315	420	72	7510	16559	-	-
GA 355	7.5	109	-	-	1050	63.1	2225	355	475	73	7760	17110	-	-
	8.5	123	-	-	969	58.2	2053	355	475	73	7760	17110	-	-
	10	145	-	-	890	53.5	1886	355	475	73	7760	17110	-	-
	13	189	-	-	731	43.9	1549	355	475	73	7760	17110	-	-
GA 400	7.5	109	-	-	1175	70.6	2490	400	535	74	8360	18433	-	-
	8.5	123	-	-	1109	66.6	2350	400	535	74	8360	18433	-	-
	10	145	-	-	1011	60.8	2142	400	535	74	8360	18433	-	-
	13	189	-	-	844	50.7	1788	400	535	74	8360	18433	-	-
GA 450	7.5	109	-	-	1298	78.0	2750	450	600	75	8360	18433	-	-
	8.5	123	-	-	1240	74.5	2628	450	600	75	8360	18433	-	-
	10	145	-	-	1144	68.8	2424	450	600	75	8360	18433	-	-
	13	189	-	-	960	57.7	2034	450	600	75	8360	18433	-	-
GA 500	7.5	109	-	-	1410	84.7	2988	500	670	76	7960	17551	-	-
	8.5	123	-	-	1347	80.9	2854	500	670	76	7960	17551	-	-
	10	145	-	-	1257	75.5	2664	500	670	76	7960	17551	-	-
	13	189	-	-	1068	64.2	2263	500	670	76	7960	17551	-	-

GA compressor range - 50 Hz: air and water-cooled variants

GA 500 figures are for medium voltage IP 23 motor

COMPRESSOR	Ма	ximum wo	rking press	sure	Ca	apacity FAD	j (1)	Installe	d motor	Noise level ⁽²⁾		Weigh	ıt	
ТҮРЕ	Pa	ick	Full F	eature	Pac	k / Full Fea	ture				P	ack	Full	Feature
	bar(e)	psig	bar(e)	psig	l/s	m³/ min	cfm	kW	hp	dB(A)	kg	lb	kg	lb
GA 200-315 Twin														
GA 200-100	7.4	107	7.15	104	586	35.1	1242	185	250	76	4957	10928	5357	11810
GA 200-125	9.1	132	8.85	128	532	32.0	1128	185	250	76	4957	10928	5357	11810
GA 200-150	10.8	157	10.55	153	483	29.0	1024	185	250	76	4957	10928	5357	11810
GA 250-100	7.4	107	7.15	104	683	41.0	1448	225	300	76	5057	11149	5457	12030
GA 250-125	9.1	132	8.85	128	620	37.1	1314	225	300	76	5057	11149	5457	12030
GA 250-150	10.8	157	10.55	153	569	34.1	1206	225	300	76	5057	11149	5457	12030
GA 250-200	13.8	200	13.55	196	477	28.6	1011	225	300	76	5057	11149	5457	12030
GA 315-100	7.4	107	7.15	104	777	46.5	1647	260	350	76	5257	11590	5657	12470
GA 315-125	9.1	132	8.85	128	707	42.3	1499	260	350	76	5257	11590	5657	12470
GA 315-150	10.8	157	10.55	153	660	39.5	1399	260	350	76	5257	11590	5657	12470
GA 315-200	13.8	200	13.55	196	555	33.2	1177	260	350	76	5257	11590	5657	12470
GA 355-100	7.4	107	-	-	1032	62.1	2191	335	450	73	7760/7860	17110/17331	-	-
GA 355-125	9.1	132	-	-	940	56.5	1992	335	450	73	7760/7860	17110/17331	-	-
GA 355-150	10.8	157	-	-	831	49.9	1761	335	450	73	7760/7860	17110/17331	-	-
GA 355-200	13.8	200	-	-	692	41.6	1466	335	450	73	7760/7860	17110/17331	-	-
GA 400-100	7.4	107	-	-	1128	67.9	2394	372	500	74	8360/7960	18433/17551	-	-
GA 400-125	9.1	132	-	-	1042	62.6	2208	372	500	74	8360/7960	18433/17551	-	-
GA 400-150	10.8	157	-	-	935	56.2	1981	372	500	74	8360/7960	18433/17551	-	-
GA 400-200	13.8	200	-	-	784	47.1	1661	372	500	74	8360/7960	18433/17551	-	-
GA 450-100	7.4	107	-	-	1334	80.4	2835	447	600	75	8360/8620	18433/19007	-	-
GA 450-125	9.1	132	-	-	1222	73.4	2589	447	600	75	8360/8620	18433/19007	-	-
GA 450-150	10.8	157	-	-	1126	67.7	2386	447	600	75	8360/8620	18433/19007	-	-
GA 450-200	13.8	200	-	-	943	56.7	1998	447	600	75	8360/8620	18433/19007	-	-
GA 500-100	7.4	107	-	-	1518	91.2	3217	522	700	76	7960	17551	-	-
GA 500-125	9.1	132	-	-	1404	84.4	2975	522	700	76	7960	17551	-	-
GA 500-150	10.8	157	-	-	1296	77.9	2746	522	700	76	7960	17551	-	-
GA 500-200	13.8	200	-	-	1114	66.9	2361	522	700	76	7960	17551	-	-

GA compressor range - 60 Hz: air and water-cooled variants

GA 500W figures are for medium voltage IP 23 motor. GA 355W - GA 400W - GA 450W: two different motor types used for IEC/CSA-UL at 60Hz low voltage

(1) Unit performance measured according to ISO 1217 (1996)

Reference conditions:

- absolute inlet pressure 1 bar (14.5 psi)

- intake air temperature 20°C (68°F)

FAD is measured at the following working pressures:

- 7.5 bar variants at 7 bar
 8.5 bar variants at 8 bar
 10 bar variants at 9.5 bar
 150 psi variants at 150 psi

- 13 bar variants at 12.5 bar - 200 psi variants at 193 psi - 20 bar variants at 19 bar

- 290 psi variants at 276 psi

(2) Noise level:

measured according to Pneurop / Cagi PN8NTC2.2 test code; tolerance ±3 dB(A) Integrated dryer:

pressure dewpoint of integrated refrigerant dryer at reference conditions: 3 to 4°C Integrated filter:

particle removal down to 1 micron and maximum remaining oil aerosol of 0.1 mg/m³

GR 110-200

Oil-injected rotary screw compressors, 110-200 kW / 150-270 hp

Atlas Copco's GR 110-200 oil-injected rotary screw compressors are ideal for highpressure applications requiring a reliable air supply of 13 and 20 bar. The installation, operation and maintenance of these robust and reliable machines is kept simple. Their two-stage design ensures the most efficient operation at higher pressure. Our GR 110-200 compressors will cut your costs and enable smooth, continuous operation right across your production processes. You can choose from air- or water-cooled versions.

CUSTOMER BENEFITS

• **High reliability** – The two-stage compression element features an asymmetric rotor profile you can rely on. Thanks to the extremely reduced load on bearings, rotors and gears, the element lifetime is long, ensuring low wear and tear and reliability at the lowest operating cost.

• Advanced control monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Easy installation** – The GR 110-200 is truly plug-and-play. Simply put the machine on a flat floor, connect the power line and the compressed air outlet, and push the start button.

• **Minimal maintenance** – GR 110-200 compressors are designed for trouble-free maintenance, with easily accessible oil and air filters and simple cooler cleaning procedures.

COMPRESSOR	Ма	x. worki	ng pressu	re		Capacit FAD*	V	Install Motor Pe	ed ower	Noise Level**		Wei	ight	
ТҮРЕ	Pa	ck	Full Fe	ature	Pac	k/ Full Fe	ature				Pac	k	Full F	eature
	bar(e)	psig	bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	kg	lb	kg	lb
GA 315 VSD														
GA 315 VSD	4	58	4	58	854	51.2	1810	290	390	75	6165	13563	6615	14553
	7	109	7	109	847	50.8	1795	290	390	75	6165	13563	6615	14553
	10	145	9.9	143	710	42.6	1505	290	390	75	6165	13563	6615	14553
GR 110 - 200 Two stage	e 13 bar													
GR 110	13	189	12.75	185	255	15.3	541	110	150	72	3140	6908	3470	7634
GR 132	13	189	12.75	185	308	18.5	653	132	175	75	3140	6908	3470	7634
GR 160	13	189	12.75	185	369	22.1	782	160	215	75	3547	7803	3877	8529
GR 200	13	189	12.75	185	437	26.2	926	200	270	76	3547	7803	3877	8529
GR 110 - 200 Two stage	e 20 bar													
GR 110	20	290	19.75	286	211	12.6	447	110	150	72	3140	6908	3470	7634
GB 200	20	290	19.75	286	385	23.1	816	200	270	75	3547	7803	3877	8529

GA VSD/ GR Compressor range 50Hz

* Unit performance measured according to ISO 1217, Annex C, Edition 4

Reference conditions:

Absolute inlet pressure 1 bar (14.5 psi)

• Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

•	7.5	bar	versions	at	7	ba
---	-----	-----	----------	----	---	----

- 8.5 bar versions at 8 bar
- 10 bar versions at 9.5 bar
 13 bar versions at 12.5 bar
- 20 bar versions at 20 bar
- ** Noise Level

measured according to Pneurop/Cagi PN8NTC2.2 test code; tolerance ±3 dB(A) Interarated Dryer.

Pressure dewpoint of intergrated refrigerant dryer at reference conditions: 3 to 4°C Intergrated Filter:

• 100 psi variants at 100 psi

125 psi variants at 125 psi
150 psi variants at 150 psi

200 psi variants at 200 psi

290 psi variants at 290 psi

Partical removal down to 1 micron and maximum remaining oil aerosol of 0.1mg/m³

			Dimer	isions		
Compressor	1	4	E	3	(;
type	mm	inch	mm	inch	mm	inch
GA 200 - 315	3386	133.3	2120	83.4	2400	94.4
GA 315 - 500A*	5855	230.5	2120	83.4	2500	98.4
GA 315 - 500W*	4173	164.3	2120	83.4	2500	98.4
GA 315 VSD	4000	157.4	2120	83.4	2400	94.4
GR 110-200	2779	109.4	1886	74.3	1990	78.3

* W = Water-cooled

A = Air-cooled

GA VSD/ GR Compressor range 60Hz

COMPRESSOR	Ма	x. worki	ng pressu	re		Capacity FAD*	V	Install Motor P	led ower	Noise Level**		Wei	ight	
ТҮРЕ	Pa	ck	Full Fe	ature	Pac	k/ Full Fe	ature				Pac	k	Full F	eature
	bar(e)	psig	bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	kg	lb	kg	lb
GA 315 VSD														
GA 315 VSD	4	58	4	58	854	51.2	1810	290	390	75	6165	13563	6615	14553
	7	109	7	109	847	50.8	1795	290	390	75	6165	13563	6615	14553
	10	145	9.9	143	710	42.6	1505	290	390	75	6165	13563	6615	14553
GR 110 - 200 Two stage	e 13 bar													
GR 110-200	13.8	200	13.55	196	261	15.6	541	110	150	72	3140	6908	3470	7634
GR 160-200	13.8	200	13.55	196	350	21.0	782	150	200	75	3547	7803	3877	8529
GR 200-290	13.8	200	13.55	196	442	26.5	926	185	250	78	3547	7803	3877	8529
GR 110 - 200 Two stage	e 20 bar													
GR 110-290	20	290	19.75	286	224	13.4	475	110	150	72	3140	6908	3470	7634
GR 200-290	20	290	19.75	286	384	23.0	814	200	270	78	3547	7803	3877	8529

* Unit performance measured according to ISO 1217, Annex C, Edition 4

Reference conditions:

• Absolute inlet pressure 1 bar (14.5 psi)

• Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:

• 7.5 bar versions at 7 bar • 8.5 bar versions at 8 bar • 10 bar versions at 9.5 bar

• 13 bar versions at 12.5 bar

• 20 bar versions at 20 bar

- 100 psi variants at 100 psi 125 psi variants at 125 psi
 - 120 psi variants at 120 psi
 150 psi variants at 150 psi
 200 psi variants at 200 psi
 290 psi variants at 290 psi
- ** Noise Level

measured according to Pneurop/Cagi PN8NTC2.2 test code; tolerance ±3 dB(A) Intergrated Dryer:

Pressure dewpoint of intergrated refrigerant dryer at reference conditions: 3 to $4^{\circ}{\rm C}$ Intergrated Filter:

Partical removal down to 1 micron and maximum remaining oil aerosol of $0.1 mg/m^3$



			Dimer	nsions		
Compressor	1	4	I	3	(C
туре	mm	inch	mm	inch	mm	inch
GA 200 - 315	3386	133.3	2120	83.4	2400	94.4
GA 315 - 500A*	5855	230.5	2120	83.4	2500	98.4
GA 315 - 500W*	4173	164.3	2120	83.4	2500	98.4
GA 315 VSD	4000	157.4	2120	83.4	2400	94.4
GR 110-200	2779	109.4	1886	74.3	1990	78.3

* W = Water-cooled

A = Air-cooled

B&D

Oil-lubricated high-pressure reciprocating compressors, up to 450 bar (a) (6500 psia), 37-150 kW.

Atlas Copco's B&D series of oil-lubricated reciprocating compressors meet your needs for high-pressure compressed air up to 450 bar(a). These flexible compressors offer capacities from 150 m3/min to 2000 m³/ min on certain configurations. Compact, with very low vibration levels and a sealed crankcase, B&D compressors are the perfect solution for the compression of air, nitrogen, natural gas, processed biogas, hydrogen, noble gases and other industrial gases. They are based on technology developed by GreenField, a company with a renowned reputation worldwide and part of the Atlas Copco Group.

CUSTOMER BENEFITS

• **Safety** – A sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.

• **High reliability** – The B&D piston technology offers field-proven ruggedness and reliability. Low compression ratios in the individual stages result in low thermal load for high reliability and high volumetric efficiency.

• **Easy installation** – Very compact, frame-mounted and incorporating anti-vibration pads, B&D compressors come as complete all-in packages. All designs are submitted as turnkey installations, virtually assuring the equipment is ready for operation soon after its arrival. This is a testament to their ease of installation.

• A wide array of solutions – B&D compressors are available for inlet pressures from 1 to 14 bar, and 1- to 5-stage configurations.

• Low maintenance – An advanced maintenance concept ensures short downtimes and long intervals between maintenance.



TECHNICAL SPECIFICATIO	TECHNICAL SPECIFICATIONS							
Capacity FAD (I/s)	12 - 142 l/s							
Working pressure	17 - 451 bar(e)							
Installed motor power	15 - 165 kW							
Capacity	42 - 510 Nm³/h							
Inlet pressure	0.06 - 2 bar							
Gases handled	air, nitrogen, helium, hydrogen, methane, biomethane							

CU/CT/CN

Oil-lubricated high pressure trunk-piston compressors, up to 351 bar(a) (5090 psia), 22-200 kW.

Atlas Copco's CU/CT/CN is a complete series of oil-lubricated reciprocating compressors to meet your needs for high pressures up to 351 bar(a). Compact, with very low vibration levels and a sealed crankcase, CU/CT/ CN compressors are the perfect solution for the compression of air, nitrogen, natural gas, processed biogas, hydrogen, noble gases and other industrial gases. They are based on technology developed by GreenField, a company with a renowned reputation worldwide and part of the Atlas Copco Group.

CUSTOMER BENEFITS

• **High level of safety** – A pressure-tight sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.

• **High reliability** – The CU/CT/CN trunk-piston technology offers field-proven ruggedness and reliability. Low compression ratios in the individual stages result in low thermal load for high reliability and high volumetric efficiency.

• **Easy installation** – Very compact, frame-mounted and incorporating anti-vibration pads, CT/CU/CN compressors come as complete all-in packages that are simple to install without the need for foundations.

• Low maintenance – An advanced maintenance concept ensures short downtimes and long intervals between maintenance.

• A wide array of solutions – CU/CT compressors are available for inlet pressures from 1 to 19 bars, and up to 5-stage configurations. Discharge pressures are up to 350 bar for CU and for CT, while CN units are available for inlet pressures from atmosphere to 1.35 bar(a) for pressures up to 350 bar. They are suitable for diverse applications: CNG car/bus refueling stations, H2 refueling systems, bottle filling, air-blast circuit breakers. A specific range of CU/CT compressors has been designed for seismic applications, for installation onboard ships, with closed loop freshwater/seawater cooling and marine adaptations.



TECHNICAL SPECIFICATIO	NS
Capacity FAD (I/s)	4.2 - 445 l/s
Working pressure	1 - 351 bar(e)
Installed motor power	30 - 200 kW
Capacity	15 - 1600 Nm³/h
Inlet pressure	1 - 19 bar
Gases handled	air, nitrogen, carbon monoxide, carbon dioxide, helium, hydrogen, argon, methane, biomethane

GG Oil-lubricated gas screw compressors, 16 bar(a) (232 psia)

Atlas Copco's lubricated gas screw compressors meet your needs for methane and biomethane applications for pressures up to 16 bar(a) (232 psia). Single-stage, watercooled and directly-driven, these compressors benefit from the latest technologies with exclusive bearing arrangements and variable speed drive. They comply with ATEX design requirements.

CUSTOMER BENEFITS

• Efficient capacity control – Variable Speed Drive can regulate the capacity of the compressor to keep inlet and outlet pressures constant, depending on the application.

• High efficiency and consistent performance – The GG's highly efficient rotor profile maximizes the flow and minimizes the horsepower. Direct drive through a flexible coupling means no gear losses or wasted energy.

• **Sturdy design** – A triplex bearing arrangement has an L-10 calculated life of 130,000 hours. Superior shaft seal design and unparalleled precision manufacturing combine to ensure durable quality year after year. This makes the SG gas compressor the optimal solution for gas applications.

• **Compact and easy to install** – This single stage compressor takes up minimal floor space. Frame-mounted, the GG gas compressor comes as a complete all-in package which can easily be integrated in your process.



TECHNICAL SPECIFICATIO	TECHNICAL SPECIFICATIONS								
Capacity FAD (I/s)	136 - 278 l/s								
Capacity FAD (m ³ /h, cfm)	102 - 900 m³/h								
Working pressure	1.55 - 17 bar(e)								
Installed motor power	90 - 132 kW								
Capacity	450 - 920 Nm³/h								
Inlet pressure	1.4 bar (a)								
Gases handled	processed biomethane								

S100/S750 Car and bus refueling stations.

Atlas Copco's S100/S750 car and bus modular refueling stations are compact highperformance installations designed for the refueling of passenger cars, indoor and lightduty vehicles, buses, heavy-duty trucks, ferries and special vehicles with natural gas (CNG/NGV), biogas and H2. They are based on technology developed by GreenField, a company with a renowned reputation worldwide and part of the Atlas Copco Group

CUSTOMER BENEFITS

• **High level of safety** – A pressure-tight sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.

• **Total solution** – With Atlas Copco you get total customer service, from a comprehensive study of the station layout to the delivery of the complete units

• A wide array of solutions – We provide fast-fill, low-fill or motherdaughter systems to meet your needs for standard to customized stations

• Based on our high-performance compressors:

 - CU/CT series – Lubricated trunk-piston technology, air- or water-cooled, with sealed crankcase – gas-tight up to 19 bar(a) (260 psig) – for capacities up to 1600 Nm³/h (1000 scfm).

 - DM series – Oil-less, hermetically sealed compressors – gas-tight up to 40 bar(a) (570 psig) – for capacities up to 210 Nm³/h (125 scfm).

• Compact – Available in concrete or sheet metal housing, their compact design is an asset on site

- Modular Our standard stations are adapted to:
- Up to 250 cars, 50 trucks or 25 buses per day
- Up to 150 cars, 30 trucks or 15 buses per day
- Up to 450 cars, 90 trucks or 45 buses per day



TECHNICAL SPECIFICATIO	TECHNICAL SPECIFICATIONS							
Type of vehicle	buses, cars, others							
Filling time (cars)	150 to 450 cars per day							
Filling time (buses)	15 to 45 buses per day							
Filling time (others)	30 to 90 trucks per day							
Type of vehicle	Bus							

OIL-FREE COMPRESSORS

If you require oil-free compressed air for sensitive processes within the food and drink industries, in a dairy or a brewery, in medical technology or electronic manufacturing, then compromises are not an option. Many processes in the pharmaceutical industry, surface refinement or the textile industry are also completely dependent on oil-free compressed air.

Oil-free compressed air

If you require oil-free compressed air for sensitive processes within the food and drink industries, in a dairy or a brewery, in medical technology or electronic manufacturing, then compromises are not an option. Many processes in the pharmaceutical industry, surface refinement or the textile industry are also completely dependent on oil-free compressed air.



Atlas Copco is the first manufacturer of oil-free compressors that have achieved a compressed air quality of Class 0 in accordance with DIN-ISO 8573-1 – certified by the TÜV. This is because the air never comes into contact with oil throughout the compression stages of the Z compressors from Atlas Copco. Therefore, it does not have to be laboriously filtered again with a high power input. There is also no residual risk of contaminating the product during its contact with the compressed air.

We can provide a suitable oil-free solution for any application, any volume flow and (almost) any working pressure; from 0.4 bar, for example, for aerating sewage plants, up to 40 bar for producing PET bottles. Potential options include:

Our ZR/ZT compressors, for the most popular applications and pressures (up to 13 bar), are available with rotary technology for medium volume flows or with screw compression for improved performance. Air or water-cooled. They are available with speed regulation (VSD - Variable Speed Drive), if required, allowing you to save up 35% power on average, and the additional costs for the integrated frequency converter usually pay for themselves within one to two years. If you want, you can choose the Full Feature version (FF), which also has an integrated refrigerant or desiccant dryer.

Or our ZB Turbos and ZS blower for applications with low pressure (from 0.4 to 1.7 bar working pressure). If you want to use pneumatic feed, ventilate biological clarifiers, or clean filters in power plants, these machines are the perfect solution. With the ZS+ blowers you can lower your power consumption, in comparison to conventional, belt-driven rotary piston blowers, by up to 40%, and the ZB centrifugal compressors with speed regulation save as much as 60% power compared to normal full-load/idle machines. This is because the turbo impellers are a very special patented development from Atlas Copco – with extremely high efficiency.

Our ZH Turbos are hard to beat when it comes to efficiency. They are suitable for heavy industry, where an extremely high amount of air with working pressures between 3.5 and 10.4 bar is continually required; for example, a few thousand to tens of thousands cubic meters per hour.



LFx series

Compact oil-free piston compressors, 0.5-1.5 kW / 0.7-2 hp

The LFx ensures highly energy-efficient compressed air generation thanks to the patented "Super-flow" compressed air inlet system.

• LFx 0.7-2.0 | Page 53 - 54



AQ 30-55 / 15-55 VSD

Water-injected screw compressors, 15-55 kW / 20-75 hp

Atlas Copco's AQ water-injected screw compressors, available in water-cooled and aircooled versions, meet your precise needs for pure, oil-free air while offering high-pressure capability and improved energy efficiency.

• AQ 30-55 / 15-55 VSD | Page 60 - 62



LF series

Industrial oil-free aluminum piston compressors, 1.5-7.5 kW / 2-10 hp

Atlas Copco's LF oil-free aluminium piston air compressors stand for exceptional reliability and extremely low operating costs and are virtually maintenance-free.

• LF | Page 55 - 56



ZT 15-22, ZR/ZT 30-45, ZR/ZT 22-37-55 VSD

Oil-free rotary tooth compressors, 15-55 kW / 20-75 hp

Atlas Copco's ZR/ZT oil-free rotary tooth compressors meet your needs for pure oil-free air while offering wide pressure ranges and improved energy efficiency.

- ZT 15-22 | Page 64
- ZR/ZT 30-45 | Page 64
- ZR/ZT 22-37-55 VSD | Page 64



SF series

Oil-free scroll compressors, 1.5-22 kW / 2-30 hp

Atlas Copco's SF oil-free scroll compressors provide 100% oil-free for critical applications in industries such as R&D laboratories, hospitals, universities, dental applications, food & beverage.

• SF 1 - 22 | Page 57 - 59



Z 55-900 (VSD)

Oil-free air- and water-cooled rotary screw compressors, 55-935 kW / 75-1253 hp

Atlas Copco's Z 55-900 VSD Pack and Full Feature ranges power your production with ultimate reliability and efficiency under the harshest conditions.

- ZR 55 90 FF | Page 67 68
- ZR 75 90 VSD FF | Page 67 68
- ZR 110 750 | Page 69 72
- ZR 132 900 VSD | Page 72
- ZT 110 275 | Page 73 75
- ZT 132 315 VSD | Page 75



ZH series

Oil-free centrifugal compressors, 400-2750 kW, 500-3500 hp

Designed to save energy and guarantee reliability, Atlas Copco's ZH oil-free centrifugal compressors are provided as complete ready-to-integrate packages including internal piping, integrated coolers, motor, lubrication, inlet guide vanes, control system and 100% matched components.

• ZH | Page 76



ZH 350+

Oil-free high-speed drive centrifugal compressors, 350 kW, 470 hp

Atlas Copco's ZH 350+ oil-free centrifugal compressors are designed to save you energy. Operating at high speed and high efficiency, they are directly driven by a permanent magnet synchronous motor.

• ZH 350+ | Page 79

LFx 0.7 - 2.0 series

Compact oil-free piston compressors, 0.5-1.5 kW / 0.7-2 hp

Atlas Copco's range of small-capacity piston compressors provides you a reliable, oil-free solution for your low air demands. The LFx ensures highly energy-efficient compressed air generation thanks to the patented "Super-flow" compressed air inlet system.

The LFx compressors' capacities range from from 1.02 up to 2.53 l/s (2.16 up to 5.36 cfm), with an optional 1- or 3-phase supply and a maximum working pressure of 10 bar (145 psi).

CUSTOMER BENEFITS

• Flexible installation – The LFx's small and compact design offer maximum installation flexibility. The LFx is both suitable for stand-alone use and integration in your OEM (Original Equipment Manufacturer) product.

• **High reliability** – Thanks to a unique, robust design and the optimal combination of quality materials, LFx compressors offer improved performance and extended product life.

• **Certified 100% oil-free air** – LFx piston compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

• **Easy maintenance** – All components and service points are easily accessible and your LFx requires no oil changes.

• **Quiet operation** – The LFx is standard outfitted with a silencing hood. These compressors achieve noise levels as low as 62 dB(A), allowing installation close at the point of use.





		Maximu	m dimensions	We	Noise level	
		mm (W x D x H)	inch (W x D x H)	kg	lbs	dB(A)
Downerbow	LFx 0.7/1.0	520 x 340 x 490	20.5 x 13.4 x 19.3	25	55	62-63
Powerbox	LFx 1.5/2.0	520 x 340 x 490	20.5 x 13.4 x 19.3	29	63	63-64
Trolley	LFx 0.7/1.0	520 x 440 x 824	20.5 x 17.3 x 32.4	44	97	62-64
(receiver 20 I)	LFx 1.5/2.0	520 x 440 x 824	20.5 x 17.3 x 32.4	48	105	62-64
Tank mounted	LFx 0.7/1.0	828 x 355 x 891	32.6 x 14 x 35	49	108	65-67
(vessel 50 l)	LFx 1.5/2.0	828 x 355 x 891	32.6 x 14 x 35	53	117	65-67
Tank mounted	LFx 0.7/1.0	960 x 364 x 973	37.8 x 14.3 x 38.3	64	141	65-67
(vessel 90 l)	LFx 1.5/2.0	960 x 364 x 973	37.8 x 14.3 x 38.3	68	149	65-67

* Unit performance measured according to ISO 1217, Ed.3, Annex C-1996.

Reference conditions: • Absolute inlet pressure 1 bar (14.5 psi) • Intake air temperature 20°C, 68°F

** Mean noise level measured according to ISO 2151/Pneurop/Cagi PN8NTC2 test code; tolerance 2 dB(A).

FAD is measured at 7 bar.

Compressor type	Max. worki	ng pressure		Capacity FAD	Installed power		
50 Hz	bar	psig	l/s	m³/min	cfm	kW	hp
LFx 0.7	10	145	1.02	0.06	2.16	0.55	0.7
LFx 1.0	10	145	1.38	0.08	2.92	0.75	1
LFx 1.5	10	145	2.07	0.18	4.38	1.1	1.5
LFx 2.0	10	145	2.53	0.12	5.36	1.5	2

Compressor type	Max. worki	ng pressure		Capacity FAD	Installed power		
60 Hz	bar	psig	l/s	m³/min	cfm	kW	hp
LFx 0.7	10	145	1.35	0.081	2.86	0.55	0.7
LFx 1.0	10	145	1.46	0.087	3.09	0.75	1
LFx 1.5	10	145	2.39	0.14	5.06	1.1	1.5

Dimensions standard versions:

LFx 0.7-1.0 800 mm, 31.5" 550 mm, 21.7" 525 mm, 20.7"





LF Industrial oil-free aluminum piston compressors, 1.5-7.5 kW / 2-10 hp

Looking for a durable, high-performance compressed air solution for your specific industrial application? Atlas Copco's LF oil-free aluminium piston air compressors stand for exceptional reliability and extremely low operating costs and are virtually maintenance-free. LF compressors are 100% oil-free, so are ideal for your applications where oil cannot be Incorporating state-of-thetolerated. art technology, LF compressors deliver the lowest operating temperatures in the industry while offering superb quality air. High-quality materials ensure reliable performance and extra long life. The LF range is suitable for stand-alone use or easy integration in your OEM product. Also where maintenance-free compressed air is required, LF units are the best solution.

CUSTOMER BENEFITS

• **High reliability** – Thanks to a unique, robust design and the optimal combination of quality materials, LF compressors offer improved performance and extended product life.

• Certified 100% oil-free air – LF compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

• **Easy maintenance** – All components and service points are easily accessible.

• Low running costs— Operational costs are limited over a long product lifetime.

• **Saving floor space** – The compressor block which is directly coupled to the motor is manufactured using lightweight materials and provides excellent cooling characteristics: ideal for integration with limited space requirements.







LF Pack–Version Base frame with acoustic hood, especially in low noise



mobile versions with either electric or gasoline engine



COMPRESSOR	Maximum working pressure*		FAD at normal working pressure and 1,500 rpm (50 Hz)			FAD at normal working pressure and 1,800 rpm (60 Hz)			Installed recommended power		Noise level dB(A)**	
ТҮРЕ	bar(e)	psig	l/s	m³/min	cfm	l/s	m³/min	cfm	kW	hp	Unsilenced	Base-mount- ed, silenced
10 BAR LF												
LF 2-10	10	145	3.1	0.19	6.6	3.6	0.22	7.6	1.5	2	82/84	67/69
LF 3-10	10	145	4	0.24	8.5	4.6	0.28	9.7	2.2	3	83/85	68/70
LF 5-10	10	145	8.2	0.49	17.4	9.1	0.55	19.3	4	5.5	83/85	68/70
LF 7-10	10	145	11	0.66	23.3	12	0.72	25.4	5.5	7.5	84/86	72/74
LF 10-10	10	145	15.5	0.93	32.8	18.2	1.1	38.9	7.5	10	86/88	74/76

* Unit performance measured according to ISO 1217, Ed. 3, Annex C-1996.
 ** Mean noise level measured at a distance of 1 m according to ISO 2151/Pneurop/Cagi PN8NTC2 test code; tolerance 3 dB(A).

Reference conditions:

• Absolute inlet pressure 1 bar (14.5 psi). • Intake air and coolant temperature 20°C, 68°F.

FAD is measured at the following working

pressures:
10 bar versions at 7 bar.
15 bar versions at 12 bar.

• 20 bar versions at 20 bar.

• 30 bar versions at 30 bar.

Receiv	ver size 1	0, 15	& 20	bar (218,	290
or 435	psi) vers	ions.			
90, 25	0 & 475	l (24,	66 &	125 US g	allon)

Standard voltages available:

50 Hz: 1 ph 230 V, 3 ph 230, 400, 500 V 60 Hz: 1 ph 230 V, 3 ph 230, 460, 380, 575 V

SF 1-22 Oil-free scroll compressors, 1.5-22 kW / 2-30 hp

Atlas Copco's SF oil-free scroll compressors provide 100% oil-free for critical applications in industries such as R&D laboratories, hospitals, universities, dental applications, food & beverage . These ISO 8573-1 CLASS 0 certified compressors are easy to operate and maintain, and have a minimal footprint to save space in your facility. SF compressors eliminate the risks of oil contamination while providing an efficient, reliable and highly cost-effective source of pure oilfree air.

CUSTOMER BENEFITS

• Certified 100% oil-free air – SF compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

• Extremely quiet operation – The slow speed of the scroll compression elements ensures that the SF scroll compressors are exceptionally quiet. SF units are WorkPlace Air System[™] compressors, making them suitable for installation in any working environment.

• Energy efficiency – SF scroll compressors are ideal for applications where flexibility and energy efficiency are crucial. Unloaded power consumption is eliminated thanks to the simple start/stop control. The SF 6-22 uses Variable Flow Technology to match the compressed air output to the air demand.

• Low maintenance – SF scroll compressors stand for simplicity and reliability. The scroll design has a minimal number of moving parts, ensuring a long operating life with a minimum number of service interventions.

• Advanced control and monitoring – To maximize efficiency and reliability on multi-module SFs, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

Dew point receiver

mounted.

Special design / options the SF series



SF 4 Twin-Version (T) receiver mounted with two SF units and acoustic enclosure and adsorption dryers



SF 4 Standard receiver mounted with acoustic enclosure



SF Multicore 6/8/11/15/17/22 FF

oil-free scroll compressors





SF Multicore - flexibility through modular design

The Scroll Multicore concept further enhances the performance of the Scroll technology. Two to four compressor modules (PM version) are integrated into one unit and offer all the advantages of a modular system. For dry compressed air, a refrigerant dryer can be integrated as well as 2-4 compressor modules (PM/FF versions).





The specially designed software makes optimal use of the additional advantages which result from the Multicore concept: sequential operation, stage-less volume flow regulation for low power consumption – while the individual modules are controlled by software like a single SF aggregate.

	Max. working pressure		Cap	Capacity FAD*		Installe pov	Installed motor power		Dimensions L x W x H		Weight	
50 Hz / 60 Hz	bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	mm	inch	kg	lbs
SKID VERSIONS												
SE 1	8	116	2.7	0.16	5.7	1.5	2	65	800 x 600	31.5 x 23.6	105	232
511	10	145	2.1	0.13	4.4	1.5	2	65	x 540	x 21.3	105	232
SE 2	8	116	4.0	0.24	8.5	2.2	3	67	(Beceiver	(Beceiver	110	243
51 2	10	145	3.4	0.20	7.2	2.2	3	67	mounted)	mounted)	110	243
SE /	8	116	6.6	0.40	14.0	3.7	5	68	1267 x 600	49.9 x 23.6	120	265
51 4	10	145	5.60	0.30	11.9	3.7	5	68	x 1154	x 45.4	120	265
SKID VERSIONS -	DUPLEX TA	UPLEX TANK MOUNTED										
OF OT	8	116	10.6	0.64	22.5	5.9	8	72			365	805
5101	10	145	9.0	0.54	19.1	5.9	8	72	2043 x 600	80.4 x 23.6	365	805
CF OT	8	116	13.2	0.80	28.0	7.4	10	73	x 1154	x 45.4	375	827
51 01	10	145	11.2	0.67	23.7	7.4	10	73			375	827
FULLY SILENCED -	WORKPLA	CE AIR SY	STEM™									
SF 1	8	116	2.7	0.16	5.7	1.5	2	53			97	214
	10	145	2.1	0.13	4.4	1.5	2	53			97	214
05.0	8	116	4.0	0.24	8.5	2.2	3	55	590 x 600	23.2 x 23.6	97	214
3F Z	10	145	3.4	0.20	7.2	2.2	3	55	x 850	x 33.5	97	214
SE A	8	116	6.6	0.40	14.0	3.7	5	57			102	225
3F 4	10	145	5.6	0.34	11.9	3.7	5	57			102	225
SEC	8	116	10.4	0.62	22.0	5.9	8	63			340	750
350	10	145	8.8	0.53	18.6	5.9	8	63	1450 x 750	57.1 x 29.5	340	750
CE 0	8	116	13.4	0.80	28.4	7.4	10	63	x 1040	x 40.9	345	761
51.0	10	145	11.3	0.68	23.9	7.4	10	63			345	761
SE 11	8	116	20.2	1.21	42.8	11	15	63			480	1058
5111	10	145	17.0	1.00	36.0	11	15	63	1450 x 750	57.1 x 29.5	480	1058
SE 15	8	116	26.4	1.58	55.0	15	20	63	x 1844	x 72.6	560	1235
51 15	10	145	22.8	1.37	48.3	15	20	63			560	1235
SF 17 M	8	116	30.6	1.8	64.7	17	23	64				1258
SF 22 M	8	116	40.6	2.4	85.6	22	30	65	1620 x 750 64 x 20.4		662	1456
SF 11 DM	8	116	9.7	0.6	20.5	5.5	7	63	x 1850	x 72 7	503	1107
SF 15 DM	8	116	13.2	0.8	27.9	7.5	10	63	X 1000	A 12.1	564	1241
SF 22 DM	8	116	19.5	1.2	41.1	11	15	65			683	1503

Technical Specifications:

Unit performance measured according to ISO 1217, Annex C, latest edition.
 Noise level measured at a distance of 1m according to Pneurop/Cagi PN8NTC2 test code.

Reference conditions: • absolute inlet pressure 1 bar (14.5 psig) • intake air temperature 20°C (68°F)

AQ 30-55 / 15-55 VSD

Water-injected screw compressors, 15-55 kW / 20-75 hp

Atlas Copco's AQ water-injected screw compressors, available in water-cooled and air-cooled versions, meet your precise needs for pure, oil-free air while offering high-pressure capability and improved energy efficiency. Developed especially for applications demanding the highest levels of purity, such as pharmaceutical production, food processing and critical electronics, AQ compressors eliminate the risks of oil contamination as well as the resulting extra costs. They ensure consistent 100% oil-free air while you benefit from lower operating and maintenance costs with an ISO 8573-1 CLASS 0 (2010) certified compressor.

CUSTOMER BENEFITS

• **High efficiency** – Thanks to the superior cooling capability of water which ensures that the heat is removed efficiently at the source, more air per kW of power is generated. Energy savings of 35% on average are possible with the Variable Speed Drive versions:

- Load/no load transition losses are eliminated.

- Precise pressure control allows a tighter pressure band and a lower average working pressure, resulting in reduced energy consumption.

• Certified 100% oil-free air- AQ compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor.

• **Quiet operation**– AQ compressors are supplied in a sound-insulated canopy, thus avoiding the need for a separate compressor room and allowing installation in most working environments.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.





AQ 55 VSD FF





At the heart of the AQ series

is a unique screw element with water-injection for a highly efficient, almost isothermal compression. The polymer ceramic rotors with an optimized rotor profile are guided by waterlubricated bearings; this ensures that the compressor element is not contaminated with oil, in order to produce oil-free air. Rotors

A highly efficient compression process is achieved thanks to the polymer ceramic rotors with an optimized profile. The combination of corrosion-free, highly-efficient raw materials and the smooth water lubrication results in a much longer service life.

Element housing

The strength and long service life are achieved by using an element casing

AQ 37-55 VSD H: 1840 mm, 72"

W: 965 mm, 40" L: 2435 mm, 96" made of aluminum bronze, which eliminates the risk of corrosion inside the housing.

Element bearings

Using hydrodynamic bearings ensures a long service life, because there are no friction points in the bearing; it just glides on a water film and does not need any oil or lubrication.

COMPRESSOR Type	Max. work (bar(e	ing pressure e)/psig)	e Capacity FAD (*)			Installed mo	otor power	Noise level ^(**)	Weight (kg/lbs)	
	Pack	Full Feature	l/s	m³/min	cfm	kW	hp	dB(A)	Pack	Full Feature
AIR-COOLED										
AQ 30 7.5	7.5 / 109	7.25 / 105	84.9	5.1	180.1	30	40	68	1226 / 2703	1320 / 2910
10	10 / 145	9.75 / 141	68.3	4.1	144.8	30	40	68	1226 / 2703	1320 / 2910
13	13 / 189	12.75 / 185	53	3.2	113	30	40	68	1226 / 2703	1320 / 2910
AQ 37 7.5	7.5 / 109	7.25 / 105	102	6.1	215.4	37	50	69	1298 / 2862	1395 / 3075
10	10 / 145	9.75 / 141	86.4	5.2	183.6	37	50	69	1298 / 2862	1395 / 3075
13	13 / 189	12.75 / 185	69.2	4.2	148.3	37	50	69	1298 / 2862	1395 / 3075
AQ 45 7.5	7.5 / 109	7.25 / 105	121.4	7.3	257.8	45	60	71	1321 / 2912	1416 / 3122
10	10 / 145	9.75 / 141	98.1	5.9	208.4	45	60	71	1321 / 2912	1416 / 3122
13	13 / 189	12.75 / 185	82.2	4.9	173	45	60	71	1321 / 2912	1416 / 3122
AQ 55 7.5	7.5 / 109	7.25 / 105	139.1	8.4	296.6	55	75	72	1378 / 3038	1497 / 3300
10	10 / 145	9.75 / 141	118.1	7.1	250.7	55	75	72	1378 / 3038	1497 / 3300
13	13 / 189	12.75 / 185	98.4	5.9	208.4	55	75	72	1378 / 3038	1497 / 3300
WATER-COOLED										
AQ 30 7.5	7.5 / 109	7.25 / 105	88.5	5.3	187.5	30	40	65	1121 / 2471	1215 / 2679
10	10 / 145	9.75 / 141	71.2	4.3	151.8	30	40	65	1121 / 2471	1215 / 2679
13	13 / 189	12.75 / 185	55	3.3	116.5	30	40	65	1121 / 2471	1215 / 2679
AQ 37 7.5	7.5 / 109	7.25 / 105	107.1	6.4	226.9	37	50	66	1193 / 2630	1290 / 2844
10	10 / 145	9.75 / 141	91.2	5.5	194.2	37	50	66	1193 / 2630	1290 / 2844
13	13 / 189	12.75 / 185	72.9	4.4	155.4	37	50	66	1193 / 2630	1290 / 2844
AQ 45 7.5	7.5 / 109	7.25 / 105	128.5	7.7	272.3	45	60	67	1216 / 2681	1313 / 2895
10	10 / 145	9.75 / 141	108	6.5	230	45	60	67	1216 / 2681	1313 / 2895
13	13 / 189	12.75 / 185	89.9	5.4	190.7	45	60	67	1216 / 2681	1313 / 2895
AQ 55 7.5	7.5 / 109	7.25 / 105	152.7	9.2	323.6	55	75	68	1273 / 2806	1392 / 3069
10	10 / 145	9.75 / 141	131.2	7.9	279	55	75	68	1273 / 2806	1392 / 3069
13	13 / 189	12.75 / 185	109	6.5	230	55	75	68	1273 / 2806	1392 / 3069

Technical specifications 50 Hz versions

(*)Unit performance measured according to ISO1217 Annex C, latest edition.

Reference conditions:

Absolute inlet pressure 1 bar (14.5 psi)

• Intake air temperature 20°C (68°F)

(**)Noise level measured at a distance of 1m according to Pneurop/Cagi PN8NTC2 test code: 3dB()

FAD is measured at the following working pressure:7 bar versions at 7.5 bar(e)



61

COMPRESS Type	SOR	Max. worki (bar(e	ing pressure }/psig)		Capacity FAD (1)	Installed motor po		Noise level	ise level Weight (kg/lbs)	
		Pack	Full Feature	l/s	m³/min	cfm	kW	hp	dB(A)	Pack	Full Feature
AIR-COOLED			,								
AQ 30	7.4	7.4 / 107	7.15 / 104	87.8	5.3	187.2	30	40	68	1226 / 2703	1320 / 2910
	9.1	9.1 / 132	8.85 / 128	78.7	4.7	166.1	30	40	68	1226 / 2703	1320 / 2910
	10.8	10.8 / 157	10.55 / 153	67.5	4.1	144.8	30	40	68	1226 / 2703	1320 / 2910
	12.5	12.5 / 181	12.25 / 178	59.2	3.6	127.1	30	40	68	1226 / 2703	1320 / 2910
AQ 37	7.4	7.4 / 107	7.15 / 104	105.5	6.3	222.5	37	50	69	1298 / 2862	1395 / 3075
	9.1	9.1 / 132	8.85 / 128	87.7	5.3	187.2	37	50	69	1298 / 2862	1395 / 3075
	10.8	10.8 / 157	10.55 / 153	83	5	176.6	37	50	69	1298 / 2862	1395 / 3075
	12.5	12.5 / 181	12.25 / 178	76.1	4.6	162.4	37	50	69	1298 / 2862	1395 / 3075
AQ 45	7.4	7.4 / 107	7.15 / 104	122.4	7.3	257.8	45	60	71	1321 / 2912	1416 / 3122
	9.1	9.1 / 132	8.85 / 128	103	6.2	219.1	45	60	71	1321 / 2912	1416 / 3122
	10.8	10.8 / 157	10.55 / 153	96	5.8	204.8	45	60	71	1321 / 2912	1416 / 3122
	12.5	12.5 / 181	12.25 / 178	88.7	5.3	187.2	45	60	71	1321 / 2912	1416 / 3122
AQ 55	7.4	7.4 / 107	7.15 / 104	146.8	8.8	310.8	55	75	72	1378 / 3038	1497 / 3300
	9.1	9.1 / 132	8.85 / 128	118.2	7.1	250.7	55	75	72	1378 / 3038	1497 / 3300
	10.8	10.8 / 157	10.55 / 153	119.6	7.2	254.3	55	75	72	1378 / 3038	1497 / 3300
	12.5	12.5	12.25	106	6.4	226	55	75	72	1378 / 3038	1497 / 3300
WATER-COOLI	ED										
AQ 30	7.4	7.4 / 107	7.15 / 104	91.8	5.5	194.2	30	40	65	1121 / 2471	1215 / 2679
	9.1	9.1 / 132	8.85 / 128	82.7	5	176.6	30	40	65	1121 / 2471	1215 / 2679
	10.8	10.8 / 157	10.55 / 153	70.4	4.2	148.3	30	40	65	1121 / 2471	1215 / 2679
	12.5	12.5 / 181	12.25 / 178	61.7	3.7	130.7	30	40	65	1121 / 2471	1215 / 2679
AQ 37	7.4	7.4 / 107	7.15 / 104	111.3	6.7	236.6	37	50	66	1193 / 2630	1290 / 2844
	9.1	9.1 / 132	8.85 / 128	93	5.6	197.8	37	50	66	1193 / 2630	1290 / 2844
	10.8	10.8 / 157	10.55 / 153	87.5	5.3	187.2	37	50	66	1193 / 2630	1290 / 2844
	12.5	12.5 / 181	12.25 / 178	80.7	4.8	169.5	37	50	66	1193 / 2630	1290 / 2844
AQ 45	7.4	7.4 / 107	7.15/104	134	8	282.5	45	60	67	1216 / 2681	1313 / 2895
	9.1	9.1 / 132	8.85 / 128	115.2	6.9	243.7	45	60	67	1216 / 2681	1313 / 2895
	10.8	10.8 / 157	10.55 / 153	104.2	6.3	222.5	45	60	67	1216 / 2681	1313 / 2895
	12.5	12.5 / 181	12.25 / 178	97.8	5.9	208.4	45	60	67	1216 / 2681	1313 / 2895
AQ 55	7.4	7.4 / 107	7.15 / 104	161.7	9.7	342.6	55	75	68	1273 / 2806	1392 / 3069
	9.1	9.1 / 132	8.85 / 128	132.7	8	282.5	55	75	68	1273 / 2806	1392 / 3069
	10.8	10.8 / 157	10.55 / 153	131.5	7.9	279.1	55	75	68	1273 / 2806	1392 / 3069
	12.5	12.5	12.25	118.7	7.1	250.7	55	75	68	1273 / 2806	1392 / 3069

Technical specifications 50 Hz versions

Technical specifications AQ 37-55 VSD

COMPRESSOR Type	Max. working pressure (1)		C	apacity FAD	(2)	Installed m	otor power	Noise level ⁽³⁾	Weight	(kg/lbs)
	bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	Pack	Full Feature
AIR-COOLED										
AQ 37 VSD 13(1)	13	175	42.0 - 104.0	2.5-6.2	89.0 - 220.4	37	50	69	1195 / 2635	1306 / 2879
AQ 55 VSD 13(1)	13	175	42.3 - 154.9	2.5 - 9.3	89.6 - 328.2	55	75	72	1195 / 2635	1314 / 2897
WATER-COOLED										
AQ 37 VSD 13(1)	13	175	42.0 - 108.0	2.5 - 6.2	89.0 - 228.8	37	50	66	1090 / 2403	1201 / 2648
AQ 55 VSD 13(1)	13	175	41.9 - 160.9	2.5 - 9.3	88.8 - 340.9	55	75	69	1090 / 2403	1209 / 2665

(1) Full-Feature units max. working pressure 12.5 bar(e)/181 psig.

(2) Stated performance according ISO1217 ed 04 Annex E, measured at 7 bar.

(3) Mean sound level according to ISO2151, tolerance 3 dB(A).

ZT 15-22, ZR/ZT 30-45, ZR/ZT 22-37-55 VSD

Oil-free rotary tooth compressors, 15-55 kW / 20-75 hp

Atlas Copco's ZR/ZT oil-free rotary tooth compressors meet your needs for pure oil-free air while offering wide pressure ranges and improved energy efficiency. Developed especially for applications demanding the highest levels of purity, such as pharmaceutical production, food processing and critical electronics, ZR/ ZT compressors eliminate the risks of oil contamination as well as the resulting extra costs. These ISO 8573-1 CLASS 0 certified compressors are easy to operate and are available with Variable Speed Drive for further energy savings.

CUSTOMER BENEFITS

• Certified 100% oil-free air – ZR/ZT compressors provide 100% pure, clean air, complying with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006, Atlas Copco was the first manufacturer in the world to receive such certification for an oil-free compressor. • VSD for direct energy savings – Energy savings of 35% on average are possible with the Variable Speed Drive versions:

- Unload losses are reduced to a minimum.
- No blow-off of compressed air to the atmosphere.
- Load/no load transition losses are eliminated.

- Precise pressure control allows a tighter pressure band and a lower average working pressure, resulting in reduced energy consumption.

• Quiet operation – The vertical layout of the coolers reduces the noise levels from the fan, motor and element. Moreover, ZR/ZT compressors are supplied in a sound-insulated canopy, thus avoiding the need for a separate compressor room and allowing installation in most working environments.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Easy maintenance** – The robust air inlet filter offers a long lifetime and high reliability for long service intervals and low maintenance needs.



Technical Specifications:

COMPRESSOR	Max. w pres	vorking sure	(Capacity FAD	*	Insta motor	alled power	Noise level**	Weight drye	without er***	Integrated
ТҮРЕ	bar(e)	psig	l/s	m³/min	cfm	kW	hp	dB(A)	kg	lbs	available
AIR-COOLED ONL	Y										
ZT 15	7.5	109	37.6	2.3	80						
	8.6	125	34.9	2.1	74	15	20	65	1060	2337	ID
	10	145	29.9	1.8	63						
ZT 18	7.5	109	48.0	2.9	102						
	8.6	125	45.7	2.7	97	18	25	67	1080	2381	ID/IMD
	10	145	37.2	2.2	79						
ZT 22	7.5	109	59.0	3.5	125						
	8.6	125	53.2	3.2	113	22	30	69	1086	2394	ID/IMD
	10	145	45.0	2.7	95						
AIR- (ZT) AND W	ATER-COO	LED (ZR)									
ZR/ZT 30	7.5	109	78.7	4.7	167	30	40	63	1/122	2157	
	8.6	125	73.7	4.4	156		40	05	1432	5157	
ZR/ZT 37	7.5	109	96.5	5.8	204	37	50	65	1/132	3157	
	8.6	125	92.1	5.5	195	57	50	05	1432	5157	
ZR/ZT 45	7.5	109	114.4	6.9	243	45	60	67	1432	3157	
	8.6	125	108.9	6.5	231	-10	00	07	1402	0107	10/11/10
ZT 22 VSD	7.5	109	20.6-55.3	1.3-3.4	43.8-117.6						
	8.6	125	20.1-51.0	1.2-3.1	42.7-108.5	22	30	69	1120	2469	ID
	10	145	19.7-47.0	1.2-2.8	41.9-100						
ZR/ZT 37 VSD	7.5	109	41.3-101.2	2.5-6.2	87.8-215.2	37	50	68	1432	3157	ID/IMD
	8.6	125	41.2-97.3	2.5-5.9	87.6-206.9				02	0.07	.5,
ZR/ZT 55 VSD	7.5	109	41.3-142.5	2.5-8.7	87.6-303.1	55	75	68	1432	3157	ID/IMD
	8.6	125	41.2-138.8	2.5-8.4	87.6-295.2					0.07	

* Unit performance measured according to ISO 1217, Ed 3, Annex C-1996

Unit performance measured according to ISU 1217, Ed 3, Annex C-1996 Reference conditions:

 absolute inlet pressure 1 bar (14.5 psi)
 intake air temperature 20°C (68°F)

 Noise level measured according to Pneurop/Cagi PN8NTC2, tolerance: 3 dB(A).
 *** Integrated dryers will increase the weight.
 *** For ZT air-cooled units: +3 dB(A).

FAD is measured at the following working pressure:
7.5 bar versions at 7 bar.
8.6 bar versions at 8 bar.
10 bar versions at 9.75 bar.



	۵)imensions (mm/incl	1)
	Length	Width	Height
ZT 15-22	1760 / 69.3"	1026 / 40.4"	1621 / 63.8"
ZR/ZT 30-45	2005 / 78.9"	1026 / 40.4"	1880 / 74.0"
ZT 22 VSD	2195 / 86.4"	1026 / 40.4"	1621 / 63.8"
ZR/ZT 37-55 VSD	2440 / 96.1"	1026 / 40.4"	1880 / 74.0"

Z 55-900 (VSD)

Oil-free air- and water-cooled rotary screw compressors, 55-935 kW / 75-1253 hp

Atlas Copco's Z 55-900 VSD Pack and Full Feature ranges power your production with ultimate reliability and efficiency under the harshest conditions. The first air compressors in the world to be certified Class 0 according to ISO 8573-1 edition 2, 2010, they ensure completely oil-free air to protect your process and end products. Several energy saving features – Variable Speed Drive, energy-free MD dryers and energy recovery – are offered. Z 55-900 VSD compressors are all-inclusive, plugand-play packages that ensure easy and low cost installation and a quick start-up.

CUSTOMER BENEFITS

• Highest reliability – For over 50 years, Z compressors stand for durability and reliability. They incorporate Atlas Copco's proven screw technology, stainless steel coolers, AGMA A4/DIN 5 gears and state-of-the art electrical drive systems, all of which contribute to overall high reliability. Z compressors are built using long-standing internal engineering practices, and are manufactured and tested according ISO 9001.

• Certified 100% oil-free – Z 55-900 compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• Maximum energy savings – Atlas Copco's unique and time proven rotor coating ensures high efficiency over the compressors lifetime. The state-of-the art air compressor element is powered by a high-efficiency electric motor, contributing to maximum compressor package efficiency. Further optimize your energy savings with our innovative and unique Variable Speed Drive, our energy recovery feature and energy-free MD dryers.

• Easy installation – The integrated design of the Z compressor includes internal piping, coolers, motor, lubrication and control system: all supplied as a ready-to-use package. Installation is fault-free, commissioning time is low and no external instrument air is required.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.



Technical Data

True performance:

Atlas Copco Z-compressors are measured according to ISO 1217, Edition 3, Annex C stipulating the FAD (Free Air Delivery) measurement at the outlet of the package, net of all losses.

Atlas Copco specifications correspond to the capacity and pressure that are effectively available to the user, not to the air volume that is sucked in. Differences can be substantial.



Dimensions & weight

	A	В	C	Weight		Α	В	C	Weight		Α	В	C	Weight
ZR 55	2180	1450	2184	1640	ZR 55 FF	2180	1450	2184	1890	ZR 55 *	2180	1450	2184	1640
ZR 75	2180	1450	2184	1715	ZR 75 FF	2180	1450	2184	1965	ZR 75 *	2180	1450	2184	1715
ZR 90	2180	1450	2184	1780	ZR 90 FF	2180	1450	2184	2030	ZR 90 *	2180	1450	2184	1780
ZR 75 VSD	2630	1450	2184	2030	ZR 75 VSD-FF	2630	1450	2184	2280	ZR 75 VSD *	2630	1450	2184	2030
ZR 90 VSD	2630	1450	2184	2030	ZR 90 VSD-FF	2630	1450	2184	2280	ZR 90 VSD *	2630	1450	2184	2030
ZT 55	2180	1450	2184	1760	ZT 55 FF	2880	1450	2184	2360	ZR 55 FF *	2880	1450	2184	1990
ZT 75	2180	1450	2184	1835	ZT 75 FF	2880	1450	2184	2475	ZR 75 FF *	2880	1450	2184	2065
ZT 90	2180	1450	2184	1900	ZT 90 FF	2880	1450	2184	2500	ZR 90 FF *	2880	1450	2184	2130
ZT 75 VSD	2630	1450	2184	2100	ZT 75 VSD-FF	3330	1450	2184	2700	ZR 75 VSD-FF *	3330	1450	2184	2370
ZT 90 VSD	2630	1450	2184	2100	ZT 90 VSD-FF	3330	1450	2184	2700	ZR 90 VSD-FF *	3330	1450	2184	2370

(1) Reference conditions:

- dry air
 absolute inlet pressure 1 bar(a)
 - cooling and air intake temperature 20 °C

nominal working pressure

performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

- (3) Max. capacity is at reference pressure and not at max. pressure
- (4) Pressure dewpoint is specified for
 - 20 °C cooling air/water temperature
 relative humidity of 60 %

 - nominal working pressure
 - load level of minimum 50 % For VSD: at reference speed
- (5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2
- Maximum intake / cooling air temperature is 50 °C (6) for HAT versions
 - Conversions
 - 1 kg = 2.2 lbs
 - 1 mm = 0.039 inch $^{\circ}F = ^{\circ}C \times 9/5 + 32$

Atlast -С Cil-free a А

* Equipped with Energy Recovery system

ZR/ZR FF Watercooled oil-free	Fre	ee air delivery (0	Installe	ed motor	Cooling consum	y water option ⁽²⁾	Pressure dewpoint ⁽⁴⁾	Sound pressure level ⁽⁵⁾
compressors						ZR	ZR-FF	ZR-FF	
Туре	l/s	m³/min	cfm	kW	hp	l/s	l/s	°C	dB(A)
50 Hz units									
ZR 55 - 7.5	143	8.6	303	55	75	0.9	1.3	-24	65
ZR 55 - 8.6	131	7.9	278	55	75	0.9	1.3	-24	65
ZR 55 - 10	121	7.3	257	55	75	0.9	1.3	-25	65
60 Hz units									
ZR 55 - 7.25	155	9.3	329	55	75	1	1.4	-24	65
ZR 55 - 9	138	8.3	293	55	75	1	1.4	-25	65
ZR 55 - 10.4	128	7.7	271	55	75	1	1.4	-25	65
50 Hz units									
ZR 75 - 7.5	194	11.6	411	75	100	1.2	1.8	-26	65
ZR 75 - 8.6	184	11.0	390	75	100	1.2	1.8	-26	65
ZR 75 - 10	174	10.4	369	75	100	1.2	1.8	-27	65
60 Hz units									
ZR 75 - 7.25	213	12.8	452	75	100	1.3	1.9	-26	65
ZR 75 - 9	194	11.6	411	75	100	1.3	1.9	-27	65
ZR 75 - 10.4	185	11.1	392	75	100	1.3	1.9	-27	65
50 Hz units									
ZR 90 - 7.5	234	14.0	496	90	120	1.4	2.1	-27	65
ZR 90 - 8.6	220	13.2	466	90	120	1.4	2.1	-28	65
ZR 90 - 10	209	12.5	443	90	120	1.4	2.1	-28	65
60 Hz units									
ZR 90 - 7.25	262	15.7	555	90	120	1.6	2.3	-26	65
ZR 90 - 9	235	14.1	498	90	120	1.6	2.3	-28	65
ZR 90 - 10.4	224	13.4	475	90	120	1.6	2.3	-29	65

ZR 55-90 FF compressor range

ZR 75-90 VSD-FF compressors

ZR VSD / ZR VSD-FF Watercooled oil-free compressors		Free air delivery (1)		Cooling consum	water ption ⁽²⁾	Pressure dewpoint ⁽⁴⁾	Sound pressure level ⁽⁵⁾
				ZR	ZR-FF	ZR-FF	
Types – 50/60 Hz	l/s	m³/min	cfm	l/s	l/s	°C	dB(A)
ZR 75 VSD-9 bar (e)				1.25	1.92	-30	65
Max (3)	220	13.2	466				
Min	75	4.5	159				
ZR 75 VSD-10.4 bar (e)				1.25	1.92	-30	65
Max (3)	198	11.9	420				
Min	98	5.9	208				
ZR 90 VSD-9 bar (e)				1.25	1.92	-30	65
Max (3)	258	15.5	547				
Min	75	4.5	159				
ZR 90 VSD-10.4 bar (e)				1.25	1.92	-30	65
Max (3)	232	13.9	492				
Min	98	5.9	208				

(1) Reference conditions:

- dry air

absolute inlet pressure 1 bar(a)
absolute inlet pressure 1 bar(a)
cooling and air intake temperature 20 °C
nominal working pressure
performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for - 20 °C cooling air/water temperature

- relative humidity of 60 %

- nominal working pressure

- load level of minimum 50 % For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions Conversions

- 1 kg = 2.2 lbs

- 1 mm = 0.039 inch - °F = °C x 9/5 + 32

ZR 55-90 FF compressors

ZT/ZT FF Aircooled oil-free	Fre	e air delivery ⁽¹⁾		Installer	d motor	Insta fan n	alled notor	Pressure dewpoint ⁽⁴⁾	Sound pressure level ⁽⁵⁾
compressors						ZT	ZT-FF	ZT-FF	
Туре	l/s	m³/min	cfm	kW	hp	kW	kW	°C	dB(A)
50 Hz	1	1		1	1	1	1	1	
ZT 55 - 7.5	142	8.5	301	55	75	2	3.1	-28	72
ZT 55 - 8.6	130	7.8	276	55	75	2	3.1	-28	72
ZT 55 - 8.6 HAT (6)	120	7.2	254	55	75	2	-	-	72
ZT 55 - 10	120	7.2	254	55	75	2	3.1	-28	72
60 Hz									
ZT 55 - 7.25	154	9.2	326	55	75	2	3.6	-28	72
ZT 55 - 8.6 HAT (6)	127	7.6	269	55	75	2	-	-	72
ZT 55 - 9	137	8.2	290	55	75	2	3.6	-28	72
ZT 55 - 10.4	127	7.6	269	55	75	2	3.6	-29	72
50 Hz									
ZT 75 - 7.5	193	11.6	409	75	100	3.6	4.7	-30	72
ZT 75 - 8.6	184	11.0	390	75	100	3.6	4.7	-30	72
ZT 75 - 8.6 HAT (6)	174	10.4	369	75	100	3.6	-	-	72
ZT 75 - 10	174	10.4	369	75	100	3.6	4.7	-31	72
60 Hz units									
ZT 75 - 7.25	212	12.7	449	75	100	3.8	5.6	-30	72
ZT 75 - 8.6 HAT (6)	184	11.1	390	75	100	3.8	-	-	72
ZT 75 - 9	194	11.6	411	75	100	3.8	5.6	-31	72
ZT 75 - 10.4	184	11.0	390	75	100	3.8	5.6	-31	72
50 Hz units									
ZT 90 - 7.5	233	14.0	494	90	120	3.6	4.7	-31	72
ZT 90 - 8.6	220	13.2	466	90	120	3.6	4.7	-32	72
ZT 90 - 8.6 HAT (6)	208	12.5	441	90	120	3.6	-	-	72
ZT 90 - 10	208	12.5	441	90	120	3.6	4.7	-32	72
60 Hz units									
ZT 90 - 7.25	261	15.7	553	90	120	3.8	5.6	-32	72
ZT 90 - 8.6 HAT (6)	222	13.3	470	90	120	3.8	-	-	72
ZT 90 - 9	236	14.2	500	90	120	3.8	5.6	-32	72
ZT 90 - 10.4	222	13.3	471	90	120	3.8	5.6	-33	72

ZT 75-90 VSD-FF compressors

ZT VSD / ZT VSD-FF Aircooled		Free air delivery $^{(1)}$		Pressure dewpoint ⁽⁴⁾	Sound pressure level ⁽⁵⁾
on-nee compressors				ZT-FF	
Types – 50/60 Hz	l/s	m³/min	cfm	°C	dB(A)
ZT 75 VSD-9 bar (e)				-30	72
Max (3)	220	13.2	466		
Min	75	4.5	159		
ZT 75 VSD-10.4 bar (e)				-30	72
Max (3)	198	11.9	420		
Min	98	5.9	208		
ZT 90 VSD-9 bar (e)				-30	72
Max (3)	258	15.5	547		
Min	75	4.5	159		
ZT 90 VSD-10.4 bar (e)				-30	72
Max (3)	232	13.9	492		
Min	98	5.9	208		

(1) Reference conditions:

- dry air

absolute inlet pressure 1 bar(a)
cooling and air intake temperature 20 °C

- nominal working pressure

performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for

- 20 °C cooling air/water temperature
- relative humidity of 60 %
- nominal working pressure
 load level of minimum 50 %
- For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions

- Conversions 1 kg = 2.2 lbs 1 mm = 0.039 inch °F = °C x 9/5 + 32

(2) Cooling water temperature rise of 15 °C

	ZR watercooled	Free	air delive	ry ⁽¹⁾	Installed motor	Cooling water consump- tion ⁽²⁾	Pressure dewpoint ⑶	Sound p leve	el ⁽⁴⁾	Weight		Dimensio	ns
	Туре	l/s	m³/min	cfm	kW	l/s	°C	w/o duct dB(A)	with duct dB(A)	kg	A mm	B mm	C mm
	50 Hz - 7.5 bar(e)												
	ZR 110	318	19.1	674	110	3.5	-28	70	68	3265	3440	2000	1650
sr)	ZR 132	367	22.0	778	132	4.1	-29	70	68	3390	3440	2000	1650
Drye	ZR 145	394	23.6	835	145	4.2	-30	70	68	3530	3440	2000	1650
IMI	ZR 160	471	28.3	998	160	4.4	-25	67	66	4705	4340	2000	1650
(wit	ZR 200	607	36.4	1286	200	5.1	-25	67	66	5365	4340	2000	1650
Ë	ZR 250	726	43.6	1538	250	5.8	-28	67	66	5360	4340	2000	1650
	ZR 275	780	46.8	1653	275	6.2	-30	67	66	5560	4340	2000	1650
	ZR 110	318	19.1	674	110	1.7	-	67	65	2635	2540	2000	1650
	ZR 132	367	22.0	778	132	1.9	-	67	65	2760	2540	2000	1650
	ZR 145	394	23.6	835	145	2.0	-	67	66	2900	2540	2000	1650
	ZR 160	471	28.3	998	160	2.3	-	67	66	3795	3140	2000	1650
	ZR 200	607	36.4	1286	200	3.0	-	67	66	3995	3140	2000	1650
_	ZR 250	726	43.6	1538	250	3.7	-	67	66	3990	3140	2000	1650
Dryer	ZR 275	780	46.8	1653	275	4.1	-	67	66	4190	3140	2000	1650
Q	ZR 300	775	46.5	1642	315	4.0	-	70	69	6650	3700	2400	2120
0/M)	ZR 315	855	51.3	1812	315	4.4	-	71	69	6650	3700	2400	2120
ack	ZR 355	949	56.9	2011	355	4.8	-	71	69	6950	3700	2400	2120
	ZR 400	1049	62.9	2223	400	5.4	-	71	70	7050	3700	2400	2120
	ZR 425	1162	69.7	2462	450	6.2	-	72	70	7250	3700	2400	2120
	ZR 450	1257	75.4	2663	450	7.2	-	73	71	9500	4060	2400	2120
	ZR 500	1387	83.2	2939	500	7.8	-	73	71	9500	4060	2400	2120
	ZR 630	1726	103.6	3657	630	9.4	-	75	73	10225	4060	2400	2120
	ZR 750	2075	124.5	4397	750	11.3	-	75	73	10325	4060	2400	2120

ZR 110-750 and ZR 132-900 VSD compressors - 50 Hz

(1) Reference conditions:

dry air absolute inlet pressure 1 bar(a) cooling and air intake temperature 20 °C

nominal working pressure

 performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for

- 20 °C cooling air/water temperature

- relative humidity of 60 %
 nominal working pressure
 load level of minimum 50 %

- For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions

- Conversions 1 kg = 2.2 lbs 1 mm = 0.039 inch
- $\ ^\circ F = \ ^\circ C \ x \ 9/5 + 32$

	ZR watercooled	Free	e air deliver	'Y ⁽¹⁾	Installed motor	Cooling water consump- tion ⁽²⁾	Pressure dewpoint ⁽³⁾	Sound p lev	oressure el ⁽⁴⁾	Weight	I	Dimension	s
	Туре	l/s	m³/min	cfm	kW	l/s	°C	w/o duct dB(A)	with duct dB(A)	kg	A mm	B mm	C mm
	50 Hz - 8.6 bar(e)												
	ZR 110	285	17.1	604	110	3.1	-28	70	68	3265	3440	2000	1650
÷	ZR 132	326	19.6	691	132	3.5	-29	70	68	3390	3440	2000	1650
yer	ZR 132 VSD	372	22.3	778	132	3.9	-28/-32	68-72	66-69	3500	3440	2000	1650
D	ZR 145	362	21.7	767	145	3.9	-30	70	68	3530	3440	2000	1650
Q	ZR 160 VSD	435	20.1	922	160	4.2	-25	69.74	66 71	4705	4340	2000	1650
-	ZR 100 V3D	553	20.9	1172	200	4.2	-20/-32	67	66	5365	4340	2000	1650
vit	ZR 250	691	41.5	1464	250	5.6	-23	67	66	5360	4340	2000	1650
- - -	ZR 250 VSD	721	43.3	1528	250	5.8	-25/-30	63-73	62-71	6080	4340	2000	1650
	ZR 275	723	43.4	1532	275	5.8	-30	67	66	5560	4340	2000	1650
	ZR 315 VSD	836	50.2	1771	299	6.8	-25/-30	63-73	62-71	6080	4340	2000	1650
	ZR 110	285	17.1	604	110	1.5	-	67	65	2635	2540	2000	1650
	ZR 132	326	19.6	691	132	1.7	-	67	65	2760	2540	2000	1650
	ZR 132 VSD	376	22.6	797	132	1.9	-	62-68	61-66	2870	2540	2000	1650
	ZR 145	362	21.7	767	145	1.9	-	67	66	2900	2540	2000	1650
	ZR 160	435	26.1	922	160	2.2	-	67	66	3795	3140	2000	1650
	ZR 100 VSD ZR 200	430	20.1	922	200	2.2	-	67	99-10	2870	2540	2000	1650
	ZH 200	691	41 5	1464	200	2.0	-	67	66	3990	3140	2000	1650
er)	ZR 250 VSD	721	43.3	1528	250	3.7	-	63-73	62-71	4710	3140	2000	1650
ž	ZR 275	723	43.4	1532	275	3.8	-	67	66	4190	3140	2000	1650
9	ZR 300	723	43.4	1532	315	4.1	-	71	70	6650	3700	2400	2120
≥	ZR 315	798	47.9	1691	315	4.5	-	72	70	6650	3700	2400	2120
%	ZR 315 VSD	836	50.2	1771	299	4.3	-	63-73	62-71	4710	3140	2000	1650
્ર્	ZR 355	886	53.2	1877	355	4.9	-	72	72	6950	3700	2400	2120
ack	ZR 400	978	58.7	2072	400	5.4	-	72	71	7050	3700	2400	2120
ے ت	ZR 400 VSD	1114	66.9	2361	425	6.4	-	68-75	66-73	8350	4060	2470	2120
	ZR 420	1166	70.0	2291	450	0.2	-	73	71	7250	3700	2400	2120
	ZR 400 ZR 500	1201	70.0	2471	430 500	7.1	-	74	72	9500	4000	2400	2120
	ZR 500 VSD	1231	79.1	2733	525	7.6		68-76	66-74	8350	4000	2400	2120
	ZR 630	1602	96.1	3394	630	9.3	-	76	74	10225	4060	2400	2120
	ZR 700 VSD	2063	123.8	4371	700	11.6	-	70-78	68-76	11850	4675	2470	2120
	ZR 750	1850	111.0	3920	750	10.7	-	76	74	10325	4060	2400	2120
	ZR 900 VSD	2456	147.4	5204	935	13.2	-	68-78	68-76	11850	4675	2470	2120
	50 Hz - 10 bar(e)												
	ZR 110	265	15.9	562	110	3.3	-28	70	68	3265	3440	2000	1650
~	ZR 132	313	18.8	663	132	3.8	-29	70	68	3390	3440	2000	1650
yer	ZR 132 VSD	330	19.8	699	132	4.1	0,875	68-72	66-69	3500	3440	2000	1650
ā	ZR 145	334	20.0	708	145	4.1	-30	70	68	3530	3440	2000	1650
Q	ZR 160 VSD	202	24.1	85Z 921	160	4.3	-25	69.74	66 71	4705	4340	2000	1650
4	ZR 200	504	30.2	1068	200	4.4	-25	67	66	4905	4340	2000	1650
wit	ZR 250	629	37.7	1333	250	5.6	-28	67	66	5360	4340	2000	1650
Ë	ZR 250 VSD	648	38.9	1373	250	5.8	-25/-30	67-73	65-71	6080	4340	2000	1650
	ZR 275	689	41.3	1460	275	6.0	-30	67	66	5560	4340	2000	1650
	ZR 315 VSD	746	44.8	1581	299	6.7	-25/-30	67-73	65-71	6080	4340	2000	1650
	ZR 110	265	15.9	562	110	1.6	-	67	65	2380	2540	2000	1650
	ZR 132	313	18.8	663	132	1.8	-	67	65	2440	2540	2000	1650
	ZR 132 VSD	333	20.0	706	132	1.9	-	62-68	61-66	2590	2540	2000	1650
	ZK 145	334	20.0	708	145	1.9	-	67	66	2580	2540	2000	1650
	ZR 100 ZR 160 VSD	40Z 30/I	24.1	835	160	2.3	-	62-70	61-66	2590	25/10	2000	1650
	ZR 200	504	30.2	1068	200	2.9	-	67	66	3995	3140	2000	1650
÷	ZR 250	629	37.7	1333	250	3.6	-	67	66	3990	3140	2000	1650
yeı	ZR 250 VSD	648	38.9	1373	250	3.7	-	64-70	65-68	4710	3140	2000	1650
Ā	ZR 275	689	41.3	1460	275	4.0	-	67	66	4190	3140	2000	1650
Ē	ZR 300	689	41.3	1460	315	4.2	-	71	70	6650	3700	2400	2120
	ZR 315	765	45.9	1621	315	4.5	-	72	70	6650	3700	2400	2120
ŝ	2R 315 VSD	746	44.8	1581	299	4.3	-	63-73	62-71	4710	3140	2000	1650
농	ZR 355	846	50.8	1/93	355	4.9	-	/3	/1	6950	3/00	2400	2120
Ра	2n 400 7R 400 V/SD	939	58.7	2074	400	5.7		73 69-76	66-72	7000	3700	2400	2120
	ZR 450	1047	62.8	2074	450	7.1		74	72	9500	4060	2470	2120
	ZR 500	1199	71.9	2541	500	7.9	-	74	72	9500	4060	2400	2120
	ZR 500 VSD	1150	69.0	2437	525	7.6	-	69-77	66-74	8350	4060	2470	2120
	ZR 630	1474	88.4	3123	630	9.3	-	76	74	10225	4060	2400	2120
	ZR 700 VSD	1859	111.5	3939	700	11.4	-	70-78	68-76	11850	4675	2470	2120
	ZR 750	1704	102.2	3611	750	10.5	-	76	74	10325	4060	2400	2120
	ZR 900 VSD	2057	123.4	4359	935	12.5	-	68-79	68-77	11850	4675	2470	2120
	50 Hz - 13 bar(e)												
ŧ.	ZR 145	297	17.8	629	145	4.2	-30	75	72	3530	3440	2000	1650
N B	ZR 250	505	30.3	1070	250	5.4	-28	72	70	5360	4340	2000	1650
-	ZR 275	550	33.0	1165	275	5.7	-30	72	70	5560	4340	2000	1650
9/M)	ZR 145	297	17.8	629	145	2.0	-	75	72	2900	2540	2000	1650
ack	ZK 250	505	30.3	1070	250	3.4	-	72	70	3990	3140	2000	1650
<u> </u>	ZK 2/5	551	33.1	1168	275	3.7	-	/2	/0	4190	3140	2000	1650

	ZR	Fre	e air delive	rv ⁽¹⁾	Installed	Cooling	Pressure	Sound p	ressure	Weight		Dimensions	
	watercooled				motor	water	dewnoint	lev	e ⁽⁴⁾				
						consumn-	(3)						
						tion ⁽²⁾							
								w/o duct	with duct		Α	В	c
	Туре	l/s	m³/min	cfm	HP	l/s	°C	dB(A)	dB(A)	kg	mm	mm	mm
	60 Hz - 7 bar(e)												
•	ZR 110	352	21.1	746	150	3.9	-28	70	68	3265	3440	2000	1650
₹ _	ZR 160	463	27.8	981	200	4.4	-25	67	66	4695	4340	2000	1650
ye ith	ZR 200	574	34.4	1216	250	4.9	-25	67	66	5305	4340	2000	1650
<u>s</u> a	ZR 250	667	40.0	1413	300	5.4	-28	67	66	5515	4340	2000	1650
쁘	ZR 275	752	45.1	1593	350	5.9	-30	67	66	5635	4340	2000	1650
₽	ZR 110	352	21.1	746	150	1.9	-	67	65	2635	2540	2000	1650
N N	ZR 160	463	27.8	981	200	2.3	-	67	66	3785	3140	2000	1650
w/d	ZR 200	574	34.4	1216	250	2.9	-	67	66	3935	3140	2000	1650
<u>ی</u> اور	ZR 250	667	40.0	1413	300	3.4	-	67	66	4145	3140	2000	1650
Pa	ZR 275	752	45.1	1593	350	3.8	-	67	66	4265	3140	2000	1650
	60 Hz - 8.6 bar(e)												
	ZR 110	321	19.3	679	150	3.8	-28	70	68	3265	3440	2000	1650
Ē	ZR 132 VSD	372	22.3	778	175	3.9	-28/-32	68-72	66-69	3500	3440	2000	1650
7e	ZR 145	398	23.9	843	200	4.1	-30	70	68	3530	3440	2000	1650
ā	ZR 160	419	25.1	888	200	4.4	-25	67	66	4695	4340	2000	1650
Ę	ZR 160 VSD	431	25.9	913	215	4.2	-28/-32	68-74	66-71	3500	3440	2000	1650
	ZR 200	516	31.0	1093	250	4.6	-25	67	66	5305	4340	2000	1650
ΪĘ	ZR 250	619	37.1	1312	300	5.2	-28	67	66	5515	4340	2000	1650
5	ZR 250 VSD	721	43.3	1528	335	5.8	-25/-30	63-73	62-71	6080	4340	2000	1650
Ë	ZR 275	726	43.6	1538	350	5.8	-30	67	66	5635	4340	2000	1650
	ZR 315 VSD	836	50.2	1771	400	6.8	-25/-30	63-73	62-71	6080	4340	2000	1650
	ZR 110	321	19.3	679	150	1.7	-	67	65	2635	2540	2000	1650
	ZR 132 VSD	376	22.6	797	175	1.9	-	62-68	61-66	2870	2540	2000	1650
	ZR 145	398	23.9	843	200	2.1	-	68	66	2900	2540	2000	1650
	ZR 160	419	25.1	888	200	2.1	-	67	66	3785	3140	2000	1650
	ZR 160 VSD	436	26.1	922	215	2.2	-	62-70	61-66	2870	2540	2000	1650
	ZR 200	516	31.0	1093	250	2.6	-	67	66	3935	3140	2000	1650
	ZR 250	619	37.1	1312	300	3.1	-	67	66	4145	3140	2000	1650
er)	ZR 250 VSD	721	43.3	1528	335	3.7	-	63-73	62-71	4710	3140	2000	1650
²	ZR 275	726	43.6	1538	350	3.7	-	67	66	4265	3140	2000	1650
	ZR 300	755	45.3	1600	350	4.1	-	71	70	6550	3700	2400	2120
Σ	ZR 315	850	51.0	1801	400	4.6	-	72	70	6550	3700	2400	2120
	ZR 315 VSD	836	50.2	1771	400	4.3	-	63-73	62-71	4710	3140	2000	1650
<u>Š</u>	ZR 355	955	57.3	2024	450	5.1	-	72	70	6950	3700	2400	2120
ž	ZR 400	1043	62.6	2210	500	5.6	-	72	71	7050	3700	2400	2120
Pac	ZR 400 VSD	1114	66.9	2361	570	6.4	-	68-75	66-73	8320	4060	2470	2120
	ZR 450	1306	78.4	2767	600	7.8	-	74	72	9300	4060	2400	2120
	ZR 500	1538	92.3	3259	700	8.9	-	74	72	9500	4060	2400	2120
	ZR 500 VSD	1318	79.1	2793	703	7.6	-	68-76	66-74	8320	4060	2470	2120
	ZR 630	1700	102.0	3602	800	9.9	-	76	74	10225	4060	2400	2120
	ZR 700 VSD	2063	123.8	4371	938	11.6	-	70-78	68-76	11850	4675	2470	2120
	ZR 750	1939	116.3	4109	900	11.2	-	76	74	10225	4060	2400	2120
	ZR 900 VSD	2456	147.4	5204	1253	13.2	-	68-78	68-76	11850	4675	2470	2120

ZR 110-750 and ZR 132-900 VSD compressors - 60 Hz

(1) Reference conditions:

dry air
absolute inlet pressure 1 bar(a) - cooling and air intake temperature 20 °C

- nominal working pressure

 performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 $^{\circ}\mathrm{C}$

(3) Max. capacity is at reference pressure and not at max. pressure

- (4) Pressure dewpoint is specified for - 20 °C cooling air/water temperature
 - relative humidity of 60 %

 - nominal working pressure
 load level of minimum 50 %
 - For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions

- Conversions 1 kg = 2.2 lbs 1 mm = 0.039 inch
- ${}^{\circ}F = {}^{\circ}C \times 9/5 + 32$

	ZR watercooled	Free	air deliver	y ⁽¹⁾	Installed motor	Cooling water consump- tion ⁽²⁾	Pressure dewpoint ⁽³⁾	Sound p leve	oressure el ⁽⁴⁾	Weight		Dimensions	
	Туре	l/s	m³/min	cfm	НР	l/s	°C	w/o duct dB(A)	with duct dB(A)	kg	A mm	B mm	C mm
	60 Hz - 10.4 ba	ar(e)								, j			
	ZR 110	287	17.2	608	150	3.5	-28	70	68	3265	3440	2000	1650
	ZR 132 VSD	330	19.8	699	175	3.9	-28/-32	68-72	66-69	3500	3440	2000	1650
÷	ZR 145	336	20.2	712	200	4.1	-30	70	68	3530	3440	2000	1650
Drye	ZR 160	375	22.5	795	200	4.4	-25	67	66	4695	4340	2000	1650
QW	ZR 160 VSD	392	23.5	831	215	4.2	-28/-32	68-74	66-71	3500	3440	2000	1650
li ti	ZR 200	459	27.5	973	250	4.7	-25	67	66	4845	4340	2000	1650
۲ (v	ZR 250	548	32.9	1161	300	5.2	-28	67	66	5515	4340	2000	1650
Ē	ZR 250 VSD	648	38.9	1373	335	5.8	-25/-30	67-73	65-71	6080	4340	2000	1650
	ZR 275	641	38.5	1358	350	5.7	-30	67	66	5635	4340	2000	1650
	ZR 315 VSD	746	44.8	1581	400	6.7	-25/-30	67-73	65-71	6080	4340	2000	1650
	ZR 110	287	17.2	608	150	1.7	-	67	65	2635	2540	2000	1650
	ZR 132 VSD	333	20.0	706	214	1.9	-	62-68	61-66	2590	2540	2000	1650
	ZR 145	336	20.2	712	200	2.0	-	67	66	2900	2540	2000	1650
	ZR 160	375	22.5	795	200	2.2	-	67	66	3785	3140	2000	1650
	ZR 160 VSD	394	23.6	835	215	2.1	-	62-70	61-66	2590	2540	2000	1650
	ZR 200	459	27.5	973	250	2.6	-	67	66	3935	3140	2000	1650
	ZR 250	548	32.9	1161	300	3.1	-	67	66	4145	3140	2000	1650
	ZR 250 VSD	648	38.9	1373	335	3.7	-	64-70	65-68	4710	3140	2000	1650
/er)	ZR 275	641	38.5	1358	350	3.6	-	67	66	4265	3140	2000	1650
הם	ZR 300	677	40.6	1434	350	4.3	-	71	70	6550	3700	2400	2120
IM	ZR 315	762	45.7	1615	400	4.6	-	72	70	6550	3700	2400	2120
0/M	ZR 315 VSD	746	44.8	1581	400	4.3	-	63-73	62-71	4710	3140	2000	1650
ick (ZR 355	858	51.5	1818	450	5.1	-	73	71	6950	3700	2400	2120
Pa	ZR 400	945	56.7	2002	500	5.5	-	73	71	7050	3700	2400	2120
	ZR 400 VSD	979	58.7	2074	570	5.7	-	69-76	66-73	8350	4060	2470	2120
	ZR 450	1144	68.6	2424	600	7.7	-	74	ХХ	9300	4060	2400	2120
	ZR 500	1332	79.9	2822	700	8.7	-	75	XX	9500	4060	2400	2120
	ZR 500 VSD	1150	69.0	2437	703	7.6	-	69-77	66-74	8350	4060	2470	2120
	ZR 630	1474	88.4	3123	800	9.4	-	76	74	10225	4060	2400	2120
	ZR 700 VSD	1859	111.5	3939	938	11.4	-	70-78	68-76	11850	4675	2470	2120
	ZR 750	1739	104.3	3685	900	10.8	-	76	74	10225	4060	2400	2120
	ZR 900 VSD	2057	123.4	4359	1253	12.5	-	68-79	68-77	11850	4675	2470	2120
	60 Hz - 13 bar	(e)	1		1							1	
Dryer)	ZR 145	299	17.9	634	200	4.3	-28	75	72	3530	3440	2000	1650
ith IMD	ZR 250	491	29.5	1040	300	5.4	-28	72	70	5515	4340	2000	1650
2	ZR 275	550	33.0	1165	350	5.8	-30	72	70	5635	4340	2000	1650
k Dryer)	ZR 145	299	17.9	634	200	2.0	-	75	72	2900	2540	2000	1650
Pac w/o IMD	ZR 250	491	29.5	1040	300	3.4	-	72	70	4145	3140	2000	1650
~ ~	ZR 275	550	33.0	1165	350	3.8	-	72	70	4265	3140	2000	1650
(1) Refei	rence conditions:			(3)	Max. capaci	ty is at referer	nce pressure ar	nd not at max.	(5) ±	3 dB(A) measu	ıred at a dista	nce of 1 m and	1

- dry air

- absolute inlet pressure 1 bar(a)

cooling and air intake temperature 20 °C
 nominal working pressure
 performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

Max. capacity is at reference pressure and not at max. pressure

- (4) Pressure dewpoint is specified for 20 °C cooling air/water temperature relative humidity of 60 %

 - nominal working pressure
 load level of minimum 50 % For VSD: at reference speed

± 3 dB(A) mea ce of 1 m ar according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions Conversions

1 kg = 2.2 lbs
 1 mm = 0.039 inch
 °F = °C x 9/5 + 32
	ZT aircooled Free air delivery "		Installed motor	Installed fan motor	Pressure dewpoint	Sound p lev	oressure el ⁽⁴⁾	Weight	Dimensions				
	Туре	l/s	m³/min	cfm	kW	kW	°C	w/o duct dB(A)	with duct dB(A)	kg	A mm	B mm	C mm
	50 Hz - 7.5 bar(e)												
	ZT 110	312	18.7	661	110	4.8	-28	72	70	4095	4040	2000	1650
yer)	ZT 132	360	21.6	763	132	4.8	-29	73	70	4220	4040	2000	1650
D Dr	ZT 145	390	23.4	826	145	4.8	-30	73	71	4360	4040	2000	1650
MIM	ZT 160	460	27.57	973	160	8.8	-30	77	75	5625	5040	2100	1650
(wit	ZT 200	563	33.75	1191	200	8.8	-25	77	75	6285	5040	2100	1650
Ë	ZT 250	705	42.31	1493	250	8.8	-28	77	75	6280	5040	2100	1650
	ZT 275	740	44.38	1566	315	18.5	-30	77	75	6630	5040	2100	1650
er)	ZT 110	314	18.8	665	110	4.8	-	71	70	3585	4040	2000	1650
Dry€	ZT 145	362	21.7	/6/	132	4.8	-	72	70	3/10	4040	2000	1650
MD	ZT 160	392	23.5	072	145	4.8	-	72	70	5850	4040 5040	2000	1650
//o	ZT 100	563	33.8	1191	200	8.8	-	77	75	5385	5040	2100	1650
ick (v	ZT 250	705	42.3	1493	250	8.8		77	75	5380	5040	2100	1650
Å	ZT 275	740	44.4	1566	275	8.8	-	77	75	5580	5040	2100	1650
	50 Hz - 8.6 bar(e)												
	ZT 110	281	16.9	595	110	4.8	-28	72	70	4095	4040	2000	1650
	ZT 132	322	19.3	682	132	4.8	-29	73	70	4220	4040	2000	1650
	ZT 132 VSD	349	20.9	739	132	4.8	-25/-30	67-71	66-70	4330	4040	2000	1650
er)	ZT 145	361	21.6	785	145	4.8	-30	73	71	4360	4040	2000	1650
Dry	ZT 160	422	25.3	894	160	8.8	-30	77	75	5625	5040	2100	1650
IMD	ZT 160 VSD	404	24.2	856	160	4.8	-25/-30	67-74	66-71	4330	4040	2000	1650
with	ZT 200	510	30.6	1081	200	8.8	-25	77	75	6285	5040	2100	1650
Ħ	ZT 250	661	39.7	1401	250	8.8	-28	77	75	6280	5040	2100	1650
	ZT 250 VSD	699	41.9	1480	250	18.5	-25/-30	70-77	68-75	6660	5040	2100	1650
	ZT 275	696	41.8	1475	275	18.5	-30	77	75	6630	5040	2100	1650
	ZT 315 VSD	789	47.4	1672	299	18.5	-25/-30	70-78	68-76	6660	5040	2100	1650
	ZT 110	281	16.9	595	110	4.8	-	71	70	3585	4040	2000	1650
	ZT 132	322	19.3	682	132	4.8	-	72	70	3710	4040	2000	1650
÷	ZT 132 VSD	354	21.2	750	132	4.8	-	67-74	66-71	3820	4040	2000	1650
Drye	ZI 145	361	21.6	/85	145	4.8	-	72	/0	3850	4040	2000	1650
MD	ZT 160 VCD	422	25.3	894	160	8.8	-	11	/5	2020	5040	2100	1650
0//0	ZT 200	510	24.0	1081	200	4.0	-	77	75	5225	5040	2000	1650
ack (ZT 200	661	39.7	1401	250	8.8	-	77	75	5380	5040	2100	1650
4	ZT 250 VSD	699	41.9	1480	250	8.8	-	70-77	68-75	6130	5040	2100	1650
	ZT 275	696	41.8	1475	275	8.8	-	77	75	5580	5040	2100	1650
	ZT 315 VSD	789	47.4	1672	299	8.8	-	70-78	68-76	6130	5040	2100	1650
	50 Hz - 10 bar(e)			1	1		1	1	1	1	1	1	1
	ZT 110	260	15.6	551	110	4.8	-28	72	70	4095	4040	2000	1650
	ZT 132	313	18.8	662	132	4.8	-29	73	70	4220	4040	2000	1650
	ZT 132 VSD	316	19.0	670	132	4.8	-25/-30	67-71	66-70	4330	4040	2000	1650
(er)	ZT 145	334	20.0	707	145	4.8	-30	73	70	4360	4040	2000	1650
had	ZT 160	389	23.3	823	160	8.8	-30	78	76	5625	5040	2100	1650
IMI	ZT 160 VSD	370	22.2	784	160	4.8	-25/-30	67-74	66-71	4330	4040	2000	1650
(witł	ZT 200	490	29.4	1038	200	8.8	-30	78	76	5825	5040	2100	1650
Ħ	ZT 250	608	36.5	1287	250	8.8	-28	78	76	6280	5040	2100	1650
	ZT 250 VSD	622	37.3	1316	250	18.5	-25/-30	71-78	69-76	6660	5040	2100	1650
	ZT 275	671	40.2	1420	275	18.5	-30	78	76	6630	5040	2100	1650
-	ZT 315 VSD	709	42.5	1501	299	18.5	-25/-30	71-79	69-77	6660	5040	2100	1650
	ZI 110 ZT 122	261	15.7	553	110	4.8	-	/1	/0	3560	4040	2000	1650
	ZT 132	314	18.8	670	132	4.8	-	72	///	3/00	4040	2000	1650
ar)	ZT 145	320	19.2	0/8	132	4.8		0/-/1	00-70	4050	4040	2000	1650
Drye	∠1 140 7T 160	330	20.1	200	140	4.8	-	72	70	5050	4040 5040	2000	1650
IMD	21 100 7T 160 VSD	309	23.3	023 814	160	0.0	-	67-74	/0 66_71	4050	2040	2100	1000
0/M	ZT 200	<u>4</u> 90	23.0	1038	200	9.0		78	76	5385	5040	2100	1650
ack (ZT 250	608	36.5	1287	250	8.8	-	78	76	5380	5040	2100	1650
4	ZT 250 VSD	622	37.3	1316	250	8.8	-	71-78	69-76	6130	5040	2100	1650
	ZT 275	671	40.2	1420	275	8.8	-	78	76	5580	5040	2100	1650
	ZT 315 VSD	709	42.5	1501	299	8.8	-	71-79	69-77	6130	5040	2100	1650

ZT 110-275 and ZT 132-315 VSD compressors - 50 Hz $\,$

	ZR watercooled	Free air delivery ⁽¹⁾		Installed motor	Cooling water consump- tion ⁽²⁾	Pressure dewpoint (3)	Sound pressure level ⁽⁴⁾		Weight	Dimensions		S	
	Туре	l/s	m³/min	cfm	HP	l/s	°C	w/o duct dB(A)	with duct dB(A)	kg	A mm	B mm	C mm
	60 Hz - 10.4 ba	r(e)											
	ZR 110	287	17.2	608	150	3.5	-28	70	68	3265	3440	2000	1650
	ZR 132 VSD	330	19.8	699	175	3.9	-28/-32	68-72	66-69	3500	3440	2000	1650
Ê	ZR 145	336	20.2	712	200	4.1	-30	70	68	3530	3440	2000	1650
Irye	ZR 160	375	22.5	795	200	4.4	-25	67	66	4695	4340	2000	1650
Q	ZR 160 VSD	392	23.5	831	215	4.2	-28/-32	68-74	66-71	3500	3440	2000	1650
t t	ZR 200	459	27.5	973	250	4.7	-25	67	66	4845	4340	2000	1650
: (wi	ZR 250	548	32.9	1161	300	5.2	-28	67	66	5515	4340	2000	1650
Ë	ZR 250 VSD	648	38.9	1373	335	5.8	-25/-30	67-73	65-71	6080	4340	2000	1650
	ZR 275	641	38.5	1358	350	5.7	-30	67	66	5635	4340	2000	1650
	ZR 315 VSD	746	44.8	1581	400	6.7	-25/-30	67-73	65-71	6080	4340	2000	1650
	ZR 110	287	17.2	608	150	1.7	-	67	65	2635	2540	2000	1650
	ZR 132 VSD	333	20.0	706	214	1.9	-	62-68	61-66	2590	2540	2000	1650
	ZR 145	336	20.2	712	200	2.0	-	67	66	2900	2540	2000	1650
	ZR 160	375	22.5	795	200	2.2	-	67	66	3785	3140	2000	1650
	ZR 160 VSD	394	23.6	835	215	2.1	-	62-70	61-66	2590	2540	2000	1650
	ZR 200	459	27.5	973	250	2.6	-	67	66	3935	3140	2000	1650
	ZR 250	548	32.9	1161	300	3.1	-	67	66	4145	3140	2000	1650
	ZR 250 VSD	648	38.9	1373	335	3.7	-	64-70	65-68	4710	3140	2000	1650
er)	ZR 275	641	38.5	1358	350	3.6	-	67	66	4265	3140	2000	1650
Dry	ZR 300	677	40.6	1434	350	4.3	-	71	70	6550	3700	2400	2120
QMI	ZR 315	762	45.7	1615	400	4.6	-	72	70	6550	3700	2400	2120
0/N	ZR 315 VSD	746	44.8	1581	400	4.3	-	63-73	62-71	4710	3140	2000	1650
ck (r	ZR 355	858	51.5	1818	450	5.1	-	73	71	6950	3700	2400	2120
Pa	ZR 400	945	56.7	2002	500	5.5	-	73	71	7050	3700	2400	2120
	ZR 400 VSD	979	58.7	2074	570	5.7	-	69-76	66-73	8350	4060	2470	2120
	ZR 450	1144	68.6	2424	600	7.7	-	74	xx	9300	4060	2400	2120
	ZR 500	1332	79.9	2822	700	8.7	-	75	xx	9500	4060	2400	2120
	ZR 500 VSD	1150	69.0	2437	703	7.6	-	69-77	66-74	8350	4060	2470	2120
	ZR 630	1474	88.4	3123	800	9.4	-	76	74	10225	4060	2400	2120
	ZR 700 VSD	1859	111.5	3939	938	11.4	-	70-78	68-76	11850	4675	2470	2120
	ZR 750	1739	104.3	3685	900	10.8	-	76	74	10225	4060	2400	2120
	ZR 900 VSD	2057	123.4	4359	1253	12.5	-	68-79	68-77	11850	4675	2470	2120
	60 Hz - 13 bar(e)					1						
)ryer)	ZR 145	299	17.9	634	200	4.3	-28	75	72	3530	3440	2000	1650
₩ W	ZR 250	491	29.5	1040	300	5.4	-28	72	70	5515	4340	2000	1650
Wi	ZR 275	550	33.0	1165	350	5.8	-30	72	70	5635	4340	2000	1650
(Jaker)	ZR 145	299	17.9	634	200	2.0	-	75	72	2900	2540	2000	1650
Pack /o IMD D	ZR 250	491	29.5	1040	300	3.4	-	72	70	4145	3140	2000	1650
<u> </u>	ZR 275	550	33.0	1165	350	3.8	-	72	70	4265	3140	2000	1650

(1) Reference conditions:

- dry air

- dry air
 absolute inlet pressure 1 bar(a)
 cooling and air intake temperature 20 °C
 nominal working pressure
 performance of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) Cooling water temperature rise of 15 °C

(3) Max. capacity is at reference pressure and not at max. pressure

(4) Pressure dewpoint is specified for
 20 °C cooling air/water temperature
 relative humidity of 60 %

- nominal working pressure
 load level of minimum 50 % For VSD: at reference speed

(5) ± 3 dB(A) measured at a distance of 1 m and according to ISO 2151:2004 and using ISO 9614-2

(6) Maximum intake / cooling air temperature is 50 °C for HAT versions

- Conversions 1 kg = 2.2 lbs 1 mm = 0.039 inch °F = °C x 9/5 + 32

	ZT aircooled	Free air delivery ⁽¹⁾			Installed Installed Pro motor fan de motor		Pressure dewpoint	Pressure Sound pressure dewpoint level (4) (3)			Weight Dimensions		
	Туре	l/s	m³/min	cfm	kW	kW	°C	w/o duct dB(A)	with duct dB(A)	kg	A mm	B mm	C mm
	50 Hz - 7.5 bar(e)												
	ZT 110	312	18.7	661	110	4.8	-28	72	70	4095	4040	2000	1650
yer)	ZT 132	360	21.6	763	132	4.8	-29	73	70	4220	4040	2000	1650
D Dr	ZT 145	390	23.4	826	145	4.8	-30	73	71	4360	4040	2000	1650
th IM	ZT 160	460	27.57	973	160	8.8	-30	77	75	5625	5040	2100	1650
= (wit	ZT 200	563	33.75	1191	200	8.8	-25	77	75	6285	5040	2100	1650
Ε	ZT 250	705	42.31	1493	250	8.8	-28	//	/5	6280	5040	2100	1650
	ZT 275	214	44.38	665	315	18.5	-30	71	75	2585	5040	2100	1650
er)	ZT 110	362	21.7	767	132	4.0		72	70	3710	4040	2000	1650
Dry	ZT 145	392	23.5	829	145	4.8	-	72	70	3850	4040	2000	1650
IMD	ZT 160	460	27.6	973	160	8.8	-	77	75	5185	5040	2100	1650
o//v)	ZT 200	563	33.8	1191	200	8.8	-	77	75	5385	5040	2100	1650
ack	ZT 250	705	42.3	1493	250	8.8	-	77	75	5380	5040	2100	1650
	ZT 275	740	44.4	1566	275	8.8	-	77	75	5580	5040	2100	1650
	50 Hz - 8.6 bar(e)												
	ZT 110	281	16.9	595	110	4.8	-28	72	70	4095	4040	2000	1650
	ZT 132	322	19.3	682	132	4.8	-29	73	70	4220	4040	2000	1650
	ZT 132 VSD	349	20.9	739	132	4.8	-25/-30	67-71	66-70	4330	4040	2000	1650
ryer)	ZT 145	361	21.6	785	145	4.8	-30	73	71	4360	4040	2000	1650
4D D	ZT 160 VCD	422	25.3	894	160	8.8	-30	//	/5	5625	5040	2100	1650
ith IN	ZT 160 VSD	404 510	24.2	85b	200	4.8	-25/-30	b/-/4 77	50-71	4330	4040 5040	2000	1650
Ŧ (v	ZT 200 ZT 250	661	30.0	1401	200	8.8	-25	77	75	6280	5040	2100	1650
	ZT 250 VSD	699	41.9	1480	250	18.5	-25/-30	70-77	68-75	6660	5040	2100	1650
	ZT 275	696	41.8	1475	275	18.5	-30	77	75	6630	5040	2100	1650
	ZT 315 VSD	789	47.4	1672	299	18.5	-25/-30	70-78	68-76	6660	5040	2100	1650
	ZT 110	281	16.9	595	110	4.8	-	71	70	3585	4040	2000	1650
	ZT 132	322	19.3	682	132	4.8	-	72	70	3710	4040	2000	1650
÷	ZT 132 VSD	354	21.2	750	132	4.8	-	67-74	66-71	3820	4040	2000	1650
Jryer	ZT 145	361	21.6	785	145	4.8	-	72	70	3850	4040	2000	1650
MD [ZT 160	422	25.3	894	160	8.8	-	77	75	5185	5040	2100	1650
//o	ZT 160 VSD	410	24.6	869	160	4.8	-	67-74	66-71	3820	4040	2000	1650
ack (r	ZT 250	510	30.0	1/01	200	0.0	-	77	75	5380	5040	2100	1650
Pê	ZT 250 VSD	699	41 9	1401	250	8.8	-	70-77	68-75	6130	5040	2100	1650
	ZT 275	696	41.8	1475	275	8.8	-	77	75	5580	5040	2100	1650
	ZT 315 VSD	789	47.4	1672	299	8.8	-	70-78	68-76	6130	5040	2100	1650
	50 Hz - 10 bar(e)												
	ZT 110	260	15.6	551	110	4.8	-28	72	70	4095	4040	2000	1650
	ZT 132	313	18.8	662	132	4.8	-29	73	70	4220	4040	2000	1650
	ZT 132 VSD	316	19.0	670	132	4.8	-25/-30	67-71	66-70	4330	4040	2000	1650
ryer)	ZT 145	334	20.0	707	145	4.8	-30	73	70	4360	4040	2000	1650
1D D	ZT 160	389	23.3	823	160	8.8	-30	78	76	5625	5040	2100	1650
ith IN	21 160 VSD	3/0	22.2	/84	160	4.8	-25/-30	b/-/4 70	bb-/1	4330	4040	2000	1650
F (w	ZT 250	490 608	29.4	1030	200	0.0	-30	70	70	00Z0 6280	5040	2100	1650
	ZT 250 VSD	622	37.3	1316	250	18.5	-25/-30	71-78	69-76	6660	5040	2100	1650
	ZT 275	671	40.2	1420	275	18.5	-30	78	76	6630	5040	2100	1650
	ZT 315 VSD	709	42.5	1501	299	18.5	-25/-30	71-79	69-77	6660	5040	2100	1650
	ZT 110	261	15.7	553	110	4.8	-	71	70	3560	4040	2000	1650
	ZT 132	314	18.8	665	132	4.8	-	72	70	3700	4040	2000	1650
~	ZT 132 VSD	320	19.2	678	132	4.8	-	67-71	66-70	4050	4040	2000	1650
Dryer	ZT 145	336	20.1	711	145	4.8	-	72	70	3850	4040	2000	1650
MD	ZT 160	389	23.3	823	160	8.8	-	78	76	5185	5040	2100	1650
//o	2T 160 VSD	384	23.0	814	160	4.8	-	67-74	66-71	4050	4040	2000	1650
ick (v	21 200 7T 250	490	29.4	1038	200	8.8	-	78	76	5385	5040	2100	1650
Pa	21 200 7T 250 \/SD	622	30.5	128/	250	0.0	-	71-79	/0 69-76	6130	5040	2100	1650
	ZT 275	671	40.2	1420	230	8.8	-	78	76	5580	5040	2100	1650
	ZT 315 VSD	709	42.5	1501	299	8.8	-	71-79	69-77	6130	5040	2100	1650
						0.0				2.00		2.00	

ZT 110-275 and ZT 132-315 VSD compressors - 50 Hz $\,$

ZH Oil-free centrifugal compressors, 400-2750 kW, 500-3500 hp

Designed to save energy and guarantee reliability, Atlas Copco's ZH oil-free centrifugal compressors are provided as complete ready-to-integrate packages including internal piping, integrated coolers, motor, lubrication, inlet guide vanes, control system and 100% matched components. They are just what you need for large compressor rooms of 1-20 MW and for processes with a fluctuating or constant air demand. Choose the ZH and put your mind at rest: air is 100% certified oil-free according to ISO 8573-1 CLASS 0 (2010), and the compressors operate reliably even in extremes of temperature and humidity.

CUSTOMER BENEFITS

• Maximum uptime – All ZH components are easy to maintain, dismantle and re-assemble if required, thus reducing downtime. Advanced control and monitoring possibilities ensure that production interruptions are minimized. In addition, easily accessible major components, minimal service interventions and long overhaul intervals reduce maintenance time and costs. • **Maximum energy savings** – All components of the ZH, such as the backward leaning impeller, carbon ring air seals and inlet guide vanes, are designed to lower the pressure drops and provide the highest air volume with the lowest energy requirement.

• **Easy installation** – The design of the ZH includes internal piping, coolers, motor, lubrication, inlet guide vanes and control system: all ready for integration on site.

• Advanced control monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Certified 100% oil-free** – ZH compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.







Power-saving inlet guide vane

Effectively positioned before the 1st stage, with a constant delivery pressure in the control range, it adjusts the volume flow to the exact compressed air requirement, saving up to 9% power compared to conventional valve regulation.

Blow-off regulation for constant pressure applications

The volume flow control range of the turbo expands considerably at a constant delivery pressure due to the blow-off function.

The most flexible volume flow adaption for constant pressure processes.

Туре	Maximum working pressure	Volume flow ¹⁾		Motor rated power	Sound pressure level ²⁾	Approx. weight ³⁾	Dimensions ³⁾ L × W × H			
	bar	l/s	m³/min	kW	db(A)	kg	mm			
ZH 7000-15000-0	ZH 7000–15000–Centrifugal compressors, two-stage–with water cooling									
ZH 7000	3.0-5.0	1237-1876	74.2-112.6	315-500	68	8400-8900	4060 × 2120 × 2400			
ZH 10000	3.0-5.0	2038-2863	122.3-171.8	500-710	70	13710-13910	5250 × 2120 × 2400			
ZH 15000	3.0-5.0	3283-4604	3283-4604 197.0-276.2		74	17260-18460	5800 × 2370 × 2630			
ZH 7000-26000-0	entrifugal compressor	rs, three-stage – wit	th water cooling							
ZH 7000	6.0-10.4	1210-1943	70.6-116.6	450-800	70	9850-10850	4060 × 2120 × 2400			
ZH 10000	6.0-10.4	2051-2981	123.1-178.9	710-1120	72	15120-15720	5250 × 2120 × 2400			
ZH 15000	6.0-10.4	3281-4692	196.9-281.5	1120-1850	74	19210-21310	5800 × 2370 × 2630			
ZH 26000	6.0-10.4	4491-6955	269.5-417.3	1600-2750	84	40100-44000	$7300\times 3000\times 3500$			

1) Volume flow relating to reference conditions: intake pressure 1 bar, intake temperature 35°C, rel. humidity 60%, coolant temperature 26.7°C, motor 50 Hz

²⁾ Sound pressure level measured in accordance with ISO 2151 with tolerance of 3 dB(A)
 ³⁾ Standard specification - medium voltage motor engine IP 23

ZH 350+

Oil-free high-speed drive centrifugal compressors, 350 kW, 470 hp.

Atlas Copco's ZH 350+ oil-free centrifugal compressors are designed to save you energy. Operating at high speed and high efficiency, they are directly driven by a permanent magnet synchronous motor. Optimal 3-stage compression reduces operating costs to previously unattainable low levels. A further major benefit is that air is 100% certified oil-free according to ISO 8573-1 CLASS 0 (2010). With the ZH 350+ you get a complete plug-andrun package including internal piping, integrated coolers, motor, control system and 100% matched components.

CUSTOMER BENEFITS

• Maximum energy savings – All components of the ZH 350+ are designed to save energy. The high-speed drive means no oil lubrication, no intermediate gears and fewer rotating components, all of which drive down energy costs. The backward leaning impeller and the carbon ring air seals are designed to lower the pressure drops and provide the highest air volume with the lowest energy requirement.

• Advanced control monitoring – The compressor controller maximizes efficiency and reliability of the ZH 350+ by controlling the main drive motor and regulating system pressure within a predefined and narrow pressure band. The controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• **Maximum uptime** – All ZH 350+ components are easy to maintain, dismantle and re-assemble if required, thus reducing downtime. Advanced control and monitoring possibilities ensure that production interruptions are minimized. In addition, easily accessible major components, minimal service interventions and long overhaul intervals reduce maintenance time and costs.

• **Plug-and-run package** – The integrated design of the ZH 350+ includes internal piping, coolers, motor, and control system: all supplied as a ready-to-use package. Installation is fault-free, commissioning time is low and no external instrument air is required. You simply plug and run.

• **Certified 100% oil-free** – ZH 350+ compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.



Technical Specifications

F0/C0 11-	Wor pres	king sure	Free air delivery (1)						Installe pov	ed motor wer	Dimensions					
50/60 HZ	bar(e)	oar(e) psig	l/s		cfm		m³/h					mm in				
			Min	Max	Min	Max	Min	Мах	KVV	hp	A	В	C	A	В	C
ZH 350+	6-9	87-130	700	1100	1483	2330	2520	3960	350	470	2400	2000	2017	94.49	78.74	79.42

OIL-FREE COMPRESSORS FOR LOW & HIGH PRESSURE APPLICATIONS

Atlas Copco has special solutions in its range for applications which require very low or very high pressure. Whether you use them to handle granulate gently, aerate clarifiers evenly, or inflate PET bottles with high pressure, a lot of thought has gone into designing our compressors and they provide the required working pressure for each application in an energy-efficient way.

Solutions for low and high pressures

Atlas Copco has special solutions in its range for applications which require very low or very high pressure. Whether you use them to handle granulate gently, aerate clarifiers evenly, or inflate PET bottles with high pressure, a lot of thought has gone into designing our compressors and they provide the required working pressure for each application in an energy-efficient way.

For operations which require a lot of air but with a low overpressure, it is worth using special low-pressure systems.

They provide stable system pressure and an efficient air supply without disruptive pulsations or power drops, which occur when the compressed air diverts from the normal air network and the demand is controlled by a buffer container and a blow-off system. Our low-pressure systems are suitable for pressure increases of just above 0, up to 4 bar. So you can supply powders and granules, for example, gently cool and dry products, or aerate sewage plants.

Oil-free screw compressors, screw blowers and centrifugal compressors are available.

We have recently removed the previous ZL rotary piston blowers from our range, because we could no longer represent them in terms of energy efficiency, especially not compared to our new ZS+ screw blowers. The internal compression and a more efficient drive concept of the ZS+ series are significantly more efficient than the rotary piston blowers. The design of our ZB centrifugal compressors is particularly efficient. With the contactless electromagnetic position of the motor, which is located on the motor shaft itself along with the impeller, they achieve efficiencies of over 90%. The gearless machines are non-wearing and keep maintenance costs low.

A precise analysis of the requirements will show which solution is best for the application in question. Investing more in an expensive system often pays for itself in the first one to two years due to the improved energy efficiency.

We also offer efficient compressors for high pressures from 20 to 40 bar. We would even go so far as to say that, with our Class 0 certificate for oil-free machines and some constructive subtleties, our ZD high pressure compressor is a safe and energy-efficient compressed air solution for manufacturing PET bottles!

The risk of bottle manufacturers and bottlers contaminating their products with traces of oil due to unclean compressed air is reduced to zero. You'll find details of these and other machines for high and low pressure on the following pages.



ZE/ZA (VSD)

Oil-free rotary screw compressors, 22-500 kW / 40-700 hp. Page 84



ZS

Oil-free positive displacement screw blowers, 18-160 kW, 25-215 hp. Page 85



ZS+ VSD

Oil-free Variable Speed Drive positive displacement screw blowers, 22-160 kW, 40-215 hp. Page 86



ZB 100-160 VSD

Oil-free Variable Speed Drive centrifugal air compressors, 100-160 kW,135-215 hp. Page 87



HX / HN Oil-free reciprocating compressors Page 90



DM

Oil-less reciprocating trunk-piston compressors, up to 351 bar (a) (5090 psia), 30 kW. Page 88



P Oil-free reciprocating piston compressors, up to 40 bar (580 psig), 37-275 kW / 50-368 hp. Page 91 - 92



DX / DN

Oil-free reciprocating piston compressors, up to 45 bar (652 psig) 30-315 kW / 40-422 hp. Page 89





ZD

Oil-free screw and reciprocating piston compressors, up to 40 bar (580 psig), 136-770 kW / 182-1032 hp. Page 93 - 94

ZE/ZA (VSD) Oil-free rotary screw compressors, 22-500 kW / 40-700 hp.

Especially in harsh and dusty environments, a reliable supply of 100% certified oil-free compressed air is critical to ensure production continuity. Atlas Copco's low pressure ZE/ZA compressors fulfill this demand by offering a constant air flow at minimal energy costs. Integrated Variable Speed Drive (VSD) variants offer 35% extra energy savings on average by automatically tuning compressor flow to the precise air demand.

CUSTOMER BENEFITS

 Highest reliability – ZE/ZA compressors stand for durability and reliability. They incorporate Atlas Copco's proven screw technology, stainless steel coolers, AGMA A4/DIN 5 gears and state-of-the art electrical drive systems, all of which contribute to overall high reliability. ZE/ZA compressors are built using long-standing internal engineering practices, and are manufactured and tested according ISO 9001.

Certified 100% oil-free – ZE/ZA compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

 Reduced energy costs – With an air circuit designed to avoid and reduce pressure drops, the ZE/ZA is built to save energy. Features like VSD drive, a state-of-the-art oil-free compression element, and energy recovery greatly enhance energy savings.

• Easy installation – The compact design eliminates the need for extras and reduces installation to an absolute minimum, saving you time and money. Built for easy integration in your existing compressed air network, ZE/ZA compressors are up and running in no time.



TECHNICAL DATA	
Capacity FAD (I/s)	87 - 855 l/s
Capacity FAD (m³/h, cfm)	311 - 3078 m³/h
Working pressure	2.5 - 3.5 bar(e)
Installed motor power	22 - 500 kW

ZS Oil-free positive displacement screw blowers, 18-160 kW, 25-215 hp.

Atlas Copco's ZS blowers provide a continuous and reliable supply of 100% oil-free air – certified according to ISO 8573-1 CLASS 0 (2010). Integrating the proven benefits of screw technology, the ZS range will cut your energy costs by an average of 30% when compared to lobe technology.

CUSTOMER BENEFITS

• **Reliability** – Incorporating our proven screw technology and longstanding internal engineering practices, and designed, manufactured and tested in accordance with ISO 9001, the ZS gives you 24/7 reliability over its long lifetime. • **High efficiency** – Integrating the proven benefits of screw technology, the ZS range reduces energy costs by an average of 30% when compared to lobe technology.

• Certified 100% oil-free – ZS blowers provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **Easy installation** – Built for smooth integration in your existing compressed air network, ZS blowers are up and running in no time.



TECHNICAL DATA	
Capacity FAD (I/s)	75 - 1292 l/s
Capacity FAD (m³/h, cfm)	271 - 4651 m³/h
Working pressure	0.3 - 1 bar(e)
Installed motor power	18.5 - 160 kW

ZS+ VSD Oil-free Variable Speed Drive positive displacement screw blowers, 22-160 kW, 40-215 hp.

Atlas Copco's ZS+ VSD blowers balance the two key prerequisites when choosing a blower: reliability and energy efficiency. Integrating the proven benefits of screw technology, the ZS+ VSD reduces energy costs by an average of 30% when compared to lobe technology. But that's not all. The ZS+ VSD offers 100% oil-free air TÜV-certified according to ISO 8573-1 CLASS 0 (2010) – which is absolutely essential to avoid contamination and keep your production running smoothly. The ZS+ VSD is supplied as a state-of-the-art, ready-to-run package with completely integrated VSD convertor and proven Elektronikon® controller.



CUSTOMER BENEFITS

• **High reliability** – Incorporating our proven screw technology and long-standing internal engineering practices, and designed, manufactured and tested in accordance with ISO 9001, the ZS+ VSD gives you 24/7 reliability over its long lifetime.

• Maximum energy savings – Integrating the proven benefits of screw technology, the ZS+ VSD range reduces energy costs by an average of 30% when compared to lobe technology. VSD technology closely follows the air demand by automatically adjusting the motor speed and lowering system pressure, giving you even greater energy savings.

• Certified 100% oil-free – ZS+ VSD blowers provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• Easy installation – Delivered ready for use, ZS+ VSD blowers come as all-in-one packages including the state-of-the art Elektronikon® controller, integrated converter, forklift slots, check valve, air filter and silencers. The compact design eliminates the need for extras and reduces installation to an absolute minimum, saving you time and money.

• **Quiet operation** – Vibration and noise levels are low, resulting in a pleasant working environment for your operators.

TECHNICAL DATA	
Capacity FAD (I/s)	79 - 1272 l/s
Capacity FAD (m ³ /h, cfm)	152 - 2695 cfm
Working pressure	4 - 17 psig
Installed motor power	30 - 200 HP

ZB 100-160 VSD

Oil-free Variable Speed Drive centrifugal air compressors, 100-160 kW, 135-215 hp.

Atlas Copco's low pressure ZB 100-160 VSD blowers guarantee a continuous, highly reliable, energy-efficient and 100% oil-free air supply – certified according to ISO 8573-1 CLASS 0 (2010). These blowers are directly driven by a permanent magnet synchronous motor, which is vastly superior to conventional types. Moreover, the unique stainless steel backward lean impeller has integrated labyrinth seals which lead to high efficiency and minimal air leakage. The ZB 100-160 VSD is supplied as an all-in-one, ready-to-run package with a small footprint. Vibration and noise levels are low, resulting in an agreeable working environment for your operators.

CUSTOMER BENEFITS

• **High reliability** –Thanks to innovative magnetic bearings, low vibration turbo technology and integrated Variable Speed Drive, ZB 100-160 VSD blowers provide exceptional reliability and production continuity.

• **Maximum energy savings** – Install a ZB 100-160 VSD and benefit from reduced costs. The magnetic bearing design coupled with the



turbo compression system provides the highest air volume at the lowest energy consumption. Enjoy extra energy savings with integrated Variable Speed Drive technology, which automatically tunes the compressed air flow precisely to air demand.

• **Certified 100% oil-free** – All ZB blowers provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **Easy installation** – ZB 100-160 blowers are delivered ready for use. The all-in-one package includes a powerful PLC controller, integrated VSD, forklift slots, check valve, air filter, blow-off valve and silencers. ,

• Easy maintenance – ZB 100-160 blowers will save you time and costs due to easy serviceability. ,

• **Quiet operation** – Low vibration and noise levels provides a pleasant working environment for your operators.

The ZB module concept

For larger volume flows, multiple ZB VSD units can be connected in parallel.

- Higher availability
- Reliability through redundancy
- Wider operating range and high efficiency
- Extremely low sound pressure level
- Space-saving
- Expandable

The unique stainless steel turbo impeller with backward-curved blade design is a registered Atlas Copco patent with labyrinth seals for maximum efficiency and minimal air loss.

ZB – Turbo power



DM Oil-less reciprocating trunk-piston compressors, up to 351 bar (a) (5090 psia), 30 kW.

Atlas Copco's DM oil less reciprocating compressors will meet your needs for high pressure compression up to 351 bar(a). Compact, with very low vibration levels and a sealed crankcase, DM compressors are ideal for the compression of natural gas, processed biogas, hydrogen. They are based on technology developed by GreenField, a company with a renowned reputation worldwide and part of the Atlas Copco Group.

CUSTOMER BENEFITS

• **High degree of safety** – Its revolutionary "oil-less" technology guarantees that oil does not contaminate the gas. Its hermetically sealed crankcase ensures no emission of gases to the atmosphere, even gases with a low molecular weight.

• **High reliability** – Low compression ratios in the individual stages result in low thermal load and high reliability. The Scotch yoke principle means balanced forces and minimal vibration.

• Easy installation – Very compact, frame-mounted and incorporating
anti-vibration pads, DM compressors come as complete all-in packages
with a small footprint and are simple to install without the need for
complex piping arrangements.

• Low cost of ownership due to no water consumption and high efficiency.

• Low maintenance – An advanced maintenance concept ensures short downtimes.

• A wide array of solutions – DM compressors are available for inlet pressures of 1 to 40 bars, and 2 to 5 stage configurations. They are suitable for diverse applications such as CNG refueling stations and gas applications (e.g. Ex-zone 2 or optionally Ex-zone 1).



TECHNICAL DATA	
Capacity FAD (I/s)	7.5 - 61.4 l/s
Working pressure	1 - 350 bar(e)
Installed motor power	30 kW
Capacity	27 - 203 Nm³/h
Inlet pressure	1 - 40 bar
Gases handled	natural gas, processed biogas, hydrogen

DX / DN

Oil-free reciprocating piston compressors, up to 45 bar (652 psig) 30-315 kW / 40-422 hp.

Atlas Copco's DX/DN oil-free reciprocating booster is the alliance of an extremely robust design with the best of technology in terms of packaging and equipment. DX/ DN is your best partner in air and nitrogen compression from 7 to 45 bars. Available as a mono-stage or two-stage machine, it perfectly suits a wide variety of requirements in terms of flow and pressures. You will appreciate its canopy for its silencing properties and you will easily adopt the concrete frame that makes installation so easy. DX/DN compressors can be fitted downstream from an Atlas Copco Z compressor to create a complete package running from 1 to 40/45 bar.

CUSTOMER BENEFITS

• **Certified 100% oil-free** – DX/DN boosters provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation.

 Nitrogen-ready – We adapt the piston rings and packing rings to nitrogen composition, dew point and purity. We supply DX/DN with or without a canopy (gas detection). Inlet dewpoints from -10°C/+14°F to "bone dry" gas are handled.

• Energy savings – DX/DN boosters are also available in Variable Speed Drive versions, allowing for 35% energy savings due to:

- Unload losses are reduced to a minimum
- Load/no load transition losses are eliminated

- Precise pressure control allows a tighter pressure band and a lower average working pressure, resulting in reduced energy consumption.

• **Easy installation** – Fitted on a concrete base-plate, the DX/DN booster comes as an all-in-one package. The compact design eliminates the need for extras and accelerates installation, saving you time and money.

• **High reliability** – Low piston speed and low interstage temperatures preserve the inner parts of the machines. The horizontal design ensures a low vibration/pulsation level for increased reliability. Design is close to API 618.

 Advanced control and monitoring – The advanced Elektronikon® system helps you keep control of costs by monitoring overall system performance through service indications, malfunctions alarms and safety shutdowns.



TECHNICAL DATA	
Capacity FAD (I/s)	75 - 2870 l/s
Working pressure	12 - 42 bar(e)
Installed motor power	37 - 315 kW
Capacity FAD (m³/h, cfm)	271 - 10329 m³/h
Capacity	250 - 9500 Nm³/h
Inlet pressure	6 - 25 bar
Gases handled	air,nitrogen

HX / HN Oil-free reciprocating compressors

Atlas Copco's HX/HN oil-free reciprocating compressors are extremely reliable solutions for air, nitrogen, C0/C02, methane, hydrogen and argon. Designed for 24/24 industrial service, with minimal maintenance cost and long overhaul intervals, HX/HN compressors can work in a most efficient and cost-effective way under difficult site conditions.

CUSTOMER BENEFITS

• **Oil-free** – Thanks to their PTFE piston rings and long distance pieces, the compression chambers are perfectly oil-free. HX/HN compressors are the right solution when compressed air is in contact with the end product (drinkable water, gases).

• **Energy saving** – Reciprocating technology ensures excellent volumetric efficiency and economic operation in terms of energy. • **Flexibility** – A wide variety of regulation systems adjust the flow rate according to the real utilization of the machine: by stepped regulation (valve unloading); by-pass valve; variable speed drive; or a combination of the above solutions.

• **High reliability** – Low piston speed and low interstage temperatures preserve the inner parts of the machines. The horizontal design ensures a low vibration/pulsation for increased reliability. Design is close to API 618.

• Adaptability to your application – We can adapt the machine's internal parts and material to your gas composition requirements or to different inlet pressures. We can also adapt containers for rental equipment or in complete packages including dryer, filters and control panels. HX/HN compressors can work in difficult environments: outdoor, indoor, refineries, deserts (high inlet temperatures) and sandy environments.

• **Easy maintenance** – Horizontal design – safe and comfortable for operators – long service intervals (up to 8000 h/year without service intervention).



TECHNICAL DATA	
Capacity FAD (I/s)	45 - 3020 l/s
Working pressure	10 - 100 bar(e)
Installed motor power	37 - 560 kW
Capacity FAD (m³/h, cfm)	163 - 10873 m³/h
Capacity	150 - 10000 Nm³/h
Inlet pressure	1 - 24 bar
Gases handled	air, nitrogen, argon, carbon monoxide, carbon dioxide, hydrogen, argon,methane, biomethane

Ρ

Oil-free reciprocating piston compressors, up to 40 bar (580 psig), 37-275 kW / 50-368 hp.

Atlas Copco's P oil-free reciprocating compressors are a reference in the market for reliability and low cost of ownership. They deliver high-purity oil-free air for discharge pressures between 25 and 40 bar. Sturdy and designed for continuous industrial operation, P compressors deliver air safely, constantly and at low cost Up to 160 kW, P compressors come as very compact 3-stage machines. Above 160 kW, with the addition of an oil free screw unit in the first stage, they come as 4-stage machines. This innovative approach results in unrivalled benefits, maximizing flow in compact plug & play units.

CUSTOMER BENEFITS

• **100% oil-free** – Thanks to PTFE piston rings and long-distance pieces, the compression chambers are perfectly oil-free.

• Maximum energy savings – Reciprocating technology ensures excellent volumetric efficiency and economic operation in terms of energy. In addition, with the Elektronikon® controller you can adjust the required discharge pressure between 25 bar (362 psig) and 40 bar (580 psig) to reduce energy costs.

• Advanced control and monitoring – The advanced Elektronikon® system helps you keep control of costs by monitoring overall system performance through service indications, malfunction alarms and safety shutdowns.

• **High reliability** – Low piston speed and low inter-stage tempe ratures preserve the internal components. The horizontal design ensures low vibration/pulsation levels for increased reliability. Design is close to API 618.

• Low maintenance – The horizontal design is safe and comfortable for operators and maintenance personnel. Long service intervals reduce maintenance time and cost.

• **Easy installation** – Each P compressor is delivered as a complete package with no reassembly on site. Installation is fast, straightforward and safe. P compressors are fitted on a skid and can be installed on a suitable industrial floor with chemical bolts. This eliminates skid vibrations and preserves the motor and mechanical parts.



Technical Specifications*

	Discl	narge pressure	Flow					
Model	bar(e)	psig	l/s**	m³/h**	cfm**			
50 Hz								
P 37-50	40	580	45	162	96			
P 45-50	40	580	58	209	123			
P 55-50	40	580	72	259	153			
P 65-50	40	580	89	320	189			
P 90-50	40	580	125	450	265			
P 110-50	40	580	159	572	337			
P 132-50	40	580	190	684	403			
P 160-50	40	580	217	781	460			
P 180-50	40	580	247	889	523			
P 230-50	40	580	328	1181	695			
P 275-50	40	580	381	1372	807			
60 Hz								
P 37-60	40	580	52	187	110			
P 45-60	40	580	69	248	146			
P 65-60	40	580	90	324	191			
P 75-60	40	580	119	428	252			
P 90-60	40	580	150	540	318			
P 110-60	40	580	183	659	388			
P 132-60	40	580	205	738	434			
P 160-60	40	580	218	785	462			
P 180-60	40	580	234	842	496			
P 230-60	40	580	323	1163	684			
P 255-60	40	580	367	1321	778			

Reference conditions
 Ambient temperature & cooling water: 20°C, 68°F
 Suction pressure: 1 bar(e) (14.5 psig)
 Relative humidity: 0%

** Reference conditions according to ISO 1217, Edition 4, Annex C stipulating the Free Air Delivery measurement at the outlet of the package, net of all losses.

Standard limitations: Altitude: 1000 m (3200 feet) Standard equipment: up to 50°C (122°F) ambient temperature

ZD

Oil-free screw and reciprocating piston compressors, up to 40 bar (580 psig), 136-770 kW / 182-1032 hp.

Atlas Copco's ZD is the alliance of the world renowned ZR screw compressor, which delivers quality dry air at medium pressure, and the highly efficient D booster which brings the air to 40 bar. ZD represents a quantum leap in reciprocating technology. It is a champion in energy saving and its design is revolutionary. You will appreciate its silencing canopy and its concrete baseplate that makes installation so easy. With its numerous versions and versatility, ZD brings tremendous benefits to your bottom line.

CUSTOMER BENEFITS

• **Certified 100% oil-free** – ZD compressors provide you with 100% pure, clean air that complies with ISO 8573-1 CLASS 0 (2010) certification. CLASS 0 means zero risk of contamination; zero risk of damaged or unsafe products; zero risk of losses from operational downtime; and zero risk of damaging your company's hard-won professional reputation. In 2006 Atlas Copco was the first manufacturer in the world to receive such certification on an oil-free compressor.

• **High reliability** – The ZD's reliability is based on several fundamentals. The first compression stages are rotary, which are world renowned for reliability. Air is dried at the outlet of the screw compressor, so only dry air enters the D booster, eliminating problems linked to condensates. The D booster's horizontal design, with low vibration levels, ensures long life of internal components.

• **Maximum energy savings** – Being a 4-stage configuration, the ZD is 7% more efficient in terms of energy than the typical 3-stage configuration. In addition you can further reduce energy costs by adjusting the required discharge pressure between 25 bar (362 psig) and 40 bar (580 psig). ZD is also available in a Variable Speed Drive (VSD) version, enabling 35% energy savings. For blowing machines equipped with air recovery systems, re-injecting the air back to the booster allows further significant energy savings.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• A wide array of solutions for your compressor room – ZD allows you to manage your medium pressure and high pressure networks separately, which optimizes your investment and floor space.

• Low maintenance – For air-cooled versions, no external cooling system is needed, saving on investment, maintenance and water consumption.



Technical Specifications* The below data are for a discharge pressure of 40 bar (e)

DISCHARGE PRESSURE 40 BAR /580 PSIG	Available with			FAD*		Shaft input at ref. cond.	Pressure dew point at 40 bar > to	Sound pressure level***
	LOW VOLTAGE MOTOR	MEDIUM Voltage Motor**	l/s	m³/h	cfm	kW	°C	dB(A)
50 Hz								
ZD 800-50	•		220	792	466	143	3	73.7
ZD 1000-50	•		264	950	560	166	3	75.6
ZD 1200-50	•		334	1202	708	210	3	76.0
ZD 1400-50	•		401	1444	849	254	3	75.9
ZD 1600-50	•		445	1602	943	281	3	75.9
ZD 2100-50	•	•	627	2257	1329	384	3	81.2
ZD 2500-50	•	•	687	2473	1456	422	3	81.2
ZD 2750-50	•	•	779	2804	1651	488	3	82.2
ZD 3050-50	•	•	844	3038	1788	512	3	81.2
ZD 3350-50	•	•	937	3373	1986	571	3	81.2
ZD 3750-50	•	•	1074	3866	2276	678	3	83.1
ZD 4000-50	•	•	1114	4010	2360	712	3	84.0
60 HZ								
ZD 800-60	•		235	846	498	153	3	73.9
ZD 1000-60	•		287	1033	608	182	3	75.7
ZD 1200-60	•		317	1141	672	200	3	76.6
ZD 1400-60	•		398	1433	843	253	3	77.3
ZD 1600-60	•		457	1645	968	288	3	75.9
ZD 1900-60	•	•	547	1969	1159	389	3	80.7
ZD 2300-60	•	•	639	2300	1354	489	3	82.2
ZD 2500-60	•	•	725	2610	1536	441	3	81.7
ZD 3100-60	•	•	857	3085	1816	520	3	81.7
ZD 3500-60	•	•	951	3424	2016	585	3	83.8
ZD 4000-60	•	•	1141	4108	2418	722	3	84.0
VSD****								
ZD 1200 VSD	•		146/320	529/1152	311/678	94/208	3	77.3
ZD 1400 VSD	•		139/382	500/1375	294/809	94/255	3	77.3
ZD 2300 VSD	•		308/625	1109/2250	652/1324	193/397	3	83.9
ZD 2800 VSD	•		308/738	1109/2657	652/1564	193/481	3	83.9
ZD 3500 VSD	•		440/978	1584/3521	932/2072	270/607	3	83.9
ZD 4100 VSD	•		440/1099	1584/3957	932/2329	270/699	3	83.9

ZD MODELS	Overall dimensions (machines side by side)							
	А	В	C					
50 Hz	mm	mm	mm					
ZD 800-50	3460	4390	2185					
ZD 1000-50	3900	4590	2130					
ZD 1200-50	3900	4590	2130					
ZD 1400-50	4826	5003	2083					
ZD 1600-50	4826	5003	2083					
ZD 2100-50	4886	5345	2134					
ZD 2500-50	4886	5345	2134					
ZD 2750-50	4886	5345	2134					
ZD 3050-50	5980	5688	2400					
ZD 3350-50	5980	5688	2400					
ZD 3750-50	6843	5885	2578					
ZD 4000-50	6843	5885	2578					
60 HZ								
ZD 800-60	3460	4390	2185					
ZD 1000-60	3900	4590	2130					
ZD 1200-60	3900	4590	2130					
ZD 1400-60	3905	4920	2083					
ZD 1600-60	4826	5003	2083					
ZD 1900-60	4886	5345	2134					
ZD 2300-60	4886	5345	2134					
ZD 2500-60	4886	5345	2134					
ZD 3100-60	5980	5688	2400					
ZD 3500-60	5980	5688	2400					
ZD 4000-60	6843	5885	2578					
VSD****								
ZD 1200 VSD*****	3900	4590	2130					
ZD 1400 VSD	3905	4920	2083					
ZD 2300 VSD	4886	5345	2134					
ZD 2800 VSD	4886	5345	2134					
ZD 3500 VSD	6843	5885	2578					
ZD 4100 VSD	6843	5885	2083					

* At reference conditions and according to ISO 1217.

**Medium voltage motors (3 KV, 3.3 KV, 6 KV, 6.6 KV) for Japan only

***a-weighted sound pressure level LpA, sound power level LwA, uncertainty + 3dB, reference 20 µ Pa, according to ISO 3746 (for low voltage motors)

**** At minimum/maximum speeds

***** Please consult Atlas Copco

- Reference conditions:
- Inlet pressure: 1 bar(a)
- Relative air humidity: 0%
- Air inlet temperature: 20°C - Cooling water inlet temperature: 20°C
- Nominal effective working pressure: 40 bar

ZD plus and ZD RI ranges offer numerous combinations. Please contact your local Atlas Copco Customer Centre at www.atlascopco.com for a customized selection.

MEDICAL EQUIPMENT

Whether we like it or not, we all wind up in a hospital from time to time. When we do, we want to be sure that we receive the best possible care... and the purest possible air. That is where Atlas Copco lends a helping hand by supplying the reliable technology and global service.



MED / MED+ Medical air purifiers Page 97 - 98



GA MED

Screw compressors for medical applications Page 99 - 100

UAIR Medical Air Plant Page 101 - 102 mVAC Medical vacuum systems Page 103 - 105





Oxyplant

Medical oxygen plant Page 106 - 107



MED / MED+ Medical air purifiers

Medical Air: Purity and precision in critical healthcare environments

The critical field of patient care requires ultra-clean, purified, medical air delivered to operating theaters and hospital beds with absolute reliability. The Atlas Copco MED/MED+series of Medical Air Purifiers offersunique multi-stage filtration that converts regular compressed air from any type of compressor into internationally certified medical air. These innovative devices provide clean air for all your medical and surgical applications.

CUSTOMER BENEFITS

• Assured reliability – Built to the most exacting standards, the MED/ MED+ series is engineered to provide certified medical air even in areas with high ambient pollution. These air purifiers ensure high air quality in 'worst case' but real-life pollution scenarios. With the assurance of Atlas Copco's excellent worldwide after-sales service, the MED series offers the complete solution for critical air environments.

• **Medically certified** – The medical sector is more tightly regulated than ever before. Atlas Copco's MED/MED+ air purifiers are pre-certified to international regulations including Pharmacopoeia and quality norms such as ISO 13485. Pre-certification simplifies organization and inspection by regulatory bodies, saving the hospital time and money and reducing the risk of a rework of the system to satisfy requirements. MED/ MED+ air purifiers surpass the requirements of the most demanding standards and regulations such as:

- Medical Device Directive MDD 93/42/EEC.
- EN ISO 7396-1.
- ISO 14971.
- Health Technical Memorandums HTM 02-01 and HTM 2022.

Furthermore, they are designed and manufactured according to ISO 9001, ISO 14001 and the ISO 13485:2003 quality management system.

• Energy-efficient – The MED+ incorporates state-of-the-art energy management control with built-in purge control as standard (optionally available on the MED series). This purge control makes the purifiers more efficient, leading to energy savings of up to 90%, depending on installation and usage. The principle is simple. Although the regeneration time remains constant, the delay before switching from one tower to the other is controlled via the PDP sensor. As soon as the target PDP is reached, the dryer cycle that was on hold will resume by switching to the dry tower.

• **Assured purity** – MED/MED+ air purifiers provide the ultra clean air you require. Their innovative filtration system is the definitive medical air solution, while a small footprint allows you to make the most of the space available. The MED/MED+ offers unparalleled air purity through 7 stages of active purification.

Seven steps to quality medical air:

- A water separator to remove liquid water
- A bulk aerosol filter eliminates oil and water
- A fine coalescing filter removes even smaller particles of oil and water
- A desiccant dryer takes out any remaining water and CO2
- Activated carbon removes gaseous impurities
- A catalyst takes care of a CO oxidation
- A bacteria filter eliminates bacteria and fine particles. This bacteria filter is an Atlas Copco PDp filter, which has been externally tested and certified as a bacterial filter.





PurifierType Inlet pressure Max. inlet flow Puge Pressure drop bar(e) psig l/s m³/h cfm % dP, mbar psi MED / MED+ MED7 / MED7+ 7.0 14.8 19.0 102 25.2 510 7.4 7 10 145 8.4 30.2 17.8 15.8 510 7.4 13 188 9.4 33.8 19.9 14.1 510 7.4 MED13 / MED13+ 7 102 13.0 46.8 27.5 19.0 530 7.7 10 145 15.6 56.2 33.1 15.8 530 7.7 13 188 17.5 63.0 37.1 14.1 530 7.7 MED25 / MED25+ 7 102 25.0 90.0 53.0 18.0 560 8.1 10 145 30.0 108.0 63.6 15.0 560 8.1 13 188 33.8 121.7 71.6 13.3 560 8.1 MED35 / MED35+ 7 35.0 74.2 18.0 600 8.7 102 126.0 10 145 42.0 151.2 89.0 15.0 600 8.7 13 188 47.3 170.3 100.2 13.3 600 8.7 MED50 / MED50+ 102 180.0 106.0 19.0 820 11.9 50.0 7 10 145 60.0 216.0 127.1 15.8 820 11.9 11.9 13 188 67.5 243.0 143.0 14.1 820 MED70 / MED+70+ 7 102 70.0 252.0 148.3 18.0 660 9.6 10 145 84.0 302.4 178.0 15.0 660 9.6 13 188 94.5 340.2 200.2 13.3 660 9.6 MED80 / MED80+ 102 80.0 288.0 169.5 18.0 700 10.2 7 10 145 96.0 345.6 203.4 15.0 700 10.2 700 10.2 13 188 108.0 388.8 228.9 13.3 MED100 / MED100+ 7 102 100.0 360.0 211.9 19.0 820 11.9 10 145 120.0 432.0 254.3 15.8 820 11.9 820 11.9 13 188 135.0 486.0 286.1 14.1 MED145 / MED145+ 7 102 145.0 522.0 307.3 19.0 800 11.6 10 145 174.0 626.4 368.7 15.8 800 11.6 414.9 14.1 13 188 195.8 704.9 800 11.6

Technical specifications MED/ MED+ 060313

	MED					MED+				
	Weight, kg	Length, mm	Width, mm	Height, mm	NTP connection	Weight, kg	Length, mm	Width, mm	Height, mm	NTP connec- tion
MED7 / MED7+	184	950	650	885	1/2"	214	950	650	1851	1/2"
MED13 / MED13+	201	950	650	1075	1/2"	231	950	650	1851	1/2"
MED25 / MED25+	245	950	650	1300	1/2"	275	950	650	1851	1/2"
MED35 / MED35+	271	950	650	1545	1/2"	301	950	650	1851	1/2"
MED50 / MED50+	315	950	650	1915	1"	345	950	650	1858	1"
MED70 / MED+70+	446	1250	850	1545	1"	476	1250	850	1840	1"
MED80 / MED80+	494	1250	850	1915	1 1/2"	524	1250	850	1840	1"
MED100 / MED100+	502	1250	850	1915	1 1/2"	532	1250	850	1840	1"
MED145 / MED145+	620	1250	850	1915	1 1/2"	650	1250	850	1856	1"

Description	MED	MED+
EWD on filters and water drain	0	0
Inlet solenoid for remote control	-	0
NPT connection	0	0
QDT quality indicator	0	0
Catalyst(CO to CO ₂)	0	0
CO sensor	0	0
CO ₂ sensor	0	0
0 ₂ sensor	0	-
Overflow protection(nozzle)	0	0
AirContact and Combox-e with visualisation	-	0
Gateway(Profibus, Modbus)	-	0

GA MED Screw compressors for medical applications

Whether you work at a hospital, dental practice, veterinary lab or clinical laboratory, maximum reliability is your main priority. To successfully perform your work and make sure your equipment functions effectively, you rely on ultraclean air. Designed precisely for these applications, GA MED oil-injected compressors bring you proven reliability and Atlas Copco's latest high-efficiency compression element. You benefit from outstanding performance, flexible operation and the highest productivity, along with minimal total cost of ownership.

CUSTOMER BENEFITS

• Highest reliability – Three premium compressor series – GA 5-11 MED, GA 5-15 VSD MED and GA 15-22 MED are designed, manufactured and tested in accordance with ISO 9001, ISO 14001 and ISO 1217, Ed. 3, Annex C. Ensuring a long and trouble-free life at the lowest operating cost, each GA MED contains the latest generation of Atlas Copco's innovative oil-injected screw element.

• **Peace of mind** – All GA MED compressors are equipped with additional safety protections. Even in case of a single fault condition, the air demand is always assured.

• VSD – Driving down energy costs. Energy typically represents over 80% of a compressor's life cycle cost. Looking continuously to innovate and reduce customer costs, Atlas Copco pioneered Variable Speed Drive (VSD) technology in 1994. The GA 5-11 VSD MED range is the ideal solution for a fluctuating air demand. By monitoring the outlet pressure, the air flow is adjusted to the demand. Energy savings of 35% on average become a reality thanks to the high turndown ratio and the new fan saver cycle.

• Air system integration – The GA MED can be placed where you need it. Its low noise operation and dedicated air treatment equipment ensure a healthier environment in the plant room. Moreover, all GA MED compressors are delivered ready for use, significantly reducing installation costs.

• Advanced control and monitoring – To maximize efficiency and reliability, the Elektronikon® controls the main drive motor and regulates system pressure within a predefined and narrow pressure band. The Elektronikon® controller can be adapted to your specific needs with extra sensors, digital contacts, fieldbus, Internet and SMS communication functions. In combination with the ES multiple compressor controller, the operation of your complete compressor room is optimized.

• Integrated purity – When partnered with a dedicated MED+ or MED air purifying system, the GA MED generates compressed air into pure breathing quality air. You rest assured at all times that the air quality delivered by the system accords to what the doctor ordered.



		Max.working pressure		Capacity FAD*			Installe	Installed power		Weight	Length	Width	Height
		bar(e)	psig	l/s	m³/h	cfm	kW	hp	dBA	kg	mm	mm	mm
50 Hz													
GA 5 MED	7.5	7.5	109	15.0	54.0	31.8	5.5	7.5	60	257	1142	699	1240
	10	10	145	11.7	42.1	24.8	5.5	7.5	60	257	1142	699	1240
	13	13	189	8.4	30.2	17.7	5.5	7.5	60	257	1142	699	1240
GA 7 MED	7.5	7.5	109	21.8	78.5	46.2	7.5	10	61	270	1142	699	1240
	10	10	145	17.2	61.9	36.4	7.5	10	61	270	1142	699	1240
	13	13	189	14.2	51.1	30.1	7.5	10	61	270	1142	699	1240
GA 11 MED	7.5	7.5	109	30.7	110.5	65.0	11	15	62	293	1142	699	1240
	10	10	145	26.0	93.6	55.1	11	15	62	293	1142	699	1240
	13	13	189	22.0	79.2	46.6	11	15	62	293	1142	699	1240
GA 15 MED	7.5	7.5	109	43.0	154.8	91.1	15	20	72	375	1285	680	932
	10	10	145	36.3	130.7	76.9	15	20	72	375	1285	680	932
	13	13	189	30.1	108.4	63.8	15	20	72	375	1285	680	932
GA 18 MED	7.5	7.5	109	52.5	189.0	111.2	18.5	25	73	395	1285	680	932
	10	10	145	141.0	156.6	92.2	18.5	25	73	395	1285	680	932
	13	13	189	37.2	133.9	78.8	18.5	25	73	395	1285	680	932
GA 22 MED	7.5	7.5	109	60.2	216.7	127.6	22	30	74	410	1285	680	932
	10	10	145	51.7	186.1	109.5	22	30	74	410	1285	680	932
	13	13	189	45.0	162.0	95.3	22	30	74	410	1285	680	932
60 Hz													
GA 5 MED	100	7.4	107	15.0	54.0	31.8	5.5	7.5	60	257	1142	699	1240
	150	10.8	157	11.7	42.1	24.8	5.5	7.5	60	257	1142	699	1240
	175	12.5	181	8.5	30.6	18.0	5.5	7.5	60	257	1142	699	1240
GA 7 MED	100	7.4	107	21.0	75.6	44.5	7.5	10	61	270	1142	699	1240
	150	10.8	157	17.2	61.9	36.4	7.5	10	61	270	1142	699	1240
	175	12.5	181	14.2	51.1	30.1	7.5	10	61	270	1142	699	1240
GA 11 MED	100	7.4	107	30.4	109.4	64.4	11	15	62	293	1142	699	1240
	150	10.8	157	24.9	89.6	52.8	11	15	62	293	1142	699	1240
	175	12.5	181	22.0	79.2	46.6	11	15	62	293	1142	699	1240
GA 15 MED	100	7.4	107	42.5	153.0	90.1	15	20	72	375	1285	680	932
	150	10.8	157	35.8	128.9	75.9	15	20	72	375	1285	680	932
	175	12.5	181	29.3	105.5	62.1	15	20	72	375	1285	680	932
GA 18 MED	100	7.4	107	51.3	184.7	108.7	18.5	25	73	395	1285	680	932
	150	10.8	157	43.3	155.9	91.7	18.5	25	73	395	1285	680	932
	175	12.5	181	37.8	136.1	80.1	18.5	25	73	395	1285	680	932
GA 22 MED	100	7.4	107	60.6	218.2	128.4	22	30	74	410	1285	680	932
	150	10.8	157	50.7	182.5	107.4	22	30	7/	/10	1285	680	032

Technical specifications GA 5-7-11-15-18-22 MED

Technical specifications GA 5-7-11-15 VSD MED

	Max.working pressure		Capacity FAD*			Installed power		Noise Ievel	Weight	Length	Width	Height
	bar(e)	psig	l/s	m³/h	cfm	kW	hp	dBA	kg	mm	mm	mm
50 / 60 Hz												
	7.5	109	5.7-15.0	20.5-54.0	12.1-31.8	5.5	7.5	62	278	1395	699	1240
GA 5 VSD MED	10	145	7.1-13.2	25.6-47.5	15.0-28.0	5.5	7.5	62	278	1395	699	1240
	13	188	8.9-10.0	32.0-36.0	18.9-21.2	5.5	7.5	62	278	1395	699	1240
	7.5	109	4.9-20.3	14.4-73.0	10.4-43.0	7.5	10	64	280	1395	699	1240
GA 7 VSD MED	10	145	7.2-16.8	25.9-60.5	15.3-35.6	7.5	10	64	280	1395	699	1240
	13	188	5.1-13.8	23.0-49.7	10.8-29.2	7.5	10	64	280	1395	699	1240
	7.5	109	6.5-30.7	23.4-110.5	13.8-65.0	11	15	66	293	1395	699	1240
GA 11 VSD MED	10	145	8.7-24.1	31.3-86-8	18.4-51.1	11	15	66	293	1395	699	1240
	13	188	7.9-20.7	28.4-74.5	16.7-43.9	11	15	66	293	1395	699	1240
GA 15 VSD MED	7.5	109	9.1-37.1	32.8-133.6	19.3-78.6	7.5	10	69	300	1395	699	1240
	10	145	8.8-30.9	31.7-111.2	18.6-65.5	7.5	10	69	300	1395	699	1240
	13	188	8.5-24.8	30.6-89.3	18.0-52.5	7.5	10	69	300	1395	699	1240

* Unit performance measured according to ISO 1217, Annex C, latest edition.
** Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions: • Absolute inlet pressure 1 bar (14.5 psi) • Intake air temperature 20°C, 68°F

7.5 bar versions at 7 bar(e)
10 bar versions at 9.5 bar(e)
13 bar versions at 12.5 bar(e)

FAD is measured at the following working pressures:

Maximum working pressure for VSD machines: • 13 bar(e) (188 psig)

Atlas Copco introduces a new range of Medical Air Plants, consisting of 2-6 dedicated compressors, two air purifiers and the Medical Central controller. Medical Air Plant are available both for medical air and surgical air applications and are designed for continuous operation with frequent start/stop.

Medically certified

Atlas Copco's uAir Medical Air Plant are pre-certified to international regulations including Pharmacopoeia and quality norms such as ISO 13485. Pre-certification simplifies organization and inspection by regulatory bodies, saving the hospital time and money. Medical Air Plant comply with the requirements of the most demanding medical standards and regulations such as:

Medical Device Directive MDD	ISO 14971
93/42/EEC	
EN ISO 7396-1	HTM 02-01 and HTM 2022.

The advanced ES-Medical central controller supervises the complete medical installation (including compressors, dryers and vessels) and is specially designed to make plant complying with medical regulations.

- Full compliance with ISO7396-1, Chapter #6 "Monitoring and Alarm signals"
- Monitoring "Medical" and "Surgical" air lines
- Full integration with Building Management System and external Alarms systems
- Remote monitoring and connectivity functions
- Already preconfigured and tested
- Plug and play
- Internet-based visualization using a simple Ethernet connection
- Increased reliability, new safety function implemented: Emergency Force Local, internal logging and others
- Easy readout of the CO / CO₂ / flow sensors





Medical Equipment

uAIR Medical Air Plant (7-145 l/s / 15-307 cfm)

According to ISO 7396-1 three sources of supply should be foreseen. For this reason there are two compressors and one dryer reserved as a backup.

Туре	Pressure,	ure, Plant flow, IS07396-1 Compr		Compressors		Dryer		Min. Vessel	
	bar	l/s	l/m	Туре	Q-ty	Туре	Q-ty	Volume	Q-ty
uAIR-GF	4/8	6,8	408	GA5-10	1(+2)	MED7+	1(+1)	250	2
4 / 8 bar	4/8	12,6	756	GA7-10	1(+2)	MED13+	1(+1)	250	2
	4/8	20,6	1236	GA11-10	1(+2)	MED25+	1(+1)	250	2
	4/8	28,7	1722	GA15-10	1(+2)	MED35+	1(+1)	500	2
	4/8	34,4	2064	GA18-10	1(+2)	MED35+	1(+1)	500	2
	4/8	40,9	2454	GA22-10	1(+2)	MED50+	1(+1)	500	2
	4/8	49,2	2952	GA15-10	2(+2)	MED50+	1(+1)	500	2
	4/8	56,4	3384	GA15-10	2(+2)	MED70+	1(+1)	500	2
	4/8	78,8	4728	GA22-10	2(+2)	MED80+	1(+1)	500	2
	4/8	80,6	4836	GA22-10	2(+2)	MED100+	1(+1)	500	2
	4/8	140,9	8454	GA18-10	4(+2)	MED145+	1(+1)	500	2
uAIR-GF	4 / 11	7,1	426	GA5-13	1(+2)	MED7+	1(+1)	250	2
4 / 11 bar	4 / 11	11,7	702	GA7-13	1(+2)	MED13+	1(+1)	250	2
	4 / 11	15,7	942	GA11-13	1(+2)	MED13+	1(+1)	250	2
	4 / 11	25,6	1536	GA15-13	1(+2)	MED25+	1(+1)	250	2
	4 / 11	29,3	1758	GA18-13	1(+2)	MED25+	1(+1)	500	2
	4 / 11	30,9	1854	GA18-13	1(+2)	MED35+	1(+1)	500	2
	4 / 11	38,7	2322	GA22-10	1(+2)	MED35+	1(+1)	500	2
	4 / 11	41	2460	GA15-10	2(+2)	MED35+	1(+1)	250	2
	4 / 11	50,7	3042	GA15-10	2(+2)	MED50+	1(+1)	250	2
	4 / 11	77,4	4644	GA22-10	2(+2)	MED70+	1(+1)	500	2
	4 / 11	81,9	4914	GA18-13	3(+2)	MED70+	1(+1)	500	2
	4 / 11	116	6960	GA22-10	3(+2)	MED100+	1(+1)	500	2
	4 / 11	152,4	9144	GA22-10	4(+2)	MED145+	1(+1)	500	2

Flow mention for 50Hz plant variant.

Other configurations can be created with the Medical Calculation Tool. It is available on the web site: http://www.atlascopco.com/Medical.

mVAC Medical vacuum systems

Atlas Copco's mVAC Medical Vacuum Systems consist of 2 to 6 air-cooled, oil-lubricated rotary vane type vacuum pumps and a central controller with an intelligent graphical user interface. They provide a highly reliable medical vacuum (suction) for a variety of applications, mainly in operating theaters and intensive care, emergency and respirology units. The mVAC system offers (multiple) backup supply in case of failure of individual functional components.

CUSTOMER BENEFITS

• **Solid reliability** – The carbon composite material of our mVAC pumps will not break down or wear out like laminated blades. Even if the central controller should fail, every pump still has its own controller.

• **Highly connectable** – Up to six vacuum pumps can be connected in one mVAC system to ensure that even a large hospital always has a

reliable vacuum to meet all its needs. Furthermore, using AIRConnect[™] Visualization you can connect to extensive monitoring and status information to get the most out of your mVAC system.

• Energy-efficient – The mVAC incorporates a multi-pump arrangement to better match the flow demand. In this arrangement, the advanced Elektronikon® Graphic controller maximizes energy efficiency by controlling the individual vacuum pumps and regulating the overall vacuum. Uniform wear is ensured at all times.

• **Cost-effective** – Our unique Elektronikon® control system gives you the means to effectively manage and optimize your mVAC system. Device status is monitored in real time, required services are delivered rapidly, breakdowns can be prevented and downtime shortened. In short, it provides all you need to keep operational costs to a minimum.

• **Easy installation** – All interconnection piping and copper connections are supplied as an integral part of the mVAC system. This 'plug and play' approach makes installation even easier.



Technical specifications

mVAC 250-8000

HTM 2022 - 50	HTM 2022 - 50 Hz												
MODEL TYPE	System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C	System flow (referred to suction pressure)	Number of pumps	Pump power	Dimensions* (filters included)	Weight** (filters included)	Number of vessels	Total vessel capacity					
	l/min	m³/h		kW	LxWxH (mm)	Kg		L					
mVAC-250-DH	250	40	2	1.1	2040x980x1650	540	1	500					
mVAC-500-TH	500	79	3	1.1	2300x980x1650	650	1	500					
mVAC-660-TH	660	105	3	1.5	2400x980x1900	800	1	1000					
mVAC-1000-TH	1000	159	3	2.2	2400x980x1900	860	1	1000					
mVAC-1500-Q	1500	238	4	2.2	1830x980x1700	750	1	1500					
mVAC-2560-T	2560	406	3	5.5	2600x1200x1600	1365	2	3000					
mVAC-3840-0	3840	609	4	5.5	2600x1200x1990	1700	2	4000					
mVAC-4950-Q	4950	786	4	7.5	3400x1250x1700	1800	3	6000					
mVAC-6000-P	6000	952	5	7.5	4100x1250x1700	2050	3	6000					
mVAC-6600-P	6600	1047	5	7.5	4100x1250x1700	2050	4	8000					
mVAC-8000-H	8000	1270	6	7.5	4100x1250x1990	2360	4	8000					

mVAC 300-9200

HTM 2022 - 60 H	HTM 2022 - 60 Hz													
MODEL TYPE	System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C	System flow (referred to suction pressure)	Number of pumps	Pump power	Dimensions* (filters included)	Weight** (filters included)	Number of vessels	Total vessel capacity						
	l/min	m³/h		kW	LxWxH (mm)	Kg		L						
mVAC-300-DH	300	48	2	1.5	2040x980x1650	540	1	500						
mVAC-500-TH	500	79	3	1.5	2300x980x1650	650	1	500						
mVAC-800-TH	800	127	3	2.2	2400x980x1900	800	1	1000						
mVAC-1200-T	1200	190	3	3.0	1910x980x1700	610	1	1500						
mVAC-1860-Q	1860	295	4	3.0	2200x1200x1700	1050	1	2000						
mVAC-3000-T	3000	476	3	7.5	2600x1200x1600	1365	2	3000						
mVAC-4500-Q	4500	714	4	7.5	3400x1250x1990	1825	3	4500						
mVAC-5850-0	5850	928	4	9.2	3400x1250x1990	1800	3	6000						
mVAC-7800-P	7800	1238	5	9.2	4100x1250x1990	2160	4	8000						
mVAC-9200-H	9200	1460	6	9.2	4100x1250x1990	2360	5	10000						

* When available, horizontal vessels are included. ** Packaging included, vertical vessels excluded.

Additional options

AirConnect™ Visualization and Notification package							
Customized software setting for different norms (HTM / ISO / AS)							
Oil level switch							
Synthetic oil							
Painted vessels							

mVAC 250-6600

HTM 02-01 / IS	0 7396-1	50 Hz						
MODEL TYPE	System FAA @ -600 mbar(e) referred to 0 bar(e), 20°C	System flow (referred to suction pressure)	Number of pumps	Pump power	Dimensions* (filters included)	Weight** (filters included)	Number of vessels	Total vessel capacity
	l/min	m³/h	m³/h		kW LxWxH (mm)		Kg	
mVAC-250-TH	250	40	3	1.1	2300x980x1650	650	1	500
mVAC-330-TH	330	52	3	1.5	2300x980x1650	690	1	500
mVAC-500-TH	500	79	3	2.2	2400x980x1650	750	1	500
mVAC-660-Q	660	105	4	1.5	1910x980x1430	660	2	1000
mVAC-1000-Q	1000	159	4	2.2	1910x980x1700	740	2	1000
mVAC-1280-T	1280	203	3	5.5	2200x1100x1450	1025	3	1500
mVAC-2560-0	2560	406	4	5.5	2600x1200x1700	1625	2	3000
mVAC-3300-Q	3300	524	4	7.5	2600x1200x1700	1625	2	4000
mVAC-3840-P	3840	609	5	5.5	3300x1200x1990	1950	2	4000
mVAC-4950-P	4950	786	5	7.5	4100x1250x1700	2050	3	6000
mVAC-6000-H	6000	952	6	7.5	4100x1250x1700	2250	3	6000
mVAC-6600-H	6600	1047	6	7.5	4100x1250x1700	2250	4	8000

mVAC 300-7800

HTM 02-01 / ISO 7396-160 Hz										
MODEL TYPE	System FAA @ System flow -600 mbar(e) (referred to referred to suction 0 bar(e), 20°C pressure)		Number of pumps	Pump power	Dimensions* (filters included)	Weight** (filters included)	Number of vessels	Total vessel capacity		
	l/min	m³/h		kW LxWxH (mm)		Kg		L		
mVAC-300-TH	300	48	3	1.5	2300x980x1650	650	1	500		
mVAC-400-TH	400	63	3	2.2	2300x980x1650	690	1	500		
mVAC-620-T	620	98	3	3.0	1910x980x1430	750	2	1000		
mVAC-800-Q	800	127	4	2.2	1910x980x1700	660	2	1000		
mVAC-1200-Q	1200	190	4	3	1910x980x1430	740	2	2000		
mVAC-1500-T	1500	238	3	7.5	2200x1100x1450	1025	2	2000		
mVAC-3000-Q	3000	476	4	7.5	2600x1200x1700	1640	2	3000		
mVAC-3900-Q	3900	619	4	9.2	2600x1200x1990	1700	2	4000		
mVAC-4500-P	4500	714	5	7.5	4100x1250x1990	2075	3	4500		
mVAC-5850-P	5850	928	5	9.2	4100x1250x1700	2050	3	6000		
mVAC-7800-H	7800	1238	6	9.2	4100x1250x1990	2360	4	8000		

* When available, horizontal vessels are included. ** Packaging included, vertical vessels excluded.



mVAC-500-TH



mVAC-1280-T



mVAC-6000-H

Oxyplant Medical oxygen plant

Medical oxygen is an irreplaceable requirement for many basic medical procedures and treatments, and an invaluable adjunct to many other treatments. It is one of the drugs medical facilities cannot be without.

Cylinder Oxygen is bulky, which makes transportation difficult and even dangerous. Oxygen in liquid form is both voluminous and has very limited storage life. A solution of these inconveniences is to produce oxygen on site using Atlas Copco's new Medical Oxygen Plant (Oxyplant). A key element of Oxyplant is our PSA module which separates the oxygen from ambient air and allows the facility to have a stand alone oxygen production capability right on the facility site.

KEY FEATURES

• Typical Medical Oxygen Plant consisting of two independent oxygen generation lines, bank of cylinders and high pressure booster.

- Plant setup according to ISO10083 Figure A.5.
- Oxygen quality according to European Pharmacopeia Oxygen 93%.

CUSTOMER BENEFITS

• Modules are individually controlled and monitored for simplex or duplex PSA arrangements.

- Modules can be operated at ideal pressure for oxygen production without affecting the delivery pressure.
- Full electronic controls display output and all control parameters, allowing you control of each module.
- Noise is minimized and the safety of workers can be protected against nitrogen exhaust.
- Standard installed oxygen analyzers continuously monitor oxygen quality giving you peace of mind.
- Offering (multiple) backup supply in case of a failure in individual functional components
- One-stop-shop for medical solutions. We manufacture all main components ourselves(compressors, dryers, filters and PSA generators).
- Ambient temperature up to 45°



Туре	Capacity	Compres-	Refrige-	Air filter	Air	Oxygen	Buffer,	Oxygen filter sets (PDp & Sterile)		Booster	Filling
	[Nm³/h]	sor	rant dryer	sets	buffer Vessel	genera- tor	incl. pressure regulator				station
Oxyplant 4	3,4	GA5	FX6	17	150L	OGP4	150L	9	Type 1	2-stage, up to 3,2Nm³/h	4/6/10 outlets
Oxyplant 6	5,5	GA7	FX7	32	150L	OGP6	150L	9	Type 1	2-stage, up to 3,2Nm ³ /h	4/6/10 outlets
Oxyplant 8	7,2	GA11	FX9	32	280L	OGP8	280L	9	Type 1	3-stage, up to 7,2Nm³/h	4/6/10 outlets
Oxyplant 10	8,8	GA11+	FX10	44	500L	OGP10	500L	9	Type 1	3-stage, up to 8,8Nm³/h	4/6/10 outlets
Oxyplant 14	13,2	GA15+	FX11	60	500L	OGP14	500L	9	Type 1	3-stage, up to 13,2Nm³/h	4/6/10 outlets
Oxyplant 18	18	GA18+	FX12	60	500L	OGP18	500L	9	Type 1	4-stage, up to 18Nm³/h	4/6/10 outlets
Oxyplant 20	19	GA22+	FX15	120	1000L	OGP20	1000L	17	Type 2	4-stage, up to 19Nm³/h	4/6/10 outlets
Oxyplant 29	27,1	GA30+	FX16	120	1000L	OGP29	1000L	17	Type 2	4-stage, up to 27Nm³/h	4/6/10 outlets
Oxyplant 45	42	GA45+	FX18	150	2000L	OGP45	2000L	32	Type 2	4-stage, up to 27Nm ³ /h	4/6/10 outlets
Oxyplant 55	51	GA55+	FX19	175	2000L	OGP55	2000L	32	Type 2	4-stage, up to 27Nm³/h	4/6/10 outlets

Specifications:

Unit outlet oxygen purity 93%

4-5 bar(e) outlet pressure

• 400V 50Hz & 380V 60Hz

Set-up include:

• 2 compressors

• 2 refrigerant dryers

Oxygen Standards

Atlas Copco Medical Oxygen Plant is able to produce oxygen compliant with the European Pharmacopeia (EurPh) monograph for Oxygen 93 or the United States Pharmacopeia (USP) monograph for Oxygen 93. Both standards were created explicitly to permit the use of PSA produced oxygen.

• 2 filter sets (PD/DD/QD)

• 2 air buffer vessels

• 1 booster

• 1 filling station

• 2 oxygen generators,

• 2 oxygen buffer vessels

• 2 pressure regulator, PDP and sterile filter

Parameters	Eur Ph	IS010083	USP	Laboratory Assay of Oxyplant	
	Oxygen 93%		Oxygen 93%		
Oxygen	93.0% ±3	>90%	>90.0	90-95%	
			< 96.0%		
Carbon monoxide	5 ppm	5 ppm	0.00%	0,11 ppm	
Carbon dioxide	300 ppm	300 ppm	0.03%	0,82 ppm	
Water	67 ppm	67 ppm	N/S	3 ppm	

Compliance

Today's medical arena is more tightly regulated than ever. Atlas Copco's medical oxygen generators are manufactured according to Medical Device— Quality Management System ISO 13485:2003 and ISO 9001. It could be also certified as ISO 10083 compliant. Medical Equipment

Compressors for Railway, Marine and Ski Slope Applications

Custom Solutions from Atlas Copco – Used All Over the World

Atlas Copco compressors have an almost infinite number of potential applications. As well as being used in trade and industry, compressors from Atlas Copco are ideal for use on trains, trams, subways and ships, or can be employed as reliable and economical air compressors for snowmaking. Such applications call for compressors with a special degree of versatility and expertise.

... on Railways

Designed for the toughest environments: On locomotives, railcars and trams, they can brake, open and close doors and raise and lower the pantographs. They are totally reliable, even under the toughest conditions, and are specially designed and built to match customer requirements.

- GAR screw compressors with up to 37 kW rated motor power
- SFR scroll compressors with up to 6.1 kW rated motor power
- LFXR piston compressors with up to 1.5 kW rated motor power
- LFR/LTR/LGR oil-lubridcated and oilfree piston compressors with up to 9.4 kW rated motor power



Download a QR Reader and scan the code for more information on our railway offerings. http://www.atlascopco.com/railwayus



SFR
... at Sea

They are ideal for use as ships' starting air compressors and are available with many different certifications. From 2.2 to 315 kW rated motor power, with 30 bar working pressure and volume flows of 2 to 781 l/s. Atlas Copco also offers the right compressors for use in working air applications on ships.

- MAS GA screw compressors with up to 315 kW rated motor power
- LT piston compressors with up to 15 kW rated motor power
- SF Scroll compressors (up to 15kW)
- ZT- Oil-free tooth compressors (up to 45 kW)



GA 160 W



Download a QR Reader and scan the code for more information on our marine offerings. http://www.atlascopco.com/marineus

... on Ski Slopes

Set up as centralized or decentralized compressors, they supply compressed air for snow cannons, which turn water into snow. The compressors help create the right conditions on the slope and, naturally, are oil-free.

- LE piston compressors with up to 7.5 kW rated motor power
- LF piston compressors with up to 7.5 kW rated motor power



AIR AND GAS TREATMENT

Tears of joy because of the low power consumption! We don't just offer refrigerant and desiccant dryers tailored to your needs - our compressed air processing systems are actually designed and constructed so thoughtfully that they will reduce your utility bills in the coming years. Whether you work with a pressure dewpoint of 3° C or need air in which the residual moisture only condenses below -70° C.

Compressed air treatment

Do you already know which compressor you want, but you're just missing the appropriate processing systems? A dryer for example? On the following pages you'll find a wide selection to suit every requirement, partly adapted to our compressors, to make your whole system more efficient. This is particularly sensible if the refrigerant or desiccant dryer is directly integrated in the compressor casing. This saves you time and floor space, and you'll have less installation expenditure.

Intake air from the compressor always contains moisture. With the compression and subsequent cooling, the compressed air is always saturated to 100% with moisture. Anyone who sends compressed air through a pipe network needs to protect against corrosion in order to prevent machine failures or production waste.

As a result, each compressed air system includes atleast one dryer and/or other processing components, such as filters or condensate separators. Different drying technologies are available: refrigerant dryers for simple applications and desiccant dryers for high to extremely high standards.

Refrigerant dryers are very reliable and economical. They work with built-in refrigerant compressors, which cool the air via heat exchangers, separate the resulting condensate and produce dry air with a pressure dewpoint of 3°C, so your systems are reliably protected from corrosion.

For industries, in which – for example – products have to be supplied or dried with compressed air, desiccant dryers are recommended and may even be indispensable. The air is not just cooled, the moisture is actively withdrawn via a desiccant, the so-called adsorption material. As soon as the desiccant is saturated, no more moisture can be withdrawn and it must be regenerated.

In order to guarantee a continuous air supply, rather than interrupting your manufacturing processes, desiccant dryers work with two containers or atleast one container, which is separated into two sections. The air is dried in one, and the dessicant is regenerated in the other. Desiccant dryers are available with pressure dewpoints of -20°C, -40°C and even -70°C. This means the residual moisture of the processed air only condenses below the specified temperatures, such as, for example, below -70°C. This type of dry air is required in the production of electronic components, such as computer hard drives, etc.

Obviously, these applications have a higher energy requirement than simple applications, and, just like compressors, this also applies to dryers: The biggest cost factor in the lifecycle is power, not the initial investment. But whatever your requirements, and whether you choose a refrigerant or desiccant dryer, we can assure you that all of our compressed air processing systems are so well designed and so efficient, that your utility bills will be less of an issue in the coming years.



Water is a problem for your compressed air system. It can corrode and freeze compressed air pipes and tools, disturb your production process, and contaminate products. Thus, it can significantly increase maintenance costs and reduce productivity.

The drying process is the only way to remove almost all the moisture from the compressed air.



FX Refrigerant air dryers, 7-1236 l/s, 14-2516 cfm. Page 115 - 116



BD+

Blower purge desiccant air dryers, 100-3000 l/s, 212-6360 cfm Page 127 - 128



FD Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm. Page 117 - 121



MD

Heat of compression rotary drum dryers, 88-2500 l/s, 185-5297 cfm Page 129 - 130



CD Heatless desiccant air dryers, 360-1600 l/s, 763-3392 cfm. Page 122



XD

Heat-of-compression desiccant air dryers, 1400-7000 l/s, 2970-14840 cfm. Page 131 - 132



CD+ Heatless desiccant air dryers, 25-1400 l/s, 53-2968 cfm.





SD Membrane dryers Page 133 - 134

BD

Blower purge desiccant air dryers, 360-1600 l/s, 763-3392 cfm. Page 125 - 126



BAP / BAP+

Purification units for breathable air Page 135 - 136



NGP series

PSA nitrogen generators, capacity 1-300 l/s, flow 4-1100 Nm³/h,purity 95-99.999% Page 138 - 139



WSD 25-750 / WD 80 / EWD 50-1500 Water separators and drains

Page 147 - 148



NGM 1-7

Membrane nitrogen generators, capacity 1.4-140 l/s, flow 5-500 Nm³/h, purity 95-99% Page 140 - 141



QDT

Activated carbon tower, 20-310 l/s, 42-657 cfm Page 149 - 150



OGP series

PSA oxygen generators, capacity 0.6-56 I/s, flow 2-200 Nm³/h, purity 90-95% Page 142 - 143



OSC and OSD

Oil/water separator systems for the condensate treatment Page 151 - 152

DD+, DDp+, PD+, PDp+, OD+ filters (Standard and high pressure)

Compressed air filters Page 144 - 146

FX Refrigerant air dryers, 7-1236 l/s, 14-2516 cfm.

Dry, quality air is vital for long-term, troublefree operation of your processes. Atlas Copco's FX dryers protect your products and systems against damage or corrosion.They remove moisture from compressed air with a dew point as low as 3°C/37,4°F. Easy to install, simple to operate and reliable, they provide the dry air you need, allowing you to concentrate on your core business.

CUSTOMER BENEFITS

• **Reliability** – FX dryers offer a steady pressure dew point down to 3°F/37,4°F, with no freezing of condensed moisture, and no chance of moisture entering the compressed air system. They are constructed from generously sized, quality components. A simple and proven design is backed up by an effective control system (hot gas bypass) to ensure reliable performance.

• **Reduced energy costs** – Designed to ensure a low pressure drop, the FX dryer gives you dry air at low cost.

• **Easy installation** – Thanks to a plug and play concept, installation of your FX dryer could not be easier. You only need a single electrical connection. All units are pre-commissioned and self-regulating.

• Low maintenance – Long service intervals, few component replacements and an ergonomic design for fast access to key components combine to reduce the need for maintenance to an absolute minimum.





Substantial cost savings

- Increased reliability and service life of tools and machines.
- Fewer leaks in the piping, resulting in lower energy consumption.
- Fewer repairs to tools, machines and piping.
- Few inconvenient machine breakdowns and interruptions.



FX 1–21 Refrigeration Dryer

Туре Maximum Volume flow¹⁾ Pressure Pressure Power con- Refrigerant Inlet/outlet Approx. Dimensions working loss dewpoint sumption connections weight $\mathsf{L}\times\mathsf{W}\times\mathsf{H}$ pressure bar l/s m³/min mbar approx.°C kW kg mm FX – Refrigerant dryer air-cooled FX 1 16 6 0.36 3 0.13 R 134 a 19 150 G 3/4" $350 \times 500 \times 484$ FX 2 16 10 0.60 250 3 0.16 R 134 a G 3/4" 19 $350 \times 500 \times 484$ FX 3 16 14 0.84 250 3 0.19 R 134 a G 3/4" 20 $350 \times 500 \times 484$ FX 4 16 20 1.20 250 3 0.27 R 134 a G 3/4" 25 $350 \times 500 \times 484$ FX 5 16 30 1.80 300 3 0.28 R 134 a G 3/4" 27 $350 \times 500 \times 484$ 3 FX 6 16 39 2.34 0.61 R 404 a G 1" 51 $370 \times 500 \times 804$ 320 FX 7 13 50 3.00 320 3 0.67 R 404 a G 1" 51 $370 \times 500 \times 804$ FX 8 13 60 3.60 3 0.79 R 404 a 61 460 × 560 × 829 180 G 1 1/2" FX 9 13 68 4.08 250 3 0.87 R 404 a G 1 1/2" 68 $460 \times 560 \times 829$ R 404 a FX 10 13 87 5.22 180 3 1.07 G 1 1/2" 73 $460 \times 560 \times 829$ 13 6.48 3 1.19 R 404 a FX 11 108 200 G 1 1/2" 90 $580 \times 560 \times 939$ 7.68 3 1.45 R 404 a FX 12 13 128 270 G 1 1/2" 90 $580 \times 560 \times 939$ FX 13 13 167 10.02 250 3 1.80 R 410 a G 2" 128 735 × 898 × 1002 FX 14 13 200 12.00 300 3 2.10 R 410 a G 2" 146 735 × 898 × 1002 R 410 a FX 15 13 250 15.00 300 3 2.65 G 2" 158 $735 \times 898 \times 1002$ FX 16 13 300 18.00 300 3 3.50 R 410 a G 2" 185 735 × 898 × 1002 FX 17 24.00 3 4.70 R 410 a 325 1020 × 1023 × 1560 13 400 250 G 3" FX 18 13 500 30.00 300 3 5.30 R 410 a G 3" 335 1020 × 1023 × 1560 FX 19 3 13 583 34.98 350 6.40 R 410 a G 3" 350 1020 × 1023 × 1560 13 R 410 a FX 20 833 49.98 300 3 8.40 G 3" 550 $1020\times 2099\times 1560$ FX 21 13 1166 69.96 3 11.80 R 410 a DN 125 250 600 1020 × 2099 × 1560

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

FD Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm.

The compressed air you use must be clean and dry. Moisture can cause corrosion in pipe work, premature failure of pneumatic equipment, or product spoilage. Based on direct expansion technology with cycling, non-cycling and Variable Speed variants, Atlas Copco's FD dryers remove moisture from compressed air with a dewpoint as low as +3°C/+37.4°F. They are highly energy-efficient, easy to install, and among the most environmentally friendly and quietest in their class. Most importantly, they deliver dry air to protect your air system and finished products.

CUSTOMER BENEFITS

• **High reliability** – Atlas Copco's FD refrigerant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as +3°C/+37.4°F. Separate components undergo severe endurance tests while the unique design of the heat exchanger significantly improves dryer lifetime. Advanced control functions ensure dry air at all conditions and prevent freezing at low loads.

• **Maximum energy savings** – Atlas Copco's refrigerant dryers incorporate energy-saving features that cut your carbon footprint. Incorporating unique heat exchanger technology and Saver Cycle Control, the FD ensures a low pressure drop of typically below 0.2 bar/2.9 psi and minimal energy consumption. Integrated Variable Speed Drive (VSD) technology variants offer even further energy savings by automatically tuning the energy input to the precise demand. The FD offers an extremely low total cost of ownership.

• **Easy installation** – FD dryers have a small footprint thanks to an innovative all-in-one design. Delivered ready for use, installation is straightforward, minimizing costly production downtime. On some models, in- and outlet connections are positioned on top of the unit, enabling installation against a wall.

• Environmentally friendly – Enclosed in a sound suppression canopy to reduce noise levels, FD dryers stand out by being among the most environmentally friendly and quietest in their class. They fully comply with ISO 14001 standards and Montreal Protocol regulations, and use CFC-free refrigerants to prevent any damage to the earth's ozone layer. FD dryers have an ozone depletion potential of zero.



Reducing energy costs

The refrigerant dryers from Atlas Copco have different integrated energy-saving functions, which improve the CO_2 balance and reduce costs. Thanks to a unique heat exchange technology and saver-cycle control, the FD series provides a lower pressure drop of an average of under 0.2 bar at minimal energy requirement. The speed regulation (VSD, Variable Speed Drive) allows additional energy savings because the energy consumption is automatically tailored to the requirements. This results in low costs over the entire service life.







FD 120-285 und FD 610-1010

FD 5–2000 refrigeration dryer



Saver-Cycle control

To save energy, FD dryers from Atlas Copco adapt their working cycle to the actual load, so the ambient temperature and the pressure dewpoint are constantly monitored and compared. With lower heat input, the refrigerant compressor stops, significantly reducing the power consumption.

Туре	Maximum working pressure	Volume flow ¹⁾		Pressure loss	Pressure dewpoint	Power consumption	Refrigerant	Inlet/ outlet connections	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/ min	mbar	approx.°C	kW			kg	mm
FD – Refrigerant d	lryer, air-coo	led								
FD 5	16	6	0.36	70	3	0.20	R 134 a	G 3/4"	27	496 × 377 × 461
FD 10	16	10	0.60	110	3	0.20	R 134 a	G 3/4"	27	496 × 377 × 461
FD 15	16	15	0.90	120	3	0.33	R 134 a	G 3/4"	32	496 × 377 × 461
FD 20	16	20	1.20	120	3	0.41	R 134 a	G 3/4"	34	496 × 377 × 461
FD 25	16	25	1.50	170	3	0.41	R 134 a	G 3/4"	34	496 × 377 × 461
FD 30	16	30	1.80	250	3	0.41	R 134 a	G 3/4"	34	496 × 377 × 461
FD 40	16	40	2.40	200	3	0.48	R 134 a	G 1"	57	688 × 389 × 604
FD 50	16	50	3.00	200	3	0.69	R 134 a	G 1"	58	688 × 389 × 604
FD 60	13	60	3.60	220	3	0.63	R 134 a	G 1"	80	726 × 482 × 804
FD 70	13	70	4.20	220	3	0.87	R 134 a	G 1"	81	726 × 482 × 804
FD 95	13	95	5.70	220	3	1.18	R 134 a	G 1"	87	726 × 482 × 804
FD 120	14	120	7.20	110	3	1.00	R 410 a	G 1 1/2"	170	836 × 661 × 982
FD 150	14	150	9.00	150	3	1.00	R 410 a	G 1 1/2"	170	836 × 661 × 982
FD 185	14	185	11.10	220	3	1.40	R 410 a	G 2 1/2"	185	916 × 802 × 982
FD 220	14	220	13.20	120	3	1.70	R 410 a	G 2 1/2"	197	916 × 802 × 982
FD 245	14	245	14.70	180	3	1.90	R 410 a	G 2 1/2"	197	916 × 802 × 982
FD 285	14	285	17.10	220	3	2.10	R 410 a	G 2 1/2"	197	916 × 802 × 982
FD 310 – 40°C	14	310	18.60	230	3	2.80	R 410 a	G 3"	198	850 × 986 × 1190
FD 310 – 46°C	14	310	18.60	230	3	2.80	R 410 a	G 3"	200	850 × 986 × 1190
FD 310 – 50°C	14	310	18.60	230	3	2.90	R 410 a	G 3"	202	850 × 986 × 1190
FD 410 - 40°C	14	410	24.60	210	3	3.00	R 410 a	G 3"	220	850 × 986 × 1375
FD 410 - 46°C	14	410	24.60	210	3	4.60	R 410 a	G 3"	240	850 × 1250 × 1375
FD 410 - 50°C	14	410	24.60	210	3	4.80	R 410 a	G 3"	290	850 × 1525 × 1375
FD 510 - 40°C	14	510	30.60	200	3	4.50	R 410 a	G 3"	260	850 × 1250 × 1375
FD 510 – 46°C	14	510	30.60	200	3	6.40	R 410 a	G 3"	310	850 × 1525 × 1375
FD 510 – 50°C	14	510	30.60	200	3	6.90	R 410 a	G 3"	315	850 × 1525 × 1375
FD 610	14	610	36.60	170	3	4.80	R 410 a	DN 100	320	1040 × 1060 × 1580
FD 760	14	760	45.60	170	3	5.30	R 410 a	DN 100	380	1245 × 1060 × 1580
FD 870	14	870	52.20	150	3	6.60	R 410 a	DN 150	400	1245 × 1060 × 1580
FD 1010	14	1010	60.60	170	3	7.40	R 410 a	DN 150	460	1580 × 1060 × 1580
FD 1250	13	1250	75.00	240	3	8.30	R 404 a	DN 150	860	1350 × 1640 × 1880
FD 1400	13	1400	84.00	240	3	8.50	R 404 a	DN 200	940	1350 × 1640 × 1880
FD 1600	13	1600	96.00	130	3	13.6	R 404 a	DN 200	1280	1350 × 1640 × 1880
FD 2000	13	2000	120.00	220	3	20.00	R 404 a	DN 200	1345	1350 × 1640 × 1880

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

Туре	Maximum working pressure	Volum	e flow ¹⁾	Pressure loss	Pressure dewpoint	Power con- sumption	Refrigerant	Inlet/outlet connections	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/min	mbar	approx.°C	kW			kg	mm
FD – Refrigerant d	ryer, air-cool	ed, 20-bar ve	rsions							
FD 5-20	20	7.3	0.44	40	3	0.20	R 134 a	G 3/4"	27	496 × 377 × 461
FD 10-20	20	14.4	0.87	90	3	0.20	R 134 a	G 3/4"	27	496 × 377 × 461
FD 15-20	20	21.8	1.31	100	3	0.33	R 134 a	G 3/4"	32	496 × 377 × 461
FD 20-20	20	27.6	1.65	100	3	0.41	R 134 a	G 3/4"	34	496 × 377 × 461
FD 25-20	20	34.8	2.09	140	3	0.70	R 134 a	G 3/4"	34	496 × 377 × 461
FD 30-20	20	43.5	2.61	200	3	0.70	R 134 a	G 1"	34	496 × 377 × 461
FD 40-20	20	58.0	3.48	160	3	0.70	R 134 a	G 1"	57	$688 \times 389 \times 604$
FD 50-20	20	72.5	4.35	160	3	0.70	R 134 a	G 1"	58	688 × 389 × 604
FD – Refrigerant d	ryer, water-c	poled								
FD 310W	14	310	18.6	230	3	2.00	R 410 a	G 3"	180	850 × 986 × 1190
FD 410W	14	410	24.6	210	3	2.40	R 410 a	G 3"	240	850 × 1250 × 1375
FD 510W	14	510	30.6	200	3	4.10	R 410 a	G 3"	260	850 × 1250 × 1375
FD 610W	14	610	36.6	170	3	3.10	R 410 a	DN 100	350	1245 × 1060 × 1580
FD 760W	14	760	45.6	170	3	3.60	R 410 a	DN 100	360	1245 × 1060 × 1580
FD 870W	14	870	52.2	150	3	4.50	R 410 a	DN 150	370	1245 × 1060 × 1580
FD 1010W	14	1010	60.6	170	3	5.10	R 410 a	DN 150	380	1245 × 1060 × 1580
FD 1250W	13	1250	75.0	240	3	8.30	R 404 a	DN 150	860	1350 × 1640 × 1880
FD 1400W	13	1400	84.0	200	3	8.50	R 404 a	DN 200	940	1350 × 1640 × 1880
FD 1600W	13	1600	96.0	200	3	13.60	R 404 a	DN 200	1280	1350 × 1640 × 1880
FD 2000W	13	2000	120.0	250	3	20.00	R 404 a	DN 200	1345	1350 × 1640 × 1880

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

FD Refrigerant air dryers, 6-4000 l/s, 13-8480 cfm



Integrated speed regulation (VSD)

Some FD refrigerant dryers have a built-in VSD control, which adapts the energy consumption to the actual used compressed air, significantly reducing energy consumption. Compared to conventional dryers, this saves up to 70%. The compressor runs with variable speeds to maintain a stable dewpoint. The speed of the refrigerant compressor is adapted to the inlet conditions, so less energy is needed for lower loads.

FD 4000 W VSD



Functional diagram for the FD-VSD series

- 1 Liquid separator
- 2 Refrigerant compressor
- 3 Condenser
- 4 Refrigerant dryer/filter
- 5 Control device
- 6 Air/refrigerant heat exchanger
- 7 Water separator
- 8 Air heat exchanger
- 9 Outlet for dried air
- a Inlet for moist air
- b Elektronikon®
 - (control and regulating unit)

FD VSD

Refrigeration dryers - with speed control







FD 2000 VSD

Туре	Maximum working pressure	Volum	e flow ¹⁾	Pressure loss	Pressure dewpoint	Power consump- tion	Refrigerant	Inlet/outlet connections	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/min	mbar	approx.°C	kW			kg	mm
FD – VSD series -	- Refrigerant	dryer, air-co	oled							
FD 760 VSD	14	up to 760	up to 45.6	170	3	5.3	R 410 a	DN 100	380	1245 × 1060 × 1580
FD 870 VSD	14	up to 870	up to 52.2	150	3	5.8	R 410 a	DN 150	400	1245 × 1060 × 1580
FD 1010 VSD	14	up to 1010	up to 60.6	170	3	6.6	R 410 a	DN 150	460	1580 × 1060 × 1580
FD 1250 VSD	13	up to 1250	up to 75.0	240	3	10.1	R 404 a	DN 200	750	1300 × 1350 × 1880
FD 1400 VSD	13	up to 1400	up to 84.0	240	3	9.1	R 404 a	DN 200	820	1300 × 1350 × 1880
FD 1600 VSD	13	up to 1600	up to 96.0	130	3	13.3	R 404 a	DN 200	1110	2120 × 1350 × 1880
FD 2000 VSD	13	up to 2000	up to 120.0	220	3	19.5	R 404 a	DN 200	1155	2120 × 1350 × 1880
FD – VSD series -	- Refrigerant	dryer, water	-cooled							
FD 760 W VSD	14	up to 760	up to 45.6	90	3	3.3	R 410 a	DN 100	410	1580 × 1060 × 1580
FD 870 W VSD	14	up to 870	up to 52.2	120	3	4.2	R 410 a	DN 150	410	1580 × 1060 × 1580
FD 1010 W VSD	14	up to 1010	up to 60.6	170	3	5.6	R 410 a	DN 150	410	1580 × 1060 × 1580
FD 1250 W VSD	13	up to 1250	up to 75.0	240	3	9.9	R 404 a	DN 200	750	1300 × 1350 × 1880
FD 1400 W VSD	13	up to 1400	up to 84.0	240	3	8.5	R 404 a	DN 200	820	1300 × 1350 × 1880
FD 1600 W VSD	13	up to 1600	up to 96.0	130	3	9.3	R 404 a	DN 200	1110	2120 × 1350 × 1880
FD 2000 W VSD	13	up to 2000	up to 120.0	220	3	13.5	R 404 a	DN 200	1155	2120 × 1350 × 1880
FD 2400 W VSD	13	up to 2400	up to 144.0	230	3	18.3	R 404 a	DN 200	1180	2000 × 1350 × 1880
FD 4000 W VSD	13	up to 4000	up to 240.0	220	3	28.9	R 404 a	DN 250	2010	2200 × 2300 × 1910

¹⁾ Volume flow based on 20°C, 1 bar. Reference conditions: working pressure 7 bar, compressed air temperature 35°C, ambient temperature 25°C, relative humidity on entry 100%, pressure dewpoint 3°C.

CD Heatless desiccant air dryers, 360-1600 l/s, 763-3392 cfm.

Atlas Copco's CD heatless desiccant air dryers are designed for a long lifetime of reliable operation. Using only compressed air as a purge, they provide you with the clean, dry air you need to extend the life of your equipment and ensure the quality of your end product. They are available in a range of sizes with a pressure dewpoint as low as -40°C/-40°F, and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

• **Reliability** – Atlas Copco's CD desiccant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -40°C/-40°F.



CD 630



CD 360-1600



CD 1+-1400+

Dryer type	Inlet volume flow: 7		Pressure loss	Filt	ter sizes (recomm	ended)	Weight	Dimensions		
	bar [10	10 psig]	(without filter)	Pre-filter		Afterfilter		mm		
	l/s	m³/hr	bar	1 µm 0.01 µm 0.1 ppm 0.01 ppm		1 µm	kg	L	w	Н
Heatless desiccant air	r dryers, 360)-1600 l/s, 7	63-3392 cfm.							
CD 360	360	1296	0.19	DD280	PD280	DDp280	650	1173	1116	1854
CD 480	480	1728	0.14	DD390	PD390	DDp390	970	1776	988	2549
CD 630	630	2268	0.14	DD520	PD520	DDp520	1240	1884	843	2604
CD 970	970	3492	0.12	DD780	PD780	DDp780	2010	2359	1039	2643
CD 1260	1260	4536	0.12	DD1050	PD1050	DDp1050	2470	2472	1039	2636
CD 1600	1600	5760	0.11	DD1400	PD1400	DDp1400	3560	2693	1428	2576

• **Reduced energy costs** – Optimally sized pipes and valves ensure a limited pressure drop. Options are available to increase the efficiency and reduce the energy consumption of your CD dryer.

• **Space-saving** – The CD's all-in-one design leads to a small footprint, saving valuable space in your facility.

• Efficient control – The control system – fitted in an IP54 cubicle for easy cabling and safety – ensures proper operation of your CD dryer.

• Low maintenance – Delivered ready for use, installation of your CD dryer is straightforward, cutting costly production downtime. All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and high-quality valves results in three-year maintenance intervals.

CD+

Heatless desiccant air dryers, 25-1400 l/s, 53-2968 cfm.

Atlas Copco's CD+ heatless desiccant dryers protect your systems and processes. Their robust design ensures they operate with total reliability and deliver a constant, stable dewpoint in full load conditions and even during a temporary overload. The result is dry and clean compressed air for a broad range of industrial applications. Technological innovations ensure that this air is produced reliably and cost-effectively. Our CD+ dryers are available in a range of sizes with a guaranteed dewpoint down to -40°C/-40°F (optionally -70°C/-100°F), and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

• **High reliability** – Atlas Copco's CD+ desiccant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -70°C/-100°F. Up to 30% desiccant overfill and the long lifetime of the desiccant further enhance reliability.

• Maximum energy savings – CD+ dryers incorporate energy-saving features that cut your carbon footprint. A low pressure drop below 0.2 bar/2.9 psi drives down energy costs. Dewpoint sensing and control adapts the energy consumption to the real load of the dryer.

• **Easy installation** – Your CD+ dryer is delivered ready for use with silencers, sensors and the control unit already wired and connected.

 Advanced control and monitoring – The advanced Elektronikon® control and monitoring system takes continuous care of your CD+ dryer to ensure optimal efficiency.

• **Minimum maintenance** – All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and durable valves extends maintenance intervals beyond the standard three years.

• **Durability** – A proven, rugged design for the switching valves, the most important moving components in the dryer, significantly improves the lifetime of your CD+ dryer.







CD 25+

CD 185+

CD 850+



Heatless desiccant air dryers

Dry air from the outlet of the dryer container is released to the outside air pressure and guided through the saturated desiccant, where it takes up the adsorbed moisture.

After the desorption the blow-off valve is closed, and the container is put under pressure again.

Dryer type	Inlet volu	me flow: 7	Pressure loss (without filter)	Filt	er sizes (recomm	ended)	Weight	Dimensions		
	bar (10	l0 psig]	(without filter)	Pre	-filter	Afterfilter			mm	
	l/s	m³/hr	bar	1 µm 0.1 ppm	0.01 µm 0.01 ppm	1 µm	kg	L	w	н
Heatless desiccant a	ir dryers, 25	5-1400 I/s, 5	3-2968 cfm.							
CD 1+	1	3.6	0.20	DD3	PD3	integrated	7	106	172	540
CD 1.5+	1.5	5.4	0.20	DD3	PD3	integrated	8	106	172	590
CD 2+	2	7.2	0.20	DD3	PD3	integrated	9	106	172	720
CD 2.5+	2.5	9.0	0.20	DD3	PD3	integrated	10	106	172	835
CD 3+	3	10.8	0.20	DD3	PD3	integrated	11	106	172	855
CD 5+	5	18.0	0.20	DD3	PD3	integrated	19	149	295	640
CD 7+	7	25.2	0.20	DD3	PD3	integrated	22	149	295	725
CD 10+	10	36.0	0.20	DD3	PD3	integrated	25	149	295	875
CD 12+	12	43.2	0.20	DD3	PD3	integrated	29	149	295	1015
CD 17+	17	61.2	0.20	DD3	PD3	integrated	35	149	295	1270
CD 22+	22	79.2	0.35	DD3	PD3	integrated	44	149	295	1505
CD 25+	25	90	0.06	DD32	PD32	DDp32	50	550	201	1233
CD 30+	30	108	0.09	DD32	PD32	DDp32	50	550	201	1233
CD 35+	35	126	0.10	DD32	PD32	DDp32	60	550	201	1478
CD 50+	50	180	0.32	DD60	PD60	DDp60	80	550	201	1846
CD 60+	60	216	0.12	DD60	PD60	DDp60	100	550	364	1233
CD 70+	70	252	0.16	DD60	PD60	DDp60	120	550	364	1479
CD 80+	80	288	0.33	DD120	PD120	DDp120	160	550	364	1846
CD 100+	100	360	0.35	DD120	PD120	DDp120	160	550	364	1846
CD 145+	145	522	0.43	DD150	PD150	DDp150	240	550	526	1846
CD 110+	107	385	0.12	DD120	PD120	DDp120	340	950	728	1695
CD 150+	150	540	0.16	DD150	PD150	DDp150	415	1089	848	1731
CD 185+	185	666	0.20	DD175	PD175	DDp175	445	1089	848	1731
CD 250+	250	900	0.14	DD280	PD280	DDp280	600	1106	960	1816
CD 300+	300	1080	0.19	DD280	PD280	DDp280	650	1173	1116	1854
CD 330+	330	1188	0.10	DD390	PD390	DDp390	950	1088	1776	2537
CD 400+	400	1440	0.10	DD390	PD390	DDp390	1030	1088	1776	2537
CD 550+	550	1980	0.10	DD520	PD520	DDp520	1310	1091	1884	2592
CD 850+	850	3060	0.10	DD780	PD780	DDp780	2120	1259	2359	2655
CD 1100+	1100	3960	0.10	DD1050	PD1050	DDp1050	2600	1259	2472	2637
CD 1400+	1400	5040	0.11	DD1400	PD1400	DDp1400		1428	2693	2576

BD Blower purge desiccant air dryers, 360-1600 l/s, 763-3392 cfm.

Atlas Copco's BD blower purge desiccant air dryers are designed for a long lifetime of reliable operation. They use a combination of air from an external blower, heat and minimal compressed air, and incorporate unique, patented technological innovations and energy-saving options. BD dryers provide you with the clean, dry air you need to extend the life of your equipment and ensure the quality of your end product. They are available in a range of sizes with a pressure dewpoint as low as -40°C/-40°F, and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

• **Reliability** – Atlas Copco's BD desiccant dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -40°C/-40°F.

• **Reduced energy costs** – Optimally sized pipes and valves ensure a limited pressure drop. Options are available to increase the efficiency and reduce the energy consumption of your BD dryer.

• **Space-saving** – The BD's all-in-one design leads to a small footprint, saving valuable space in your facility.

• Efficient control – The control system – fitted in an IP54 cubicle for easy cabling and safety – ensures proper operation of your BD dryer.

• Low maintenance – Delivered ready for use, installation of your BD dryer is straightforward, cutting costly production downtime. All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and high-quality valves results in three-year maintenance intervals.



BD 360



BD 970

Electronic dewpoint control

When the dewpoint reaches a preset value, the dryer automatically switches between the towers. This extends the drying time and results in considerable power savings, instead of changing the tower functions periodically. The power savings can be as high as 70%. The dewpoint is continuously monitored and indicated on the dryer display.





Functional diagram for the BD desiccant dryer

Blower purge desiccant air dryers The blower sucks in ambient air and blows it across the external heating element. The heated air is then guided from top to bottom through the saturated desiccant and absorbs the adsorbed moisture.

Cooling

Purging: After heating, the hot desiccant is cooled in the container. For the cooling, dry compressed air is passed from the outlet of the adsorption container from top to bottom through the hot reactivated container, and thus released.

Dryer type Inlet volume flow: 7 bar		Average	Pressure loss (without filter)	Filter s	sizes (recom	nended)	Weight	Dimensions			
			power input	(without filter)	Pre-	filter	Afterfilter		mm		
	l/s	m³/hr	kW	bar	1 µm 0.1 ppm	0.01 µm 0.01 ppm	1 µm	kg	L	W	H
Blower purge	desiccant	air dryers									
BD 360	360	1296	8.4	0.16	DD280	PD280	DDp280	1160	1100	1028	1829
BD 480	480	1728	10.4	0.16	DD390	PD390	DDp390	1275	1764	1024	2558
BD 630	630	2268	14.8	0.16	DD520	PD520	DDp520	1560	1884	1024	2612
BD 970	970	3492	21.8	0.16	DD780	PD780	DDp780	2540	2359	1175	2702
BD 1260	1260	4536	27.7	0.16	DD1050	PD1050	DDp1050	3035	2472	1175	2681
BD 1600	1600	5760	35.3	0.11	DD1400	PD1400	DDp1400	4100	2720	2199	2548

BD+

Blower purge desiccant air dryers, 100-3000 l/s, 212-6360 cfm

Atlas Copco's BD+ blower purge desiccant air dryers are designed for outstanding industrial performance and a long lifetime of reliable operation. They eliminate moisture completely before it can cause any damage to your compressed air net or production equipment. BD+ dryers use a combination of air from an external blower, heat and minimal compressed air, and incorporate unique, patented technological innovations and energy-saving options. BD+ dryers are available in a range of sizes with a guaranteed dewpoint down to -40°C/-40°F (optionally -70°C/-100°F), and come in an IP54 protected cubicle.

CUSTOMER BENEFITS

• **High reliability** – BD+ dryers eliminate system failures, production downtime and costly repairs by removing moisture from compressed air with a pressure dewpoint as low as -70°C/-100°F. Up to 30% desiccant overfill and the long lifetime of the desiccant further enhance reliability.

• **Maximum energy savings** – BD+ dryers incorporate energy-saving features that cut your carbon footprint. A low pressure drop below 0.2 bar/2.9 psi drives down energy costs. Dewpoint sensing and control adapts the energy consumption to the real load of the dryer.

• **Easy installation** – Your BD+ dryer is delivered ready for use with heaters, sensors and the control unit already wired and connected.

• Advanced control and monitoring – The advanced Elektronikon® control and monitoring system gives clear indication of dryer status, operation cycle and alarms. It includes alarms for low inlet pressure, blower, heater and valve operation, plus limit switches, pressure and temperature sensors.

• **Minimum maintenance** – All internal components are easily accessible to facilitate maintenance. The use of high-grade desiccant and high-quality valves extends maintenance intervals beyond three years.

• **Durability** – A proven, rugged design for the switching valves and the blower, the most important moving components in the dryer, significantly improves the lifetime of your BD+ dryer.



BD 1100+

Dryer type Inlet volume flow: 7 bar		bar Average Pressure	Filter si	zes (recom	mended)	Weight Dimensions					
			power input	loss (without filter)	Pre-f	ilter	Afterfilter			mm	
	l/s	m³/hr	kW	bar	1 µm 0.1 ppm	0.01 µm 0.01 ppm	1 µm	kg	L	W	H
Purge air coolin	g										
BD 100+	100	360	3.0	0.20	DD120	PD120	DDp120	640	1250	770	1720
BD 150+	150	540	3.0	0.20	DD150	PD150	DDp150	680	1300	870	1770
BD 185+	185	666	5.0	0.20	DD175	PD175	DDp175	710	1300	870	1770
BD 250+	250	900	5.5	0.20	DD280	PD280	DDp280	775	1345	955	1816
BD 300+	300	1080	5.5	0.20	DD280	PD280	DDp280	820	1425	1010	1853
BD 330+	330	1188	9.3	0.12	DD390	PD390	DDp390	1190	1764	1024	2558
BD 400+	400	1440	10.2	0.12	DD390	PD390	DDp390	1300	1764	1024	2558
BD 550+	550	1980	12.0	0.12	DD520	PD520	DDp520	1620	1884	1024	2612
BD 850+	850	3060	17.1	0.12	DD780	PD780	DDp780	2600	2359	1175	2702
BD 1100+	1100	3960	24.2	0.12	DD1050	PD1050	DDp1050	3040	2472	1175	2681
BD 1400+	1400	5040	33.0	0.10	DD1400	PD1400	DDp1400	4100	2720	2199	2548
BD 1800+	1800	6480	39.0	0.16	DD1800	PD1800	DDp1800	4700	2793	2199	2548
BD 2200+	2200	7920	55.0	0.22	DD2100	PD2100	DDp2100	5600	2993	2199	2548
BD 3000+	3000	10800	69.0	0.18	DD3150	PD3150	DDp3150	7600	3350	2417	2893
Purge-free air c	ooling (Zero	Purge)									
BD 330+	330	1188	8.6	0.12	DD390	PD390	DDp390	1420	1764	1024	2558
BD 400+	400	1440	10.7	0.12	DD390	PD390	DDp390	1545	1764	1024	2558
BD 550+	550	1980	13.2	0.12	DD520	PD520	DDp520	1910	1884	1024	2612
BD 850+	850	3060	23.4	0.12	DD780	PD780	DDp780	2960	2359	1175	2702
BD 1100+	1100	3960	32.4	0.12	DD1050	PD1050	DDp1050	3490	2472	1175	2681
BD 1400+	1400	5040	37.0	0.10	DD1400	PD1400	DDp1400	4450	2720	2639	2548
BD 1800+	1800	6480	45.0	0.16	DD1800	PD1800	DDp1800	5050	2793	2663	2548
BD 2200+	2200	7920	62.0	0.22	DD2100	PD2100	DDp2100	5950	2993	2775	2548
BD 3000+	3000	10800	79.0	0.18	DD3150	PD3150	DDp3150	7950	3350	2923	2893

MD Heat of compression rotary drum dryers, 88-2500 l/s, 185-5297 cfm

For high-guality, dry air downstream from your oil-free screw and centrifugal compressors, Atlas Copco's MD rotary drum dryers meet your needs perfectly. Using heat of compression – which requires negligible energy input – they are the perfect solution for a wide range of applications requiring pressure dewpoints as low as -25°C/-13°F. MD dryers are also often selected for applications where refrigerated dryers are suitable (+3°C/37°F PDP) due to the significant energy savings they offer. You benefit from a reliable process, impeccable end products, and the lowest total cost of ownership. Compared to other desiccant dryers that can consume up to 15% of the compressed air, the MD dryer guarantees 100% flow capacity at the output.

CUSTOMER BENEFITS

• Maximum energy savings – The energy consumption of MD dryers is negligible: only 0.12 kW (water cooled version). MD dryers are characterized by no loss of compressed air, zero purge by design, low pressure drop and no pre- and after-filtration requirements. These factors contribute to additional energy savings and increased efficiency. A Variable Speed Drive (VSD) dryer version is available to match VSD compressors.

• Low maintenance – The combination of an easy to service vessel, minimal maintenance downtime and long service intervals reduces your maintenance time and costs.

• Environmentally friendly – MD dryers are totally oil-free and use no Freon or CFCs, and a minimal amount of desiccant (only 5-10% of conventional adsorption dryers). 95% of all components can be recycled, and the units have very low noise levels.

• **Small footprint** – The small footprint of MD dryers means they take up minimal space in your facility.



MD 2500 VSD

Туре	Compressor Type	max. Operating pressure	dewpoint ⁽¹⁾	input	weight approximately	Dimensions L × B × H
		bar	°C	kW	kg	mm
MD - desiccant drye	ers, air cooled					
MD 200	ZT 55-90	10,5	-30	1,04	460	852 × 1433 × 1347
MD 300	ZT 110-145	10,5	-30	1,04	500	852 × 1442 × 1545
MD 400	ZT 160-200	10,5	-30	1,04	500	852 × 1442 × 1545
MD 600	ZT 200-275	10,5	-30	1,34	950	1194 × 1893 × 1796
MD - adsorption dry	er, air-cooled and spe	ed control				
MD 200 VSD	ZT 75-90 VD	10,5	-25	1,04	460	852 × 1442 × 1545
MD 400 VSD	ZT 132-160 VSD	10,5	-25	1,04	500	852 × 1442 × 1545
MD 800 VSD	ZT 250-315 VSD	10,5	-25	1,34	950	1194 × 1893 × 1796
MD - adsorption, wa	iter cooled					
MD 200W	ZR 55-90	10,5	-30	0,12	410	819 × 990 × 1347
MD 300W	ZR 110-145	10,5	-30	0,12	440	819 × 997 × 1545
MD 400W	ZR 160-200	10,5	-30	0,12	440	819 × 997 × 1545
MD 600W	ZR 200-275	10,5	-30	0,12	900	1163 × 1345 × 1609
MD 1000W	ZR 300-425	10,5	-30	0,12	1000	1156 × 1369 × 2057
MD 1800W	ZR 450-750	10,5	-30	0,12	1500	1290 × 1716 × 2283
MD - adsorption, wa	ter-cooled and with s	speed control				
MD 200W VSD	ZR 75-90 VSD	10,5	-25	0,15	410	819 × 990 × 1347
MD 400W VSD	ZR 132-160 VSD	10,5	-25	0,15	440	819 × 997 × 1545
MD 800W VSD	ZR 250-315 VSD	10,5	-25	0,15	900	1163 × 1346 × 1796
MD 1100W VSD	ZR 400 VSD	10,5	-25	0,15	1000	1156 × 1369 × 2057
MD 1300W VSD	ZR 500 VSD	10,5	-25	0,15	1000	1156 × 1369 × 2057
MD 2100W VSD	ZR 700 VSD	10,5	-25	0,15	1500	1289 × 1721 × 2353
MD 2500W VSD	ZR 900 VSD	10,5	-25	0,15	1500	1289 × 1721 × 2353

(1) At full load and at reference conditions: working pressure 7 bar inlet pressure 1 bar, intake and coolant temperature 20 ° C, rel. Humidity of the intake 60%

XD

Heat-of-compression desiccant air dryers, 1400-7000 I/s, 2970-14840 cfm.

Atlas Copco's XD heat-of-compression desiccant dryers combine high drying performance with minimal energy use. The result is best-in-class air quality for the ZH centrifugal compressor series, Z screw compressors and other oilfree air compressors. They guarantee a stable pressure dew point down to -40°C/-40°F (optionally -70°C/-100°F) without temperature or dewpoint peaks.

CUSTOMER BENEFITS

Maximum energy savings – The XD's patented zero purge solution does not consume any compressed air, while the high-performance desiccant minimizes energy consumption during regeneration. The low pressure drop of all individual components results in an overall low pressure drop. Advanced controls further reduce your total energy bill.
Optimal uptime – XD dryers are renowned for their durability.

Coolers, process valves, heaters and strainer are all made from stainless steel; all piping is fully galvanized; and the cooler shells are internally coated. Corrosion resistance results in extended lifetime and minimum maintenance downtime.

• **High reliability** – The high-performance desiccant has a low sensitivity to aging and a high resistance to acid condensate, which translate into a long lifetime. All process stainless steel valves are standard equipped with reliable inductive limit switches.

• Easy installation and maintenance – The modular design, consisting of a flanged piping skid and instrumentation and two flanged vessels, allows easy installation on site, reducing the installation cost to a minimum and ensuring quick commissioning. All controls and switches are connected to the Elektronikon® controller, which arrives fully programmed on site to cut installation time and cost.

• **Low noise** – The patented zero purge dryers exclude all need for purge air. As there is no purge, noise levels are extremely low.



XD 1100 ZP



XD 4500 ZP

Туре	Working pressure	re Volume flow ¹⁾ After-he		After-heater	Pressure dew- point ¹⁾	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/min		°C	kg	mm
XD – Desiccant	dryer, water-cooled	– WITHOUT powe	r requirement/va	riants: P/ZP			
XD 1400 S	11	1400	84.0	without	-5 up to -25	4800	2988 × 3026 × 3306
XD 1800 S	11	1800	108.0	without	-5 up to -25	5000	3068 × 3126 × 3307
XD 2400 S	11	2400	144.0	without	—5 up to —25	7000	3529 × 3326 × 3374
XD 3000 S	11	3000	180.0	without	—5 up to —25	8200	3674 × 4000 × 3417
XD 3600 S	11	3600	130.0	without	—5 up to —25	10000	3963 × 4100 × 3444
XD 4000 S	11	4000	240.0	without	–5 up to –25	10400	4042 × 4200 × 3448
XD 4500 S	11	4500	270.0	without	–5 up to –25	10700	4163 × 4300 × 3460
XD 5000 S	11	5000	300.0	without	–5 up to –25	16600	4659 × 5012 × 3760
XD 6000 S	11	6000	360.0	without	–5 up to –25	17700	4859 × 5212 × 3755
XD 7000 S	11	7000	420.0	without	–5 up to –25	18300	4959 × 5312 × 3783
XD – Desiccant	dryer, water-cooled	– WITH guarantee	d pressure dew	point/variants: P/Z	P		
XD 1400 G	11	1400	84.0	with	up to –40	5160	2988 × 3026 × 3415
XD 1800 G	11	1800	108.0	with	up to —40	5360	3068 × 3126 × 3430
XD 2400 G	11	2400	144.0	with	up to –40	7390	3529 × 3326 × 3492
XD 3000 G	11	3000	180.0	with	up to –40	8630	3674 × 4000 × 3531
XD 3600 G	11	3600	130.0	with	up to –40	10400	3963 × 4100 × 3563
XD 4000 G	11	4000	240.0	with	up to –40	10800	4042 × 4200 × 3589
XD 4500 G	11	4500	270.0	with	up to –40	11100	4163 × 4300 × 3616
XD 5000 G	11	5000	300.0	with	up to40	17100	4659 × 5012 × 3911
XD 6000 G	11	6000	360.0	with	up to –40	18200	4859 × 5212 × 3915
XD 7000 G	11	7000	420.0	with	up to –40	18800	4959 × 5312 × 3940

Versions: P = PURGE cooling with compressed air loss/ZP = ZERO PURGE cooling without compressed air losses ¹¹ Volume flow based on reference conditions: working pressure 7 bar, compressed air inlet 120°C, relative humidity 10%, coolant temperature 26,7°C, version P

SD Membrane dryers

Atlas Copco's SD membrane dryers with pre-filters remove oil, particles and moisture from compressed air in the most demanding conditions. They ensure the lowest pressure drop and purge air loss for the highest possible efficiency – saving you time and money through your production process. From small spaces to environments with fluctuating ambient temperatures, SD dryers can perform in a wide variety of harsh and critical conditions. Two models are available, each with a range of performance, to offer you the exact air treatment you require.

CUSTOMER BENEFITS

• **Versatility** – SD dryers perform in all sorts of areas: small spaces, areas where flexible mounting is required, high vibration areas and in widely fluctuating temperatures.

• **Safety assurance** – SD dryers provide dry air in environments with strict safety or environmental requirements. These include low flow environments, areas without an electrical supply, explosion-proof facilities, noise-sensitive and corrosion-sensitive areas.

• **Clean and dry air for critical applications** – Because they are not powered by electricity, SD dryers function safely in environments that must be explosion-proof, such as laboratories. Thanks to their quiet operation, they can be used close to the workplace.

• **Optimal efficiency** – SD membrane dryers contain thousands of hollow fibers with an innovative inner coating. Compared to conventional membrane dryers, this unique coating increases the separation efficiency between water vapor and oxygen and nitrogen, giving an unprecedented low air leakage and the lowest purge air loss.

• Flexibility in choice – SD dryers are available in two models, each with a different Pressure Dew Point Suppression. This choice of performance ensures that, regardless of your production environment and demands, there is an SD dryer to meet your needs.

• **Energy savings** – Due to the straightforward design of the SD dryer, compressed air has no twists and turns to make inside the housing. This leads to minimal pressure drop and utmost efficiency throughout the drying process.



SUP - Menurane Dryer - pressure dew point 32 C													
Туре	max. working Pressure	Flow ¹⁾		Pressure dew point reduction	pressure drop	Pneumatic connection	supplied filter	Weight ²⁾ approxi- mately	Dimensions / L				
	bar	l/s	m³/min	ca. °C	mbar			kg	mm				
SD 1 P	7	3,0	0,16	32	0,10	G 3/8"	DD+PD 9	3,0	55 / 532				
SD 2 P	7	5,0	0,30	32	0,17	G 3/8"	DD+PD 9	3,0	55 / 532				
SD 3 P	7	9,0	0,54	32	0,17	G 1/2"	DD+PD 9	4,0	78 / 733				
SD 4 P	7	14,0	0,84	32	0,27	G 1/2"	DD+PD 17	4,2	78 / 733				
SD 5 P	7	19,0	1,14	32	0,17	G 1/2"	DD+PD 17	5,3	99 / 709				
SD 6 P	7	25,0	1,50	32	0,24	G 1/2"	DD+PD 32	5,3	99 / 709				
SD 7 P	7	35,0	2,10	32	0,18	G 1/2"	DD+PD 32	7,9	125 / 732				

1) Based on 25 ° C, 1 bar, 100% relative humidity. Reference conditions: Working pressure: 7, 10, 13 bar, temperature 35 ° C, relative humidity 100%. 2) weight (net) including DD / PD filters combination

SDP - Membrane Dryer - pressure dew point 32 ° C													
Туре	max. Working Pressure	Flo	w ¹⁾	Pressure dew point reduction	pressure drop	Pneumatic connection	supplied filter	Weight ²⁾ approxi- mately	Dimensions /L				
	bar	l/s	m³/min	ca. °C	mbar			kg	mm				
SD 1 P	10	4,0	0,24	32	0,10	G 3/8"	DD + PD 9	3,0	55 / 532				
SD 2 P	10	7,0	0,42	32	0,17	G 3/8"	DD + PD 9	3,0	55 / 532				
SD 3 P	10	12,0	0,72	32	0,17	G 1/2"	DD + PD 9	4,0	78 / 733				
SD 4 P	10	19,0	1,14	32	0,27	G 1/2"	DD + PD 17	4,2	78 / 733				
SD 5 P	10	25,0	1,50	32	0,17	G 1/2"	DD + PD 17	5,3	99 / 709				
SD 6 P	10	34,0	2,04	32	0,24	G 1/2"	DD + PD 32	5,3	99 / 709				
SD 7 P	10	44,0	2,64	32	0,20	G 1/2"	DD + PD 32	7,9	125 / 732				
SD 1 P	13	5,0	0,30	32	0,10	G 3/8"	DD + PD 9	3,0	55 / 532				
SD 2 P	13	8,5	0,51	32	0,17	G 3/8"	DD + PD 9	3,0	55 / 532				
SD 3 P	13	14,0	0,84	32	0,17	G 1/2"	DD + PD 9	4,0	78 / 733				
SD 4 P	13	22,0	1,32	32	0,27	G 1/2"	DD + PD 17	4,2	78 / 733				
SD 5 P	13	32,0	1,92	32	0,18	G 1/2"	DD + PD 32	5,7	99 / 709				
SD 6 P	13	42,0	2,52	32	0,25	G 1/2"	DD + PD 32	5,3	99 / 709				
SD 7 P	13	55,0	3,30	32	0,19	G 3/4"	DD + PD 44	8,9	125 / 732				

1) Based on 25 ° C, 1 bar, 100% relative humidity. Reference conditions: Working pressure: 7, 10, 13 bar, temperature 35 ° C, relative humidity 100%. 2) weight (net) including DD / PD filters combination

SD / N - Membra	SD / N - Membrane Dryer - the pressure dew point 55 ° C								
Туре	max. Working Pressure	Flo	W ¹⁾	Pressure dew point reduction	pressure drop	Pneumatic connection	supplied filter	Weight²) approxi- mately	Dimensions / L
	bar	l/s	m³/min	ca. °C	mbar			kg	mm
SD 1 N	7	1,5	0,09	55	0,08	G 3/8"	DD + PD 9	3,0	55 / 715
SD 2 N	7	3,5	0,21	55	0,25	G 3/8"	DD + PD 9	3,2	55 / 1020
SD 3 N	7	6,0	0,36	55	0,16	G 1/2"	DD + PD 9	4,7	78 / 1076
SD 4 N	7	9,0	0,54	55	0,25	G 1/2"	DD + PD 9	4,7	78 / 1076
SD 5 N	7	13,0	0,78	55	0,18	G 1/2"	DD + PD 17	6,1	99 / 1076
SD 6 N	7	17,0	1,02	55	0,25	G 1/2"	DD + PD 17	6,1	99 / 1076
SD 7 N	7	26,0	1,56	55	0,25	G 1/2"	DD + PD 32	9,7	125 / 1113
SD 1 N	10	2,0	0,12	55	0,08	G 3/8"	DD + PD 9	3,0	55 / 715
SD 2 N	10	4,5	0,27	55	0,24	G 3/8"	DD + PD 9	3,2	55 / 1020
SD 3 N	10	8,0	0,48	55	0,15	G 1/2"	DD + PD 9	4,7	78 / 1076
SD 4 N	10	12,0	0,72	55	0,24	G 1/2"	DD + PD 9	4,7	78 / 1076
SD 5 N	10	18,0	1,08	55	0,19	G 1/2"	DD + PD 17	6,1	99 / 1076
SD 6 N	10	22,0	1,32	55	0,24	G 1/2"	DD + PD 17	6,1	99 / 1076
SD 7 N	10	35,0	2,10	55	0,24	G 1/2"	DD + PD 32	9,7	125 / 1113
SD 1 N	13	2,5	0,15	55	0,08	G 3/8"	DD + PD 9	3,0	55 / 715
SD 2 N	13	5,5	0,33	55	0,24	G 3/8"	DD + PD 9	3,2	55 / 1020
SD 3 N	13	10,0	0,60	55	0,15	G 1/2"	DD + PD 9	4,7	78 / 1076
SD 4 N	13	15,0	0,90	55	0,24	G 1/2"	DD + PD 9	4,7	78 / 1076
SD 5 N	13	23,0	1,38	55	0,19	G 1/2"	DD + PD 17	6,1	99 / 1076
SD 6 N	13	28,0	1,68	55	0,25	G 1/2"	DD + PD 17	6,1	99 / 1076
SD 7 N	13	45,0	2,70	55	0,25	G 1/2"	DD + PD 32	9,7	125 / 1113

1) Based on 25 ° C, 1 bar, 100% relative humidity. Reference conditions: Working pressure: 7, 10, 13 bar, temperature 35 ° C, relative humidity 100%. 2) weight (net) including DD / PD filters combination

BAP / BAP+

Purification units for breathable air

Breathing air purifiers turn compressed air into certified breathing air.

High quality air is of vital importance to many industries but even more so in breathing air applications.

Atlas Copco BAP/BAP+ breathing air purifiers are designed to offer protection against a range of contaminants that may be present in a compressed air fed breathing air system. These include fumes, oil, vapors, gases, solid particles and microorganisms. Complying with International Breathing Air standards, the BAP/BAP+ breathing air purifier range assures a safe working environment in a wide range of applications.

CUSTOMER BENEFITS

• **Breathtaking air quality** – High quality air is of vital importance to many industries, but nowhere as literally as in breathing air applications. The purity of the compressed air for breathing air is crucial to assure a safe working environment in a wide range of applications like asbestos removal, tank cleaning, sand blasting and others.

For this reason, Atlas Copco has designed the BAP/BAP+ breathing air purifier range. The BAP/BAP+ takes air from any regular compressor and treats it to become ultra clean. It consists of a number of components, which together, after proper commissioning, produce air with a quality matching the Pharmacopoeia that will comply with the European Norm EN 12021 (Compressed air for breathing apparatus).

• Clean air in seven-step filtration – The BAP/BAP+ purification package for converting a compressed air source into breathing quality air. Your BAP/BAP+ package is independently certified to provide medical air in compliance with the European Pharmacopoeia.

The BAP/BAP+ has 7 stages of active purification:

- A water separator to remove liquid water
- A bulk aerosol filter eliminates oil and water
- A fine coalescing filter removes even smaller particles of oil and water
- A desiccant dryer takes out any remaining water and CO₂
- Activated carbon removes gaseous impurities
- A catalyst takes care of a CO oxidation
- A bacteria filter eliminates bacteria and fine particles. This bacteria filter is an Atlas Copco PDp filter, which has been externally tested and certified as a bacterial filter.

• More advantages of the BAP -

- Compact system, offering reliable breathing air
- Every BAP/BAP+ breathing air purifiers comes pre-assembled and tested to provide simple installation
- Complying with the European Norm EN 12021 (Compressed air for breathing apparatus)
- Challenge test to ensure the BAP meets international regulations



International compliance

Atlas Copco's Breathing Air Purifiers comply with OSHA Grade D, NFPA-99, CSA Z180.1-00, CGA G7.1-1997, EN12021, BS 4275, European Pharmacopoeia and other International Breathing Air Standards.

Technical specifications 7-145 BAP / BAP+

Purifier Type	Purifier Type Inlet pressure		Max. inlet flow			Puge Pressure drop		op
	bar(e)	psig	l/s	m³/h	cfm	%	dP, mbar	psi
BAP				·				
BAP7	7	102	7.0	25.2	14.8	19.0	510	7.4
	10	145	8.4	30.2	17.8	15.8	510	7.4
	13	188	9.4	33.8	19.9	14.1	510	7.4
BAP13	7	102	13.0	46.8	27.5	19.0	530	7.7
	10	145	15.6	56.2	33.1	15.8	530	7.7
	13	188	17.5	63.0	37.1	14.1	530	7.7
BAP25 / BAP25+	7	102	25.0	90.0	53.0	18.0	560	8.1
	10	145	30.0	108.0	63.6	15.0	560	8.1
	13	188	33.8	121.7	71.6	13.3	560	8.1
BAP35 / BAP35+	7	102	35.0	126.0	74.2	18.0	600	8.7
	10	145	42.0	151.2	89.0	15.0	600	8.7
	13	188	47.3	170.3	100.2	13.3	600	8.7
BAP50 / BAP50+	7	102	50.0	180.0	106.0	19.0	820	11.9
	10	145	60.0	216.0	127.1	15.8	820	11.9
	13	188	67.5	243.0	143.0	14.1	820	11.9
BAP70 / BAP+70+	7	102	70.0	252.0	148.3	18.0	660	9.6
	10	145	84.0	302.4	178.0	15.0	660	9.6
	13	188	94.5	340.2	200.2	13.3	660	9.6
BAP80 / BAP80+	7	102	80.0	288.0	169.5	18.0	700	10.2
	10	145	96.0	345.6	203.4	15.0	700	10.2
	13	188	108.0	388.8	228.9	13.3	700	10.2
BAP100 / BAP100+	7	102	100.0	360.0	211.9	19.0	820	11.9
	10	145	120.0	432.0	254.3	15.8	820	11.9
	13	188	135.0	486.0	286.1	14.1	820	11.9
BAP145 / BAP145+	7	102	145.0	522.0	307.3	19.0	800	11.6
	10	145	174.0	626.4	368.7	15.8	800	11.6
	13	188	195.8	704.9	414.9	14.1	800	11.6

	MED				MED+					
	Weight, kg	Length, mm	Width, mm	Height, mm	NTP con- nection	Weight, kg	Length, mm	Width, mm	Height, mm	NTP connection
BAP7 / BAP7+	184	950	650	885	1/2"	214	950	650	1851	1/2"
BAP13 / BAP13+	201	950	650	1075	1/2"	231	950	650	1851	1/2"
BAP25 / BAP25+	245	950	650	1300	1/2"	275	950	650	1851	1/2"
BAP35 / BAP35+	271	950	650	1545	1/2"	301	950	650	1851	1/2"
BAP50 / BAP50+	315	950	650	1915	1"	345	950	650	1858	1"
BAP70 / BAP+70+	446	1250	850	1545	1"	476	1250	850	1840	1"
BAP80 / BAP80+	494	1250	850	1915	1 1/2"	524	1250	850	1840	1"
BAP100 / BAP100+	502	1250	850	1915	1 1/2"	532	1250	850	1840	1"
BAP145 / BAP145+	620	1250	850	1915	1 1/2"	650	1250	850	1856	1"

Compressed air purification

Something else you should consider

Could the finest oil drops or moisture or the smallest dust grain affect your manufac-turing processes? Or even affect the quality of your products; in the worst case scenario, destroying your products or rendering them useless? Then you need to process the compressed air accordingly. Suitable dust filters, activated carbon absorbers, condensate drains, oil-water separators, and even the components of an efficient piping network - you'll find them all on the following pages.

Your compressed air system will include diverse processing components; particularly if you produce your compressed air with oil-lubricated or oil-injected compressors. But even if you are using oil-free compressors, you may need filters, a modern piping system or other accessories. The following pages present a variety of solutions for the most varied requirements.

Our dust, fine, ultra-fine and activated carbon filters eliminate even the smallest foreign particles or aerosols. You no longer need to worry about impurities when you pass your compressed air through these processing components, as we can effectively and safely separate out dust particles up to 0.01 μm in diameter and oil carry-over up to 0.003 mg/m³ of air.

You can use our oil-water separators to process your condensate from oil-injected compressors, because this condensate always structurally contains a proportion of oil, which you must remove before you can guide water into the public sewage network. You'll also save disposal costs. You should install oil-water separators when you order a compressor. To remove the condensate itself from the compressed air network, we provide reliable condensate drains – with electronic measuring of the level in the reservoir and automatic discharge.

You'll find a very special "separation technology" in our nitrogen generators: these units retain the oxygen from the (compressed) air using a carbon molecular sieve, producing nitrogen with purity levels of up to 99.999%. The machines pay for themselves quickly compared to the widespread way of working with hired bottle bundles.

At the end of this chapter you'll find information about our AlRnet[™]piping system; there is no easier, quicker or more flexible way of installing a piping network! As all the components are reusable, you'll save a lot of money if you only have to change the piping once for new operating conditions.

No more throwing out bent (steel) pipe pieces, as you can now easily plug together connectors, outlets and pipe pieces. The system permanently maintains the compressed air in your network, works without losses, and prevents leakages - reducing your energy costs.

NGP series

PSA nitrogen generators, capacity 1-300 l/s, flow 4-1100 Nm³/h purity 95-99.999%

Atlas Copco's NGP nitrogen generation systems provide a cost-effective, reliable and secure supply of nitrogen. The nitrogen generator's working principle is based on Pressure Swing Adsorption technology, which entails carbon molecular sieves that selectively separate oxygen from nitrogen. The NGP nitrogen generator is perfect for applications such as food and beverage, metal processing, electronics, etc.

CUSTOMER BENEFITS

• **Cost savings** – Our NGP systems are characterized by low operating expenses, operating expenses, and the absence of additional costs such as order processing, refills and delivery charges. Maintenance costs are kept to a minimum too.

• **Convenience** – NGP systems are continuously available, 24/7, to eliminate the risk of a production breakdown due to gas running out.

• **High purity** – We guarantee the nitrogen supply according to your needs, from 95 to 99.999% nitrogen purity.

• **Plug-and-play** – The NGP is delivered ready to use, you only need a supply of dry compressed air.



99.50%		Nitrogen capacity*		Air consumption			
	l/s	cfm	Nm³/h	l/s	cfm	Nm³/h	
NGP 4	1.1	2.4	4.0	4.0	8.5	14.40	
NGP 9	2.5	5.3	9.0	8.3	17.7	30.00	
NGP 11	3.1	6.5	11.0	10.0	21.2	36.00	
NGP 15	4.2	8.8	15.0	15.0	31.8	54.00	
NGP 21	5.8	12.4	21.0	20.0	42.4	72.00	
NGP 30	8.3	17.7	30.0	28.3	60.0	102.00	
NGP 40	11.1	23.5	40.0	39.2	83.0	141.00	
NGP 47	13.1	27.7	47.0	43.0	91.1	154.80	
NGP 62	17.2	36.5	62.0	52.5	111.2	189.00	
NGP 73	20.3	43.0	73.0	60.0	127.1	216.00	
NGP 92	25.6	54.1	92.0	90.0	190.7	324.00	
NGP 112	31.1	65.9	112.0	106.7	226.0	384.00	
NGP 185	51.4	108.9	185.0	165.0	349.6	594.00	
NGP 250	69.4	147.1	250.0	226.9	480.8	817.00	
NGP 420	116.7	247.2	420.0	396.7	840.5	1428.00	
NGP 550	151.4	320.8	545.0	510.0	1080.6	1836.00	
NGP 900	250.0	529.7	900.0	800.0	1695.0	2880.00	
NGP 1100	305.6	647.4	1100.0	1066.7	2260.1	3840.00	

* Performance +/- 5%. Reference conditions: Heterence conditions: Ambient temperature - 20°C Ambient pressure - 1013 mbar Unit inlet temperature - 20°C Inlet pressure - 7.5 bar(g) Unit outlet nitrogen purity - 99.50% Compressed air inlet quality - ISO8573-1 class 1-4-1

Outputs:

Outputs: Maximum compressed air inlet temperature - 45°C Maximum ambient temperature - 45°C Minimum compressed air inlet temperature - 5°C Minimum ambient temperature - 0°C Minimum compressed air inlet pressure - 4 bar(g) Maximum compressed air inlet pressure - 10 bar(g) Minimum nitrogen purity - 95% Maximum nitrogen purity - 99.999%















NGM 1-7

Membrane nitrogen generators, capacity 1.4-140 l/s, flow 5-500 Nm³/h, purity 95-99%

Atlas Copco's NGM membrane nitrogen generators provide a cost-effective, reliable and secure supply of nitrogen. The nitrogen generator's working principle is based on membrane air separation. The membrane allows nitrogen to pass and other gases (like oxygen, water vapor and CO_2) to permeate. The NGM series delivers flows from 5 to 500 Nm³/h and purities from 95% to 99%. These features make the NGM ideal for applications such as fire prevention, tire inflation, oil & gas, marine, packaging and more. • **Convenience** – NGM systems are continuously available, 24/7, to eliminate the risk of a production breakdown due to gas running out.

• **High purity** – We guarantee the nitrogen supply according to your needs, from 95% to 99% nitrogen purity.

• **Optimal flexibility** – The NGM is available in many sizes and thanks to its modular design, your NGM set-up can be adapted to your specific needs.

• Efficient control – To guarantee maximum uptime, continuous surveillance is a must. By properly monitoring your system with the NGM's electronic panel, you decrease downtime as well as save energy, reduce maintenance and increase production throughput.

CUSTOMER BENEFITS

• **Cost savings** – Our NGM systems are characterized by low operating expenses, and the absence of additional costs such as order processing, refills and delivery charges. Maintenance costs are kept to a minimum too.



Technical Specifications

95%		20°C		7 bar(g)			
NGM		Capacity		Air consumption			
	l/s	cfm	m³/h	l/s	cfm	m³/h	
1	3.2	6.7	11.5	8.2	17.4	29.5	
2	6.3	13.3	22.7	16.4	34.7	59.0	
3	11.1	23.5	39.9	28.9	61.2	104.0	
4	22.2	47.0	80.0	57.8	122.5	208.1	
5	33.3	70.6	119.9	86.7	183.7	312.1	
6	44.4	94,0	159.8	115.6	244.9	416.2	
7	55.6	117.8	200.2	144.4	305.9	519.8	

Reference conditions:

Ambient temperature: 20°C Ambient pressure: 1013 mbar Unit inlet temperature: 20°C Membrane working pressure: 7 bar(g) Unit outlet nitrogen purity: 95% Compressed air inlet quality: IS08573-1 class 1-4-1

Outputs (Min/Max):

Maximum compressed air inlet temperature: 50°C Maximum ambient temperature: 50°C Minimum compressed air inlet temperature: 5°C Minimum ambient temperature: 0°C Minimum compressed air inlet pressure: 4 bar(g) Maximum compressed air inlet pressure: 13 bar(g) Minimum nitrogen purity: 90% Maximum nitrogen purity: 99.5%

Correction Factors for Nitrogen Capacity

Membrane pressure (barg)	Correction factor
7	1.0
8	1.2
9	1.4
10	1.6
11	1.8
12	2.0
13	2.1

Inlet temperature (°C)		Purity (% N2)							
	95	96	97	98	99	99.5			
5	0.9	0.9	0.9	0.9	0.9	0.9			
10	0.9	0.9	0.9	0.9	0.9	0.9			
20	1.0	1.0	1.0	1.0	1.0	1.0			
30	1.0	1.0	1.0	1.0	1.0	1.0			
40	1.1	1.1	1.0	1.0	0.8	0.6			
50	1.2	1.1	1.1	1.0	0.8	0.6			



Sizing example: NGM 4: 95%, 11 bar, 40°C Capacity: 22.2 l/s x 1.8 x 1 = 40 l/s Air consumption: 57.8 l/s x 1.8 x 1.2 = 124.8 l/s



OGP series

PSA oxygen generators, capacity 0.6-56 l/s, flow 2-200 Nm³/h, purity 90-95%

Atlas Copco's OGP oxygen generation systems provide a cost-effective, reliable and secure supply of oxygen. The oxygen generator's working principle is based on Pressure Swing Adsorption technology, with zeolite pellets that selectively isolate oxygen molecules from other molecules in compressed air. The OGP oxygen generator is perfect for applications such as ozone production, waste water treatment, health care, glass industry, etc.

CUSTOMER BENEFITS

• **Cost savings** – Our OGP systems are characterized by low operating expenses and the absence of additional costs such as order processing, refills and delivery charges. Maintenance costs are kept to a minimum too.

• **Convenience** – OGP systems are continuously available, 24/7, to eliminate the risk of a production breakdown due to gas running out.

• **High purity** – We guarantee the oxygen supply according to your needs, from 90 to 95% oxygen purity.

• **Plug-and-play** – The OGP is delivered ready to use, you only need a supply of dry compressed air.



90.00%		Oxygen capacity*	ł	Air consumption			
	l/s	cfm	Nm³/h	l/s	cfm	Nm³/h	
OGP 2	0.6	1.3	2.0	6.7	14.1	22.20	
OGP 3	0.9	1.9	3.0	9.0	19.1	30.00	
OGP 4	1.1	2.4	3.7	10.8	22.9	36.00	
OGP 5	1.4	2.9	4.5	16.2	34.4	54.00	
OGP 6	2.0	4.1	6.5	21.6	45.8	72.00	
OGP 8	2.3	5.0	7.8	30.6	64.9	102.00	
0GP 10	2.9	6.0	9.5	30.6	64.9	102.00	
OGP 14	4.2	8.9	14.0	46.5	98.5	154.80	
0GP 18	5.5	11.6	18.2	56.8	120.2	189.00	
0GP 20	6.0	12.7	20.0	64.9	137.4	216.00	
0GP 23	6.9	14.6	23.0	75.7	160.3	252.00	
0GP 29	8.6	18.3	28.8	97.3	206.1	324.00	
0GP 35	10.4	21.9	34.5	108.1	229.0	360.00	
0GP 45	13.4	28.3	44.5	153.1	324.5	510.00	
0GP 55	16.5	35.0	55.0	187.4	397.0	624.00	
0GP 65	19.5	41.4	65.0	236.0	500.1	786.00	
0GP 84	25.2	53.4	84.0	290.1	614.6	966.00	
OGP 105	31.5	66.8	105.0	367.5	778.7	1224.00	
OGP 160	46.5	98.6	155.0	551.3	1168.1	1836.00	
OGP 200	60.1	127.2	200.0	663.0	1404.8	2208.00	

* Performance +/- 5%.

Reference conditions:

Ambient temperature Ambient pressure Unit inlet temperature Inlet pressure Unit outlet oxygen purity Compressed air inlet quality

20°C
1013 mbar
20°C
7.5 bar(g)
90%
ISO8573-1 class 1-4-1

Outputs

Maximum compressed air inlet temperature Maximum ambient temperature Minimum compressed air inlet temperature Minimum ambient temperature Minimum compressed air inlet pressure Maximum compressed air inlet pressure Minimum oxygen purity Maximum oxygen purity 45°C 45°C 5°C 0°C 4 bar(g) 10 bar(g) 90% 95%













DD+, DDp+, PD+, PDp+, QD+ filters

Compressed air filters

Atlas Copco's DD+, DDp+, PD+, PDp+ and QD+ filters efficiently reduce all types of contamination in your compressed air stream to protect your investment, equipment and processes. Our innovative filtration solutions are engineered to cost effectively provide the best quality air and meet today's increasing quality demands.

CUSTOMER BENEFITS

• **Reduced energy costs** – Designed for maximum contaminant removal, our filter range offers significant energy savings thanks to their optimal air flow path with low resistance. The filters' carefully engineered housing and cartridge ensure minimal pressure drops.

• **Solid reliability** – High performance stainless steel filter cores ensure durability of the cartridges. Protection paper avoids direct contact between the filter media and the stainless steel filter core.

• **High efficiency** – Top quality filter media in a deep-wrap layered composition ensure extremely high filtration efficiency, a low pressure drop and long cartridge lifetime. The flow path through housing and cartridge is optimized to reduce air turbulence and pressure drop.

• Low running costs – A unique and highly efficient head design reduces pressure drop and cuts your operational costs.


Air and Gas Treatment

Filter size	Inlet capa	city	Pressure		Connections	Dimension	IS					Weight			
						A		В		C		D			
	l/s	cfm	bar(e)	psig		mm	in	mm	in	mm	in	mm	in	kg	lbs
DD+, DDp+,	PD+, PDp+, (QD+													
10	10	21	7	102	3/8	90	3.54	61	2.40	268	10.55	75	2.95	1	2.2
20	20	42	7	102	1/2	90	3.54	61	2.40	268	10.55	75	2.95	1.1	2.4
35	35	74	7	102	1/2	90	3.54	61	2.40	323	12.72	75	2.95	1.3	2.9
50	50	106	7	102	3/4 & 1	110	4.33	98.5	3.88	374	14.72	75	2.95	1.6	4.2
70	70	148	7	102	1	110	4.33	98.5	3.88	414	16.3	75	2.95	2.1	4.6
130	130	275	7	102	1-1/2	140	5.51	105	4.13	520	20.47	100	3.94	4.2	9.3
170	170	360	7	102	1-1/2	140	5.51	105	4.13	603	23.74	100	3.94	4.5	9.9
210	210	445	7	102	1-1/2	140	5.51	105	4.13	603	23.74	100	3.94	4.6	10.1
310	310	657	7	102	2 & 2-1/2	179	7.05	121	4.76	689	27.13	150	5.91	6.9	15.2
425	425	901	7	102	3	210	8.27	128	5.04	791	31.14	200	7.87	11	24.2
550	550	1165	7	102	3	210	8.27	128	5.04	961	37.83	200	7.87	12.6	27.8
550F	520	1102	7	102	DN80	330	12.99	189	7.44	1292	50.87	728	29.66	71	156.5
780F	780	1653	7	102	DN100	460	18.11	228	8.98	1320	51.97	686	27.01	127	280.0
1050F	1050	2225	7	102	DN100	460	18.11	228	8.98	1320	51.97	686	27.01	128	282.0
1400F	1400	2967	7	102	DN150	550	21.65	287	11.30	1464	57.64	672	26.46	189	416.7
1800F	1800	3814	7	102	DN150	570	22.44	282	11.10	1467	57.76	681	26.81	210	463.0
2100F	2100	4450	7	102	DN150	620	24.41	291	11.46	1499	59.02	676	26.61	251	553.4
2700F	2700	5721	7	102	DN200	740	29.13	352	13.86	1634	64.33	692	27.24	328	723.1
3150F	3150	6675	7	102	DN200	740	29.13	352	13.86	1634	64.33	692	27.24	329	725.3
4800F	4800	10171	7	102	DN250	740	29.13	410	16.14	1662	65.43	800	31.5	507	1118.0
7200F	7200	15257	7	102	DN300	1000	39.37	485	19.09	1755	69.09	850	33.46	675	1488.0

Technical Specifications: + range 7 bar

	DD+	DDp+	PD+	PDp+	QD+
Dry pressure drop (mbar)	NA	85	NA	100	140
Wet pressure drop (mbar)	180	NA	215	NA	NA
Max oil carry-over (mg/m ³)	0.07	NA	0.008	NA	0.003
Count efficiency (% at MPPS)	NA	99.92	NA	99.98	NA

* inlet oil concentration 10 mg/m³ ** after DD+ PD+

Inlet pressure (bar)	1	2	3	4	5	6	7	8	10	12	14	16
Inlet pressure (psig)	15	29	44	58	72.5	87	102	116	145	174	203	232
Correction factor	0.38	0.53	0.65	0.75	0.83	0.92	1	1.06	1.2	1.31	1.41	1.5

Filter size	Inlet cap	bacity	Pressure		Connec- tions	Dimensi	ons					Weight	t		
						A		В		C		D			
	l/s	cfm	bar(e)	psig		mm	in	mm	in	mm	in	mm	in	kg	lbs
DD+, DDp	+, PD+, PD	p+, QD+													
10	10	21	7	102	3/8	90	3.54	61	2.40	268	10.55	75	2.95	1	2.2
20	20	42	7	102	1/2	90	3.54	61	2.40	268	10.55	75	2.95	1.1	2.4
35	35	74	7	102	1/2	90	3.54	61	2.40	323	12.72	75	2.95	1.3	2.9
50	50	106	7	102	3/4 & 1	110	4.33	98.5	3.88	374	14.72	75	2.95	1.6	4.2
70	70	148	7	102	1	110	4.33	98.5	3.88	414	16.3	75	2.95	2.1	4.6
130	130	275	7	102	1-1/2	140	5.51	105	4.13	520	20.47	100	3.94	4.2	9.3
170	170	360	7	102	1-1/2	140	5.51	105	4.13	603	23.74	100	3.94	4.5	9.9
210	210	445	7	102	1-1/2	140	5.51	105	4.13	603	23.74	100	3.94	4.6	10.1
310	310	657	7	102	2 & 2-1/2	179	7.05	121	4.76	689	27.13	150	5.91	6.9	15.2
425	425	901	7	102	3	210	8.27	128	5.04	791	31.14	200	7.87	11	24.2
550	550	1165	7	102	3	210	8.27	128	5.04	961	37.83	200	7.87	12.6	27.8
550F	520	1102	7	102	DN80	330	12.99	189	7.44	1292	50.87	728	29.66	71	156.5
780F	780	1653	7	102	DN100	460	18.11	228	8.98	1320	51.97	686	27.01	127	280.0
1050F	1050	2225	7	102	DN100	460	18.11	228	8.98	1320	51.97	686	27.01	128	282.0
1400F	1400	2967	7	102	DN150	550	21.65	287	11.30	1464	57.64	672	26.46	189	416.7
1800F	1800	3814	7	102	DN150	570	22.44	282	11.10	1467	57.76	681	26.81	210	463.0
2100F	2100	4450	7	102	DN150	620	24.41	291	11.46	1499	59.02	676	26.61	251	553.4
2700F	2700	5721	7	102	DN200	740	29.13	352	13.86	1634	64.33	692	27.24	328	723.1
3150F	3150	6675	7	102	DN200	740	29.13	352	13.86	1634	64.33	692	27.24	329	725.3
4800F	4800	10171	7	102	DN250	740	29.13	410	16.14	1662	65.43	800	31.5	507	1118.0
7200F	7200	15257	7	102	DN300	1000	39.37	485	19.09	1755	69.09	850	33.46	675	1488.0

Technical Specifications: + range 20 bar

	DD+	DDp+	PD+	PDp+	QD+
Dry pressure drop (mbar)	NA	85	NA	100	140
Wet pressure drop (mbar)	180	NA	215	NA	NA
Max oil carry-over (mg/m ³)	0.07	NA	0.008	NA	0.003
Count efficiency (% at MPPS)	NA	99.92	NA	99.98	NA

* inlet oil concentration 10 mg/m³ ** after DD+ PD+

Inlet pressure (bar)	1	2	3	4	5	6	7	8	10	12	14	16
Inlet pressure (psig)	15	29	44	58	72.5	87	102	116	145	174	203	232
Correction factor	0.38	0.53	0.65	0.75	0.83	0.92	1	1.06	1.2	1.31	1.41	1.5

WSD 25-750 / WD 80 / EWD 50-1500

Water separators and drains

Atlas Copco's WSD water separators are delivered as standard with our HD and TD after-coolers. They can also be installed in any point of your air net. The WD 80 drain valve provides completely automatic drainage of the condensate which collects at the bottom of the air receiver. The range of EWD electronically controlled condensate drains provides safe, dependable and economical condensate management.

CUSTOMER BENEFITS

• **Minimal maintenance** – Maintenance-free with no moving parts, the water separators have an automatic and manual drain.

• **High reliability** – The reliable automatic drain devices prevent condensed water from building up in the coolers.

• Energy savings – The intelligent drain function monitors condensate build-up with liquid level sensors and evacuates the condensate only when necessary, thus avoiding wastage of compressed air and giving considerable energy savings.

• Flexible installation – A wide range of different EWD drains is available for oil contaminated condensate and also may be provided with additional hard coating for use with oil-free and aggressive condensate.



WSD 25-750



TD 08-650

WD 80



HD 4-96

Туре	Maximum working pressure	Volum	e flow ¹⁾	Operating te	mperature	Compressed air connection	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/min	min°C	max°C		kg	mm
WSD – Water s	eparator with aut	omatic and manu	al drain					
WSD 25	20	25	1.5	1	70	G 1"	2.5	150 × 85 × 275
WSD 80	20	80	4.8	1	70	G 1 1/2"	3.5	185 × 130 × 432
WSD 250	20	250	15.0	1	70	G 2 1/2"	12.5	230 × 160 × 532
WSD 750	16	750	45.0	1	70	2)	15.0	298 × 194 × 627
WD – Condensa	ite drain							
WD 80	16	80	4.8	1	70	G 1/2"	2.7	132 × 132 × 182

¹⁾ Based on 20°C, 1 bar. Reference conditions: 7 bar working pressure, inlet temperature 30°C.

Туре	Maximum working pressure ¹⁾	Volume fl	low ²⁾	Pressure loss	Compressed air outlet temperature	Motor rated power	Compressed air connection	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/min	bar	°C	kW		kg	mm
TD – Aftercoo	ler, air-cooled								
TD 08	10.5/20	8	0.48	0.12	35	0.05	G 1/2"	6	270 × 130 × 225
TD 25	10.5/20	25	1.50	0.13	35	0.12	G 1"	19	460 × 391 × 658
TD 50	10.5/20	50	3.00	0.21	35	0.18	G 1"	23	560 × 437 × 735
TD 150	10.5/20	150	9.00	0.13	35	0.75	G 2 1/2"	53	740 × 479 × 1160
TD 300	10.5/20	300	18.00	0.14	35	0.75	G 2"	73	960 × 493 × 1280
TD 650	10.5/20	650	39.00	0.16	35	2.20	DN 100	185	1410 × 770 × 1525

¹⁾ 20 bar up to maximum compressed air inlet temperature 130°C, 10.5 bar up to maximum 200°C.
 ²⁾ Based on 20°C, 1 bar, with reference conditions: working pressure 7 bar, inlet temperature 160°C, ambient temperature 20°C.
 Note: DL = Compressed air. Voltage 400 V/50 Hz (TD 08 and 230 V). Other voltages available on request.

Туре	Maximum working pressure ¹⁾	Volume	flow²)	Pressure loss	Compressed air outlet temperature	Water connection	Compre conn	essed air lection	Approx. weight	Dimensions L × W × H
	bar	l/s	m³/min	bar	°C		Inlet	Outlet	kg	
HD – Afterce	ooler, water-c	ooled								
HD 4	20.0	67	4	150	27	G 3/8"	G 1 1/2"	G1 1/2"	55	344 × 170 × 1840
HD 8	20.0	133	8	200	27	G 1/2"	DN 65	DN 65	78	475 × 215 × 1973
HD 11	20.0	183	11	190	26	G 1/2"	DN 65	DN 65	85	483 × 230 × 1975
HD 16	10.5	267	16	160	28	G 3/4"	DN 100	DN 80	180	$645 \times 500 \times 2083$
HD 32	10.5	533	32	190	28	G 1"	DN 100	DN 80	210	$635 \times 500 \times 2083$
HD 48	10.5	800	48	190	28	G 1 1/4"	DN 150	2×DN 80	380	1032 × 490 × 2112
HD 64	10.5	1067	64	190	28	G 1 1/4"	DN 150	2×DN 80	410	1032 × 490 × 2112
HD 96	10.5	1600	96	190	28	G 1 1/2"	DN 175	3×DN 80	430	1412 × 490 × 2139

¹⁾ Maximum compressed air inlet temperature: 220°C.

²⁾ Based on 20°C, 1 bar, with reference conditions: water inlet temperature of 20°C, water heating of 15°C, working pressure 7 bar, inlet temperature 160°C. Note: DL = Compressed air

QDT Activated carbon tower, 20-310 l/s, 42-657 cfm

In the pharmaceutical, food & beverage, electronic and other industries where air purity is critical, you often need to remove residual oil vapors and odors from the compressed air supply. That is exactly what Atlas Copco's high-efficiency carbon filter does. The QDT activated carbon towers will, through the process of adsorption, reduce the residual oil content to lower than 0.003 mg/m³ at 35°C/95°F and 7 bar inlet pressure. The pressure drop is low and stays minimal during the lifetime of the filter. Only an activated carbon tower is able to provide Class 1 clean air in accordance with ISO 8573-1.

CUSTOMER BENEFITS

- Maximum oil vapor removal
- Pressure drop stays low
- Highest reliability
- Easy maintenance

	Nominal		Connections			Dimens	ion				
	NUIIIIIdi	сарасну	G or NPt	H Heig	ıht	L Len	gth	W Wi	dth	W	eight
Filter size	l/s	Cfm		mm	in	mm	in	mm	in	kg	lbs
QDT											
QDT 20	20	42	1/2	490	19	223	9	190	7	10	22
QDT 45	45	95	1	715	28	223	9	190	7	15	33
QDT 60	60	127	1	840	33	223	9	190	7	18	40
QDT 95	95	201	1	715	28	387	15	190	7	29	64
QDT 125	125	265	1 1/2	840	33	387	15	190	7	34	75
QDT 150	150	318	1 1/2	715	28	551	22	190	7	42	93
QDT 185	185	392	1 1/2	840	33	551	22	190	7	50	110
QDT 245	245	519	1 1/2	840	33	715	28	190	7	67	148
QDT 310	310	657	1 1/2	840	33	879	35	190	7	84	185

(1) At reference conditions: Inlet pressure 7 bar(g)/102 psig, inlet temperature 35°C/95°F.

ility Ince



For other compressed air inlet temperatures, please multiply the filter capacity by the following correction factor (Kt):

	<u></u>								
Inlet temperature °C	20	25	30	35	40	45	50	55	60
Inlet temperature °F	68	77	86	95	104	113	122	131	140
Correction factor	1.67	1.43	1.25	1	0.71	0.56	0.37	0.25	0.19

For other compressed air inlet pressures, please multiply the filter capacity by the following correction factor (Kp):

Inlet temperature °C	3	4	5	6	7	8	9	10	11	12	13
Inlet temperature °F	44	58	73	87	102	116	131	145	160	174	189
Correction factor	0.57	0.77	0.83	1	1	1	1	1.05	1.05	1.11	1.18

Example:

What is the capacity of a QDT 60, working at 8 bar(g)/116 psig with an inlet temperature of 40° C/104°F?

Kp = 1 Kt = 0.71

Actual capacity = $60 \times 1 \times 0.71 = 42.6$ l/s or 90.3 cfm





OSC and **OSD**

Oil/water separator systems for the condensate treatment

Atlas Copco's OSD and OSC condensate separators efficiently separate the oil from the water in condensates. The harmless water is drained away and the oil disposed of in an environmentally friendly manner. The OSD condensate treatment package is fully integrated into the compressor, reducing both installation costs and complexity. The OSC free standing units can separate all kinds of condensate from all compressor technologies, giving unparalleled performance and reliability for minimal maintenance.

CUSTOMER BENEFITS

- Benefits of the OSD integrated solution -
- High efficiency separation for worry-free condensate discharge.
- Performance independent of filter age.
- No installation required, saving time and money.
- Zero footprint, saving space and simplifying placing.

А

- Minimal maintenance.
- Reducing lifetime costs.
- Simple, fast and clean cartridge exchange.
- Benefits of the OSD free-standing units -
- No oil collection bottle required, so no chance to ruin previously separated condensate.
- Multiple oil condensate can be easily separated, Polyglycol condensate can be separated, Most condensate emulsions can be separated.





OSC 600

The function of the OSC oil-water separator

- 1 The condensate is fed through the muffler and expands in the expansion chamber.
- 2 The oil-water mixture then flows into cylinder A and seeps through the white oil filter. The filter only collects the oil and lets the water pass through.
- 3 The oil filter floats on the water and absorbs any remaining oil from the surface of the water.
 - The additional weight of the oil causes the filter to gradually sink as the saturation increases. This ensures that clean filter material always remains in contact with the surface of the water.
 - The indicator bar at the top of cylinder A indicates the status of the filter; the more contaminated the filter, the further the bar sinks.
 - The filter must be changed before it is fully immersed in the water.

- 4 Significantly cleaner condensate flows from cylinder A to cylinder B.
- 5 Cylinder B contains a bag of activated carbon pellets which absorb any residual oil from the condensate.
- 6 Clean, virtually oil-free condensate flows from cylinder B and can be easily and safely removed.

Туре	Volume flow ¹⁾ [Cold climate]		Volume flow ¹⁾ [Mild climate]		Volumo [Hot cl	e flow ¹⁾ limate]	Oil carry- over con- densate	Approx. weight	Dimensions L × W × H	
	l/s	m³/min	l/s	m³/min	l/s	m³/min	mg/l	kg	mm	
OSC – Oil-water separator (values for systems with compressors, air receivers, dryers and filters)										
OSC 35	65	3.9	35	2.1	17	1.0	< 20	4	$470\times165\times600$	
OSC 95	180	10.8	95	5.7	45	2.7	< 20	13	680 × 255 × 750	
OSC 145	270	16.2	145	8.7	70	4.2	< 20	15	680 × 255 × 750	
OSC 355	665	39.9	355	21.3	170	10.2	< 20	25	750 × 546 × 900	
OSC 600	1150	69.0	605	36.3	290	17.4	< 20	26	750 × 546 × 1030	
OSC 825	1550	93.0	825	49.5	400	24.0	< 20	28	945 × 650 × 1100	
OSC 1200	2220	133.2	1180	70.8	570	34.2	< 20	30	945 × 695 × 1100	
OSC 2400	4440	266.4	2360	141.6	1145	68.7	< 20	60	945 × 1185 × 1100	
	Volume flow ¹⁾ [Cold climate]									
Туре	Volume [Cold cl	flow ¹⁾ imate]	Volume [Mild cli	flow ¹⁾ [mate]	Volumo [Hot cl	e flow ¹⁾ limate]	Oil carry- over con- densate	Approx. weight	Dimensions L × W × H	
Туре	Volume [Cold cl I/s	flow ¹⁾ imate] m³/min	Volume [Mild cli I/s	flow ¹⁾ [mate] m³/min	Volumo [Hot cl I/s	e flow ¹⁾ limate] m³/min	Oil carry- over con- densate mg/l	Approx. weight kg	Dimensions L × W × H mm	
Type OSC – Oil-wa	Volume [Cold cl I/s ter separator (V	flow ¹⁾ imate] m³/min 'alues for syste	Volume [Mild cli l/s ems with comp	flow ¹⁾ [mate] m³/min ressors, air r	Volume [Hot cl I/s eceivers and fil	e flow ¹⁾ limate] m³/min lters)	Oil carry- over con- densate mg/l	Approx. weight kg	Dimensions L × W × H mm	
Type OSC – Oil-wa OSC 35	Volume [Cold cl I/s ter separator (V 105	flow ¹⁾ imate] m³/min <mark>alues for syst</mark> a 6.3	Volume [Mild cli I/s ems with comp 45	flow ¹⁾ imate] m³/min ressors, air r 2.7	Voluma [Hot cl I/s eceivers and fil 20	e flow ¹⁾ limate] m ³ /min ters) 1.2	Oil carry- over con- densate mg/l < 20	Approx. weight kg 4	Dimensions L × W × H mm 470 × 165 × 600	
Type OSC – Oil-wa OSC 35 OSC 95	Volume [Cold cl I/s ter separator (V 105 280	flow ¹⁾ imate] m ³ /min alues for syste 6.3 16.8	Volume (Mild cli I/s ems with comp 45 118	flow ¹⁾ imate] m³/min ressors, air r 2.7 7.1	Voluma [Hot cl I/s eceivers and fil 20 50	e flow ¹⁾ limate] m ³ /min ters) 1.2 3.0	Oil carry- over con- densate mg/l < 20 < 20	Approx. weight kg 4 13	Dimensions L × W × H mm 470 × 165 × 600 680 × 255 × 750	
Type OSC – Oil-wa OSC 35 OSC 95 OSC 145	Volume [Cold cl l/s ter separator (V 105 280 415	flow ¹⁾ imate] m ³ /min ialues for syste 6.3 16.8 24.9	Volume [Mild cli l/s ems with comp 45 118 175	flow ¹⁾ imate] ressors, air r 2.7 7.1 10.5	Volum (Hot cl I/s eceivers and fil 20 50 75	e flow ¹⁾ limate] m³/min ters) 1.2 3.0 4.5	Oil carry- over con- densate mg/l < 20 < 20 < 20	Approx. weight kg 4 13 15	Dimensions L × W × H mm 470 × 165 × 600 680 × 255 × 750 680 × 255 × 750	
Type OSC – Oil-wa OSC 35 OSC 95 OSC 145 OSC 355	Volume [Cold cl l/s ter separator (V 105 280 415 1035	flow ¹⁾ imate] m ³ /min alues for syste 6.3 16.8 24.9 62.1	Volume [Mild cli l/s ems with comp 45 118 175 435	flow ¹⁾ mate] m³/min ressors, air r 2.7 7.1 10.5 26.1	Volume [Hot cl //s eceivers and fil 20 50 75 190	e flow ¹⁾ limate] m³/min ters) 1.2 3.0 4.5 11.4	Oil carry- over con- densate mg/l < 20 < 20 < 20 < 20 < 20	Approx. weight kg 4 13 15 25	Dimensions L × W × H mm 470 × 165 × 600 680 × 255 × 750 680 × 255 × 750 750 × 546 × 900	
Type OSC – Oil-wa OSC 35 OSC 95 OSC 145 OSC 355 OSC 600	Volume [Cold cl l/s ter separator (V 105 280 415 1035 1800	flow ¹⁾ imate] alues for syste 6.3 16.8 24.9 62.1 108.0	Volume [Mild cli l/s ems with comp 45 118 175 435 760	flow ¹⁾ mate] m ³ /min ressors, air r 2.7 7.1 10.5 26.1 46.8	Volume [Hot cl]/s eceivers and fil 20 50 50 75 190 330	e flow ¹⁾ limate] m ³ /min ters) 1.2 3.0 4.5 11.4 19.8	Oil carry- over con- densate mg/l <	Approx. weight kg 4 13 15 25 26	Dimensions L × W × H mm 470 × 165 × 600 680 × 255 × 750 680 × 255 × 750 750 × 546 × 900 750 × 546 × 1030	
Type OSC – Oil-wa OSC 35 OSC 95 OSC 145 OSC 355 OSC 600 OSC 825	Volume [Cold cl l/s ter separator (V 105 280 415 1035 1800 2410	flow ¹⁾ imate] m ³ /min alues for syste 6.3 16.8 24.9 62.1 108.0 144.6	Volume [Mild cli l/s ems with comp 45 118 175 435 760 1020	flow ¹⁾ mate] m³/min ressors, air r 2.7 7.1 10.5 26.1 46.8 61.2	Volume [Hot cl //s eceivers and fil 20 50 75 190 330 440	e flow ¹⁾ limate] m³/min ters) 1.2 3.0 4.5 11.4 19.8 26.4	Oil carry- over con- densate mg/l < 20	Approx. weight kg 4 13 15 25 26 28	Dimensions L × W × H mm 470 × 165 × 600 680 × 255 × 750 680 × 255 × 750 750 × 546 × 900 750 × 546 × 1030 945 × 650 × 1100	
Type OSC – Oil-wa OSC 35 OSC 95 OSC 145 OSC 355 OSC 600 OSC 825 OSC 1200	Volume [Cold cl l/s ter separator (V 105 280 415 1035 1800 2410 3450	flow ¹⁾ imate] m³/min alues for syste 6.3 16.8 24.9 62.1 108.0 144.6 207.0	Volume [Mild cli 1/s ems with comp 45 118 175 435 760 1020 1455	flow ¹⁾ mate] m³/min ressors, air r 2.7 7.1 10.5 26.1 46.8 61.2 87.3	Volume [Hot cl 20 50 75 190 330 440 630	e flow ¹⁾ limate] m³/min ters) 1.2 3.0 4.5 11.4 19.8 26.4 37.8	Oil carry- over con- densate mg/l	Approx. weight kg 4 13 15 25 26 26 28 30	Dimensions L × W × H mm 470 × 165 × 600 680 × 255 × 750 680 × 255 × 750 750 × 546 × 900 750 × 546 × 1030 945 × 650 × 1100	

Туре	Volume	e flow ¹⁾	Oil content in effluent	Oil canister capacity	Approx. weight	Dimensions L × W × H	
	l/s m³/min		mg oil/l	mg oil/l L		mm	
OSD – Oil-water se	parator, integrated						
OSD 22	60	3.6	< 20	1	8	integrated in compressor	
OSD 90	250	15.0	< 20	2	9	integrated in compressor	
OSD 315	770	46.2	< 20	2	13	integrated in compressor	

¹⁾ With reference conditions: suction temperature 35°C, 70% relative humidity. In addition, depending on your compressor type and oil type. ²⁾ Dimensions: integrated in compressor (depending on type).

VACUUM PUMPS

For more than 20 years, Atlas Copco has been providing reliable vacuum solutions to the industry. We were the pioneers in bringing the oil-sealed screw technology to many vacuum customers. Years of innovation carried alongside our compressed air range, has led to extremely reliable and robust solutions.

Vacuum Pumps

Meeting an ever-growing need for vacuum

Vacuum is critical in a wide variety of applications – and the need for vacuum continues to grow, for example in the development of high-tech composite materials used in wind farms, aircraft manufacture etc. Atlas Copco has been developing state-of-the-art high-end vacuum solutions for many years. We have a market-leading status in the ongoing innovation of gas compression techniques such as screw, claw and scroll. Our vacuum specialists are constantly improving the performance of our products, targeting new application areas, and meeting new challenges.

The result is a wide portfolio of vacuum pumps that consistently help our customers become more efficient by lowering the cost of ownership, increasing sustainable productivity and enhancing final product quality.





Download a QR Reader and scan the code for more infomation on vacuums.

www.atlascopco.com/vacuum

GV 20-300

Oil-sealed rotary vane vacuum pumps, 20-365 m³/h, 12-215 cfm

Atlas Copco's GV 20-300 range is a series of robust an reliable oil-sealed rotary vane vacuum pumps, packed with innovative features.

Oil-sealed rotary vane vacuum pumps are ideal for critical applications like packaging and material handling in the general industry. With 8 models, offering pumping speeds of between 20 and 365 m³/h, you will definitely find the right model for your specific application.

Customer benefits

• **High reliability** – Thanks to a rugged design and optimal oil retention at all operating pressures. An inlet non-return valve protects the pump against counter rotation.

• **Plug and play installation** – Easy installation thanks to a compact, space-saving design.

• **Easy maintenance** – Wear is low thanks to optimally selected shaft speeds. Servicing can be done by the same engineer that services your compressed air equipment.

• Low noise and vibration levels throughout the pressure range



Technical specifications

PUMP TYPE	PUMP TYPE Pumping speed		Ultimate pressure (2)		Motor size		Water handling capability			
OIL-SEALED					1 ph	1 ph 3 ph		limit	Motor supply specification	
ROTARYVANE	m³/h	cfm	mbar (hPa)	torr	kW	kW	mbar	kg/h		
GV 20	20	10.5	2	1.50	0.75	Optional	35	0.5	1 - 230V 50Hz	
	21	12.3	2	1.50	0.9	Optional	35	0.5	1 - 230V 60Hz	
GV 25	25	14.7	0.5	0.38	0.75	0.75	40	0.7	1 - 230V 50Hz	
	29	17.0	0.5	0.38	0.9	0.9	40	0.7	1 - 230V 60Hz	
GV 40	40	23.5	0.5	0.38	1.1	1.1	30	0.9	3 - 175-260/300-450V 50Hz	
	48	28.3	0.5	0.38	1.35	1.35	30	0.9	3 - 200-300/346-520V 60Hz	
GV 60	60	35.3	0.5	0.38	-	1.5	40	1.8	3 - 175-260/300-450V 50Hz	
	75	44.1	0.5	0.38	-	1.8	40	1.8	3 - 200-300/346-520V 60Hz	
GV 100	105	61.8	0.5	0.38	-	2.2	30	2.2	IE2 motor 3-230/400V 50Hz (1)	
	125	73.6	0.5	0.38	-	3	30	2.2	3-IE2 motor 208-230V/265-460V 60Hz (1)	
GV 150	150	88.3	0.5	0.38	-	3.3	25	2.5	IE2 motor 3-230/400V 50Hz (1)	
	180	106.0	0.5	0.38	-	3.7	25	2.5	3-IE2 motor 208-230V/265-460V 60Hz (1)	
GV 200	205	120.7	0.5	0.38	-	5.5	25	3.5	IE2 motor 3-230/400V 50Hz (1)	
	245	144.2	0.5	0.38	-	6.6	25	3.5	3-IE2 motor 208-230V/265-460V 60Hz (1)	
GV 300	305	179.5	0.5	0.38	-	7.5	25	5	IE2 motor 3-230/400V 50Hz (1)	
	365 214.8		0.5	0.38	-	8.6	25	5	3-IE2 motor 208-230V/265-460V 60Hz (1)	

Smaller non-IE2 motors are available for continuous low pressure duties.
 With gas ballast valve open. All units achieve better than 0.5 mbar with gas ballast closed.

GV 630-4800

Oil-sealed rotary screw vacuum pumps, 557-5734 m³/h, 328-3377 cfm

Atlas Copco's oil-sealed rotary screw vacuum pumps bring reliable, efficient rough vacuum to the general industry. The GV 630-4800 combines a robust oil-sealed rotary screw technology with Atlas Copco's advanced screw element design.

Oil-sealed rotary screw vacuum pumps are particularly efficient in the operating pressure range between 1 mbar(a) to 500 mbar(a). That means the GV is ideal for applications such as printing, canning, plastics, electronics, packaging, bottling and similar industries.

Customer benefits

• **High reliability** – Oil-sealed technology offers wear-free, robust operation. Reliable, oversized motors and efficient oil-mist separation ensures durable operation.

• **Best-in-class efficiency** – With the highest performance output per kW input, the GV outperforms all other vacuum technologies in its pressure range. State-of-the-art coalescing filters reduce oil consumption, running temperatures and motor power consumption. Thanks to a modulating valve, the capacity of the pump can be matched exactly to the demand.

• **Plug and play installation** – A small footprint and space-saving canopy with lift-out panels offer easy installation and easy maintenance.

• Silent operation – The two screw elements rotate at slow speeds, so the GV runs at a sound level as low as 69 dB(A). This silent operation allows you to install the GV close to the point of use.



MODEL	Maximum shaft power				Pumping speed		Ultimate pressure		Inlet	Dimensions (L x W x H)	Weight	
50 Hz version	Air-cooled		Water-cooled		m³/h cfm		mbar (hPa)	torr	connector	mm	kg	lbs
MODEL 50 Hz	kW version	hp	kW	hp								
GV 630	10.1	13.5	9.8	13.1	557	328	0.7	0.5	DN100	2040 x 1280 x 1480	1070	2355
GV 1000	20.4	27.4	20.2	27.1	863	508	0.7	0.5	DN100	2040 x 1280 x 1480	1105	2430
GV 1200	30.8	41.3	30.5	40.9	1126	663	0.7	0.5	DN125	2040 x 1280 x 1480	1105	2430
GV 1600	41.4	55.5	39.8	53.4	1601	942	0.7	0.5	DN125	2560 x 1710 x 1970	1805	3970
GV 2500	58.2	78.1	56.5	75,8	2432	1432	0.7	0.5	DN200	2560 x 1710 x 1970	2860	6290
GV 4800	118.5	159.9	115.8	155.3	4778	2814	0.7	0.5	DN200	2990 x 1990 x 2000	3680	8100
MODEL 60 Hz version												
GV 630	11.7	15.7	11.3	15.2	668	393	0.7	0.5	DN100	2040 x 1280 x 1480	1080	2370
GV 1000	22.1	29.6	21.7	29.1	1036	610	0.7	0.5	DN100	2040 x 1280 x 1480	1115	2450
GV 1200	37.4	50.1	36.0	48.3	1351	796	0.7	0.5	DN125	2040 x 1280 x 1480	1130	2480
GV 1600	49.5	66.4	48.6	65.2	1921	1131	0.7	0.5	DN125	2560 x 1710 x 1970	1820	4000
GV 2500	69.1	92.7	67.5	90.5	2918	1719	0.7	0.5	DN200	2560 x 1710 x 1970	2885	6350
GV 4800	142.6	191.2	140.3	188.2	5734	3377	0.7	0.5	DN200	2990 x 1990 x 2000	3680	8100

Technical specifications GV 630-4800

Available accessories & options

		GV 630	GV 1000	GV 1200	GV 1600	GV 2500	GV 4800
	Liquid separators	0	0	0	0	0	0
	Inlet filters	~	~	✓	~	0	0
	Vacuum tank/receivers	0	0	0	0	0	0
	Check valves & pump isolation valves	0	0	0	0	0	0
	Vacuum gauges (various types & ranges)	0	0	0	0	0	0
Accessories	Multiple pump controllers	0	0	0	0	0	0
	Air-cooled	0	0	0	0	0	0
	Water-cooled	0	0	0	0	0	0
	Phase sequence protection	0	0	0	0	0	0
	Increased water handling capability	0	0	0	0	0	0
	Vacuum oil PG	~	~	~	~	~	~
	Vacuum oil PG plus for extended duty	0	0	0	0	0	0
Options	Food grade oil	0	0	0	0	0	0

✓: Standard O: Optional

TOTAL CUSTOMER CARE

Our organization and people are committed to the maximum operational availability and efficiency of your compressed air network.

Total customer care

Your bottom line, maximum availability of our equipment at minimum total operating cost, is the top priority for all of us at Atlas Copco. Our way of achieving that builds on interaction, on long-term relationships and involvement in your processes, needs and objectives. Total customer care is our goal at any level of service interaction with you; from standardized genuine parts over tailormade service plans to remote monitoring and optimization.

We want you to see Atlas Copco as a real performance partner that can contribute to the productivity of your processes. The best way of taking care of your interest is by taking the best care of your equipment.



SAVE ENERGY Page 161 - 163



MONITOR YOUR PRODUCTS Page 164



CUSTOMER SUPPORT PLANS Page 165 - 168



UPGRADE YOUR PRODUCT Page 169 - 170



GENUINE PARTS Page 171 - 179



AIR DISTRIBUTION Page 180

Download a QR Reader and scan the code for:

"Atlas Copco Service solutions to optimize the Compressor room"



Save energy

Compressed air is one of the most important utilities in the industry. It is also one of the largest consumers of energy.

With their detailed and extensive knowledge of compressed air, our energy and air consultant engineers will be able to determine an acceptable operating balance, that is both within the capabilities of your compressors and also adequate to satisfy your production with minimized operational running costs.

Maximize the performance of your compressor

Based on an audit of your production processes Atlas Copco consultants can suggest a more performing set-up for your compressed air installation, with an eye on maximum availability at lowest possible cost.

Atlas Copco logical sequence towards sustainable energy savings:

1. Pre-assessment

to estimate savings potentials

2. AIRScan energy assessments/audits

to identify savings potentials through measurement and simulations

3. Recommendations

to prepare your system for the optimization by exchanging the latest, most efficient components

4. Optimize

to achieve the savings by implementation of energy saving accessories and solutions

5. Online monitoring

to ensure the solution implemented is delivering the savings as prescribed

6. Regular AIRScan energy assessments/audits

to validate after the improvements and find further saving potentials



AIRScan -Tangible information for real solutions

A clear understanding of the changing demands over time is a corner stone in any process of system optimization. Defining the limitations of your current compressed air system is the key to finding the best solution to achieving energy efficiency for your business.

Understanding your Compressed Air Systems

A thorough survey of the compressed air system dynamics, including logging and analysing all the air net key parameters allows you to determine the right operating balance and to identify the energy savings potentials.

Using the logged information, our compressed air experts will provide a comprehensive and fully detailed report, including cost analysis, graphs and the starting points towards improving the compressed air system. At the end of the survey you will have



a valuable document stating the "real status" of your system's performance, including recommendations to finally achieve sustainable energy savings.

Air optimization -Reduce your energy consumption

Efficient compressor management is the fastest way to achieve energy savings. Each 1 bar (14.5 psi) reduction in working pressure results in 7% direct energy savings and further 3% is saved through leak reduction. Our range of ES Central Controllers will enable you to link all compressors and dryers, lower your overall pressure band, eliminate the need for higher working pressure and optimize the compressor mix at all times.

Using advanced control systems, you can maximize energy savings by:

- Regulating the system pressure within a pre defined and narrow pressure band.
- Scheduling shutdown to avoid costs during non production hours.
- Equalizing workload to avoid overloads on individual machines.



- Reducing maintenance costs thanks to comprehensive, flexible machine sequence control.
- The result is a properly managed compressed air system that can save energy, reduce maintenance cost and increase uptime.



Heat recovery system -

By recovering rejected heat and reusing it in your production cycle, allows you to further improve the overall efficiency of any compressed air system and to reduce your plant's total energy consumption.

Through the compression process, part of the energy is lost as radiation. Atlas Copco's Energy Recovery unit is able to extract an amount of energy from compressed air that is equivalent to the amount of energy that the electric motor uses.

The most common uses for the recovered energy include process heating, space heating and water heating.





Monitor your products

SMARTLINK is: an easy to install, efficient to monitor, easy tailored compressor monitoring program. It offers your company a complete insight of your compressed air production. It helps to predict potential problems (and thus anticipate them); it shows how and where the production can be optimized and energy can be saved. **SMART**LINK is as flexible and informative as you want it to be. Choose from 3 levels which solution best fits your company.



Rule out all uncertainties. With **SMARTLINK** Service installed on your compressors, scheduling of maintenance visits becomes as simple and easy as it should be; your service log book is always just one click away and your online link with Atlas Copco allows you to request and receive quotes for spare parts or additional services very fast.

Keep your compressors up and running. By e-mail and/or text you receive all relevant machine indications (warnings and shutdowns) in advance. Based on this information you then can take all necessary actions and measures to avoid the risk of a breakdown.

Safeguard the performance of your equipment. With **SMARTLINK** Energy Atlas Copco enables you to continuously monitor and analyze the energy efficiency of your compressor room. You decide on the performance indicators, you define the benchmarks. SMARTLINK analyzes and reports. You can make accurate and immediate improvements when needed. The results can be used for energy monitoring according to ISO50001.







Customer support plans

What you need is a solution to keep your production optimal at all time and preferably at the lowest operating cost. Our specialized advisors will visit your production facilities and assess your specific needs. This allows us to propose the most cost effective Customer Support Plan for your maintenance needs.

Ways to ease your mind:

• We leave it in your hands

We deliver the necessary spare parts and leave the actual maintenance up to you. We check your compressed air system regularly and identify the necessary actions. The output of each inspection is a complete diagnostic report.

• We give you a hand:

We service your compressed air system at predetermined intervals to lower the risk of unexpected problems and keep your production process optimal at all times. The routine maintenance costs are fixed, which allows you to easily forecast them.

• You hand it to us:

We service your compressed air installation following a complete maintenance system that covers all breakdowns. Your equipment will be kept in prime condition at any time and the

We leave it in your hands -Parts-Only Preventive Maintenance Plan

This Plan covers all parts required to service your Atlas Copco machine as per the recommendations found in the instruction manual. Parts are delivered to you at the correct intervals and in a pro-active manner.

Features & benefits:

• Improved equipment reliability thanks to the genuine Atlas Copco parts and lubricants



annual costs for the agreed period are fixed. This includes all the required parts, labour and travel expenses. There are no hidden surprises. **You have total peace of mind.**

- Timely delivery of all required service kits reducing your administration
- Guaranteed parts availability allowing you to eliminate expensive stock

We give you a hand -Service at predetermined intervals

Preventative Maintenance Plan

This Plan covers all regular maintenance for your compressed air equipment in a proactive manner. Certified and trained Atlas Copco service technicians use genuine parts and lubricants to maintain your installation as it should be. This is the best way to lower the risk of unexpected problems allowing you to optimize your production process. The plan can be customized and adjusted at any time.



- Improved equipment reliability thanks to genuine parts and expert technicians
- Stable costs up front helping you balance your maintenance budget
- Eliminate stock and administration by letting the experts take care of it

Inspection Plan:

A compressed air system can only be managed efficiently if the right data is available. Atlas Copco's Inspection Plan consists of regular inspection visits to identify any actions required to keep your compressed air system in prime operating condition. The output of the Inspection Plan is a complete diagnostic report, from which any work related to subsequent improvements can be quoted separately, allowing you to follow separate approval flows.

Benefits:

- No surprises, fixed yearly fee to perform the inspections including all labour and travel costs
- Improved equipment reliability thanks to regular follow-ups by the experts
- Comprehensive diagnostic report after each inspection visit



Fixed Price Services for Regular Maintenance:

From machine inspections to labour intensive recommended visits, Fixed Price Services offer you a clear path to maintaining your compressed air installation. Atlas Copco's trained technicians arrive at your door with all required parts to get the job done. They ensure that your machine runs in it's most efficient way, with lower energy consumption and less risk of unexpected costs due to failures.

Benefits:

- No surprises, one fixed price to perform the work including all travel, material and labour costs
- All manufacturer recommended service activity list done and comprehensive diagnostics report after each visit
- Reduce administration and inventory by letting Atlas Copco take care of it

Fixed Price Services for Overhaul

As the owner of Atlas Copco equipment, you are already familiar with its unique design features that help to achieve high reliability and the lowest total cost of ownership. Overhaul performed after years of equipment operation helps to keep initial reliability and efficiency. Atlas Copco's trained technicians arrive at your door with all required parts to get the job done, and leave you knowing that your machine is in nearly brand new condition.

Benefits:

- All manufacturer recommended service activity list to keep reliability and efficiency as from day one
- Competent Atlas Copco technicians to perform such a crucial work
- No surprises, one fixed price to perform the overhaul to avoid subsequent downtime and production lost





You hand it to us -Complete maintenance system

Total Responsibility Plan

This Plan lives up to its name – total peace-of-mind with full coverage of the unit including: air ends, motor, electrical and electronic systems, coolers. The program consists of certified Atlas Copco technicians providing you with all regular maintenance, engineering improvements, breakdown repairs and machine overhauls. It is a complete maintenance system with fixed annual costs for the agreed period.

Benefits:

• Use of genuine parts and expert technicians for complete coverage including overhauls and unfortunate breakdowns

• Stable costs removing all surprises as you balance your maintenance budget

• Eliminate stock and administration by letting the experts take care of it



AIRXtend

Atlas Copco's AIRXtend program is a five (5) year protection plan to maintain your system with fixed annual costs. This warranty extension is supported by the use of certified Atlas Copco technicians to perform all preventative maintenance for your system at the correct interval and in a proactive manner. Relax knowing that only the highest quality spare parts and consumables are used, originating from the same factories as your equipment.

Benefits:

- Use of genuine parts and expert technicians extending your warranty to five years
- Stable costs up front helping you balance your maintenance budget
- Eliminate stock and administration by letting the experts take care of it



Upgrade your product

Our upgrade kits are the result of continuous engineering work to make the latest technology available for your existing equipment range. This will inevitably improve the key performance features such as energy consumption and reliability. Intelligent use and the sustained health of core parts are the basic requirements for the lifelong optimum availability of your equipment.

Upgrade programs Make use of the latest technology

Upgrades take advantage of the most recent computer technology and of the progress in sophisticated compressor control software.

These upgrades increase the reliability and availability of your equipment. Furthermore, upgrading your compressor system will

result in substantial energy savings, while the cost will in most cases be equivalent to or even less than a replacement of older control systems.

Benefits:

• Optimized performance

With the portfolio of upgrades your machines will be equiped with the latest available options, allowing you to make substantial energy savings.

Enhanced reliability

Upgrade kits focus on reliable performance of critical components and increased reliability will allow your equipment to reach a longer lifetime.

Increased availability

With upgrades, availability is increased thanks to automated control and preventive replacement of all essential components. This means that the continuity of your process is not jeopardized by unnecessary downtime.



The Elektronikon® controller is at the height of technology in sophisticated compressor control software. An upgrade will improve the overall reliability and uptime of your equipment, and extend connectivity to modern plant control systems.

Xchange programs Replace major components with new more efficient components

The Xchange Program offers you the possibility to replace major components of your compressor with new more efficient components.

Motor xchange program:

Energy consumption is the major cost in the total life cycle cost of any compressor. Under the Xchange Motor Program, the latest high efficiency motors are used to replace old less efficient motors or failed motors that require rewinding.

These new motors come complete with adaptation components making the exchange a quick exercise. The energy savings with the new motors are guaranteed.

Element xchange program:

The overhaul is arranged in advance based on the expected life of the compressor element and condition monitoring. This proactive planning ensures that there is a reduced risk of faillure and prevents production loss. The combination of Atlas Copco genuine parts and skilled expertise by Atlas Copco engineers ensures that overhauled elements are restored to their original highly performance levels, increasing your profitability.

Converter xchange program:

The Xchange Converter program is a one step replacement solution to upgrade Atlas Copco VSD compressors with new variable speed drives. The lifecycle of a variable speed drive progresses from active phase to the obsolete phase in just a few years. Towards the obsolete phase the converters become difficult and expensive to repair.

The Converter Xchange program easily overcomes this difficulty and ensures that the customer's equipment is back in operation after a minimal intervention period.







Genuine parts

Our upgrade kits are the result of continuous engineering work to make the latest technology available for your existing equipment range. This will inevitably improve the key performance features such as energy consumption and reliability. Intelligent use and the sustained health of core parts are the basic requirements for the lifelong optimum availability of your equipment.

The advantages of using Atlas Copco's genuine parts:

• Longer life expectancy

Regularly servicing your equipment using genuine spare parts ensures that your installation **will last longer**. We guarantee that each new component performs equally well as the part it replaces.

• Superior quality

Our genuine parts are manufactured to the same exacting standards as your installed compressor. They have passed the same endurance tests and proven to be the best protection for your investment.

• Reliability and productivity

Using genuine parts substantially lowers the risk of a production breakdown, which would not only be very costly, but could also endanger your product quality, deadlines and profit margins. In short, genuine parts offer optimal performance of your compressed air installation.

• Energy savings and cost effectiveness

Regular replacement of parts combined with the use of genuine Atlas Copco parts make your compressed air installation last longer and cause a minimal average pressure drop, which leads to energy savings and cost effectiveness and maximum air delivery at the lowest cost of ownership.

• World class logistics

The continuity of your production process can only be guaranteed when the quality spare parts arrive at the right place and the right time. With our genuine parts distribution system, operating 24/7, you can rest assured your production continuity is in safe hands.



Lubricants



Greases



Maintainance kits





Line Filters

Lubricants

Engineered to protect



Atlas Copco lubricants are engineered with the exact right selection of additives that interact in just the right proportion to obtain optimal performance. The additives not only support the base lubrication requirements, they also interact in multi processes in the compressor.

The properties of quality:

All our efforts are aimed at optimizing the performance of your Atlas Copco compressor for the longest lifetime at the **lowest operating cost**.

The experts in our laboratories are uniquely skilled in specifying lubricant properties for Atlas Copco compressors to operate optimally in a wide range of settings and conditions, during several thousands of hours.

Atlas Copco lubricants are a unique blend of chemical properties, engineered for **optimal performance** in their dedicated functions.

Atlas Copco Fluids for screw compressors:

Roto-Inject Fluid

Atlas Copco Roto-Inject Fluid is specially formulated to protect your GA-GX rotary screw compressors and neutralize pollution. It guarantees the longest lifetime, trouble free, with constant performance, at the best operating cost.

Years of experience on thousands of types of Atlas Copco equipment have proven Roto-Inject Fluid to match all lubrication demands in varied conditions. It boasts an extended service interval of up to 4 000 hours for operation in a mild environment. This is critical to achieve the best reliability and reduce the service lifetime cost.



Roto-Xtend Duty Fluid:

When your air compressors need to perform at top capacity, only the Atlas Copco lubricant is good enough. That's why it pays to use Roto-Xtend Duty Fluid. Atlas Copco superior performance long life PAO oil, specifically developed for use in Atlas Copco oil injected screw compressors.

Based on synthetic hydrocarbons and special additives, our engineered.

8 000 h lubricant has proven its ability to meet all lubrication demands under widely varying conditions. Roto-Xtend Duty Fluid increases compressor reliability, reduces lifetime operating costs and makes your equipment last longer.

Roto-Food Grade Fluid

Roto-Foodgrade Fluid is a high performance fluid specifically designed for use in oil injected screw compressors operating in the food and beverage and packing industry. National and international regulations specify strict manufacturing standards regarding contamination risk management in this industry.

Our Roto foodgrade is based on a careful blend of synthetic fluids and additives that meet these stringent requirements , allowing for active Critical Control Points management (in an HACCP system) and providing increased customer confidence in the food products' safety.



Atlas Copco Fluids for piston compressors:

Piston Fluid

Piston compressors pose extreme demands to lubricants: the high compression temperature - possibly exceeding 150°C (300°F) - pressures up to 20 bar, condensation - typically during low cycle load - and dust contamination in installations that are not optimally maintained.

Traditional lubricants cannot cope with these extreme conditions, resulting in fast oil degradation, overheating and potentially irreversible damage and high repair costs. Therefore, high performing lubricants increase the equipment lifetime. The Atlas Copco Piston Fluid has been developed as a high resistance lubricant, withstanding severe conditions, with a long service interval and superior performance.

Considering the low oil content in piston compressors, often less than 2 liters, the economy of lesser quality oils simply is not worth the risk.



HiPER Fluid

HiPER Fluid is a premium quality reciprocating compressor lubricant, which has been developed for and tested in Atlas Copco's high pressure reciprocating compressors (product lines Intermech and GreenField)

Applications: Compressed Natural Gas Compressors Industrial Gas Compressors

HiPER Fluid meets the most stringent qualification in order to increase the performance and life time of your investment. The oil is specifically blended to handle local variations in gas composition.



Automan Fluid

Automan piston compressors pose extreme demands to lubricants: the high compression temperature, possibly exceeding 150°C (300°F), pressures up to 20 bar, condensation - typically during low cycle load - and dust contamination in installations that are not optimally maintained.

Traditional lubricants cannot cope with these extreme conditions, resulting in fast oil degradation, overheating and potentially irreversible damage and high repair costs. Therefore, high performing lubricants increase the equipment lifetime. The Atlas Copco Automan Fluid has been developed as a high resistance lubricant, withstanding severe conditions, with a long service interval and superior performance.

Considering the low oil content in piston compressors, often less than 2 liters, the economy of lesser quality oils is simply not worth the risk.

Atlas Copco Lubricants

Roto-Z

Roto-Z is a high quality lubricant, uniquely tailored to the specific requirements of the Atlas Copco Z-compressors. Its special formulation yields top performance and maximum lifetime of all moving parts. Reliability is safeguarded and equipment availability is maximal.

Roto-Z is cost-effective too: drain intervals are doubled in comparison to conventional lubricants. Roto-Z incorporates the functional benefits of a preservative mineral oil, which allows for an extended on-site storage of several months.

Roto-H Plus

Roto-H Plus is a unique lubricant, especially created for Atlas Cocpo oil-free centrifugal ZH compressors. The heavy-duty blend provides optimum lubrication of the compressor sleeve bearings. In addition, Roto-H Plus guarantees top performance and maximum durability of all other moving parts. This improved reliability translates into maximum equipment uptime.

It is a highly cost-effective lubricant: drain intervals can extend up to 24 000 hours* with only a 6-monthly oil analysis in between.

* Subject to normal operating conditions.





UTOMA



Roto-M

Roto-M is your best safeguard for good hypoid gear lubrication . It is a heavy -duty , high-viscosity blend, formulated specifically for the gear boxes on Atlas Copco MD absorption air dryers.

Roto-M provides the high film strength required in hypoid gear applications. It minimizes wear and tear and guarantees optimum lubrication of the MD worm gear drive, under all operating conditions. Its superior reliability translates into maximum equipment uptime.

Recip Oil

Recip Oil is a unique lubricant, especially created for Atlas Copco oil-free reciprocating compressors and boosters. The special blend provides optimum lubrication for high pressure applications and guarantees top performance and maximum durability of all moving parts. This improved reliability translates into maximum equipment uptime.

Greases Engineered to protect

To help your compressor perform to its optimal design standards, you need a grease that stays in place and provides effective protection and lubrication under challenging conditions. The longer the grease lasts, the longer the motor last, and the less lubrication maintenance for your compressor. With a full product range of Roto-Glide greases, you can select the grease to meet your specific requirements.

Roto-Glide:

Roto-Glide sets a new, high standard in motor bearing lubrication. Its special heavy-duty formulation provides improved bearing protection at higher operating temperatures. Because of its greater stability, Roto-Glide permits extended motor greasing intervals of up to 4 000 hours depending on the type and use of the motor.

Roto-Glide guarantees optimum lubrication of the electric motors used in Atlas Copco Z- and G-series air compressors. Improved reliability translated into maximum equipment uptime.





Maintenance kits

The parts you need, when you need them

Save time getting the right parts

The Service kits supplied by Atlas Copco contain every item down to the last gasket. Just think of the time saved; time that without a service kit would be wasted checking different sources to get a complete set of the parts you need.

Covers your complete maintenance needs

Service kits contain all the parts needed as part of a scheduled maintenance program. So from now on you can rely on one single source for all your spare parts. When installed by an Atlas Copco technician, his experience and training will keep downtime to the minimum and ensures your equipment will be kept in top condition throughout its operating life.



Advanced technology for clean condensate

For assured performance and maximum maintenance intervals, the specially designed OSC service kits are highly recommended. Each kit is designed to make life as easy and simple as possible, providing all the equipment needed for a fast, clean and trouble free element changeover.



Line Filters Compressed Air Filters

Product description

TBuilding on many years of experience in compressed air solutions and trough continuous in-depth research and testing, Atlas Copco has developed a complete range of top-of-the-bill DD, DDp, PD, PDp and QD filters according to the latest international standards which efficiently reduce all types of contamination with minimal pressure drop.



Filters Protect your investment **Compressor oil filtration**

Dust and dirt contaminating the compressor oil can lead to damage to or performance losses for rotors and their housings. Since the same oil lubricates the compressor element bearings, damage to these vital components could potentially lead to rotor contact and service.failure.

Genuine Atlas Copco compressor oil filters have high performance and are composed of specific filter elements. Features include high-grade filtration efficiency, temperature resistance, and resistance to synthetic oils. Built to withstand high operating pressures, Atlas Copco filters have superior service life, thanks to their high dirt holding capacity.

Compressor air filtration

Compressor rotors operate with minimal clearances, guaranteeing high performance. However, dirt particles can cause damage, reducing performance and potentially increasing operating costs. To safeguard the high-tech screw element at the heart of your investment, Atlas Copco focused on the intake air filtration system.

Atlas Copco uses special filtration elements to prevent contaminants from passing into the compressor. Yet, we designed them to allow the volume of air to freely flow into the machine. Parts from other manufacturers can never match the performance of these genuine Atlas Copco parts.

Compressor oil separation

Only genuine Atlas Copco replacement oil separator elements can offer extremely low oil carryover combined with low pressure differentials. This means better quality air and minimal operating costs through lower oil consumption and longer service life of fine filters installed downstream.







AIRnet Compressed air piping system

AIRnet is a compressed air piping system that delivers quality air exactly where you need it, from compressor to the point of use. The unique benefits of AIRnet effectively reduce the cost of ownership of your piping system. Discover AIRnet at www.airnet-system.com

Customer benefits:

- AIRnet provides optimum air quality at the point of use
- **FAST** AlRnet saves you 70 % on installation time vs. traditional piping systems.
- **EASY** 3 simple steps: CUT to length and deburr. INSERT in the fitting on the marked depth. SECURE and tighten correctly.
- **RELIABLE** All AlRnet products come with a 10-year warranty on all fittings and pipes, against any damages resulting from material defect.

www.airnet-system.com



www.atlascopco.com